



# Safety Data Sheet

Issue Date 14-Aug-2018

Revision Date 13-Aug-2018

Revision Number 14

## 1. IDENTIFICATION

### Product identifier

**Product Code** F066-00WHA  
**Product Name** H-B EPOXOLINE TNEMEC WHITE

### Other means of identification

**Common Name** SERIES 66, PART A  
**UN/ID no.** 1263  
**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

**Manufacturer Address** Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372 816-474-3400  
**Distributor** Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

### OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 2
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable Liquids	Category 3

### Label elements

## EMERGENCY OVERVIEW

### **Danger**

### **Hazard statements**

Causes skin irritation  
Causes serious eye damage  
May cause an allergic skin reaction  
Suspected of causing cancer

Suspected of damaging fertility or the unborn child  
 May cause respiratory irritation. May cause drowsiness or dizziness  
 Causes damage to organs through prolonged or repeated exposure  
 May be fatal if swallowed and enters airways  
 Flammable liquid and vapor



**Appearance** viscous liquid opaque

**Physical state** liquid

**Odor** aromatic

### Precautionary Statements

#### Prevention

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Wash face, hands and any exposed skin thoroughly after handling  
 Do not eat, drink or smoke when using this product  
 Use only outdoors or in a well-ventilated area  
 Contaminated work clothing should not be allowed out of the workplace  
 Wear protective gloves  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Keep cool  
 Use explosion-proof electrical/ventilating/lighting/equipment

#### Response

IF exposed or concerned: Get medical advice/attention  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 Immediately call a POISON CENTER or doctor/physician  
 If skin irritation or rash occurs: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Rinse mouth  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do NOT induce vomiting  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

#### Storage

Store locked up  
 Store in a well-ventilated place. Keep container tightly closed  
 Keep away from children

#### Disposal

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

##### Other information

Harmful to aquatic life with long lasting effects  
 SEE SAFETY DATA SHEET

Acute Toxicity

14.13200652 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
BARIUM SULFATE (TOTAL DUST)	7727-43-7	10 - <30%
TITANIUM DIOXIDE (TOTAL DUST)	13463-67-7	10 - <30%
TALC (RESPIRABLE DUST)	14807-96-6	10 - <30%
XYLENE	1330-20-7	10 - <30%
N-BUTANOL (SKIN)	71-36-3	1 - <10%
ETHYL BENZENE	100-41-4	1 - <10%
ETHYLBENZENE	100-41-4	1 - <10%
AMORPHOUS SILICA	7631-86-9	1 - <10%
TRIETHYLENE TETRAMINE	112-24-3	0.1 - <1%
BENZENE, 1,3-DIMETHYL	108-38-3	0.1 - <1%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

#### Description of first aid measures

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Call a physician immediately.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Call a physician immediately.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

#### Most important symptoms and effects, both acute and delayed

**Notes to physician** Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

#### Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Water.

#### Specific hazards arising from the chemical

Flammable liquid Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Nitrogen oxides (NOx). Aldehydes.

#### Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Use personal protective equipment. Avoid contact with eyes, skin and clothing. Remove all sources of ignition. Ensure adequate ventilation.

### Environmental Precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

### Methods and material for containment and cleaning up

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Wear personal protective equipment. Avoid contact with eyes, skin and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not breathe vapours or spray mist. In case of insufficient ventilation, wear suitable respiratory equipment. Do not ingest. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

### Conditions for safe storage, including any incompatibilities

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

**Incompatible products** Strong oxidizing agents. Acids. Cleaning solutions such as Chromerge and Aqua Regia. Water, alcohols, amines, strong bases, metal components, surface active materials.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
BARIUM SULFATE (TOTAL DUST) 7727-43-7	TWA: 5 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> TWA: 15 mg/m <sup>3</sup>	
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 15 mg/m <sup>3</sup>	5000 mg/m <sup>3</sup>
TALC (RESPIRABLE DUST) 14807-96-6	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	1000 mg/m <sup>3</sup>
XYLENE 1330-20-7	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 150 ppm STEL: 655 mg/m <sup>3</sup>	

N-BUTANOL (SKIN) 71-36-3	TWA: 20 ppm	Skin Ceiling: 50 ppm Ceiling: 150 mg/m <sup>3</sup> TWA: 100 ppm TWA: 300 mg/m <sup>3</sup>	1400 ppm
ETHYL BENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>	800 ppm
ETHYLBENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>	800 ppm
AMORPHOUS SILICA 7631-86-9	-	TWA: 6 mg/m <sup>3</sup>	3000 mg/m <sup>3</sup>
BENZENE, 1,3-DIMETHYL 108-38-3	TWA: 100 ppm STEL: 150 ppm	-	900 ppm

**Appropriate engineering controls****Engineering measures**

Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.

**Skin and body protection**

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection**

Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations**

Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing before re-use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	aromatic
<b>Appearance</b>	viscous liquid opaque	<b>Odor threshold</b>	No information available
<b>Color</b>	opaque		

**Property****Values****Remarks****pH****Melting point / freezing point**

No data available

**Boiling point / boiling range**

116 °C / 241.0 °F

**Flash point**

28 °C / 82.0 °F

Seta closed cup

**Evaporation rate****Flammability (solid, gas)**

No data available

**Flammability Limit in Air**

Upper flammability limit	NA
Lower flammability limit	NA
Vapor pressure	
Vapor density	
Specific gravity	1.7125
Water solubility	insoluble
Solubility in other solvents	
Partition coefficient: n-octanol/water	
Autoignition temperature	No data available
Decomposition temperature	
Kinematic viscosity	
Dynamic viscosity	

**Other Information**

Density	14.28229 lbs/gal
Volatile organic compounds (VOC) content	3.1421 lbs/gal
Total volatiles weight percent	22 %
Total volatiles volume percent	44.57 %
Bulk density	No information available

## 10. STABILITY AND REACTIVITY

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks. Epoxy constituents.

**Incompatible materials**

Strong oxidizing agents, Acids, Cleaning solutions such as Chromerge and Aqua Regia, Water, alcohols, amines, strong bases, metal components, surface active materials

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Aldehydes. Nitrogen oxides (NOx).

## 11. TOXICOLOGICAL INFORMATION

**Information on Likely Routes of Exposure**

<b>Inhalation</b>	Symptoms of overexposure are dizziness, headache, tiredness, nausea, unconsciousness, cessation of breathing. Vapors may irritate throat and respiratory system.
<b>Eye contact</b>	Causes serious eye damage.
<b>Skin contact</b>	Irritating to skin. May cause sensitization by skin contact.
<b>Ingestion</b>	Harmful if swallowed. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Chemical name	LD50 Oral	LD50 Dermal	LC50 Inhalation
BARIUM SULFATE (TOTAL DUST)	= 307000 mg/kg ( Rat )	-	-

7727-43-7			
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	> 10000 mg/kg ( Rat )	-	-
XYLENE 1330-20-7	= 3500 mg/kg ( Rat )	> 1700 mg/kg ( Rabbit ) > 4350 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h = 5000 ppm ( Rat ) 4 h
N-BUTANOL (SKIN) 71-36-3	= 700 mg/kg ( Rat ) = 790 mg/kg ( Rat )	= 3400 mg/kg ( Rabbit ) = 3402 mg/kg ( Rabbit )	> 8000 ppm ( Rat ) 4 h
ETHYL BENZENE 100-41-4	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.4 mg/L ( Rat ) 4 h
ETHYLBENZENE 100-41-4	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.4 mg/L ( Rat ) 4 h
AMORPHOUS SILICA 7631-86-9	= 7900 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 2.2 mg/L ( Rat ) 1 h
TRIETHYLENE TETRAMINE 112-24-3	= 2500 mg/kg ( Rat )	= 550 mg/kg ( Rabbit )	-
BENZENE, 1,3-DIMETHYL 108-38-3	= 5 g/kg ( Rat )	= 12.18 g/kg ( Rabbit ) = 14100 µL/kg ( Rabbit )	= 5984 ppm ( Rat ) 6 h

**Information on toxicological effects**

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin disorders.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** May cause sensitization of susceptible persons.

**Mutagenicity** May cause genetic defects.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7		Group 2B	-	X
TALC (RESPIRABLE DUST) 14807-96-6		Group 2B Group 3	-	
XYLENE 1330-20-7		Group 3	-	
ETHYL BENZENE 100-41-4	A3	Group 2B	-	X
ETHYLBENZENE 100-41-4	A3	Group 2B	-	X
AMORPHOUS SILICA 7631-86-9		Group 1 Group 3	Known	
BENZENE, 1,3-DIMETHYL 108-38-3		Group 3	-	

IARC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

**Reproductive effects** Suspected of damaging fertility or the unborn child.

**STOT - single exposure** May cause disorder and damage to the, Eyes, Skin, Central Nervous System (CNS)

**STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure

**Target organ effects** blood, Central nervous system, Central Vascular System (CVS), Gastrointestinal tract, Eyes, kidney, liver, respiratory system, Skin.

**Aspiration hazard** Risk of serious damage to the lungs (by aspiration).

**Acute Toxicity** 14.13200652 % of the mixture consists of ingredient(s) of unknown toxicity.

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

Harmful to aquatic life with long lasting effects

16.02679 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
TALC (RESPIRABLE DUST)		100: 96 h Brachydanio rerio g/L	

14807-96-6		LC50 semi-static	
XYLENE 1330-20-7		LC50= 13.4 mg/L Pimephales promelas 96 h LC50 2.661 - 4.093 mg/L Oncorhynchus mykiss 96 h LC50 13.5 - 17.3 mg/L Oncorhynchus mykiss 96 h LC50 13.1 - 16.5 mg/L Lepomis macrochirus 96 h LC50= 19 mg/L Lepomis macrochirus 96 h LC50 7.711 - 9.591 mg/L Lepomis macrochirus 96 h LC50 23.53 - 29.97 mg/L Pimephales promelas 96 h LC50= 780 mg/L Cyprinus carpio 96 h LC50> 780 mg/L Cyprinus carpio 96 h LC50 30.26 - 40.75 mg/L Poecilia reticulata 96 h	EC50 = 3.82 mg/L 48 h LC50 = 0.6 mg/L 48 h
N-BUTANOL (SKIN) 71-36-3	500: 72 h Desmodemus subspicatus mg/L EC50 500: 96 h Desmodemus subspicatus mg/L EC50	1730 - 1910: 96 h Pimephales promelas mg/L LC50 static 100000 - 500000: 96 h Lepomis macrochirus µg/L LC50 static 1740: 96 h Pimephales promelas mg/L LC50 flow-through 1910000: 96 h Pimephales promelas µg/L LC50 static	1897 - 2072: 48 h Daphnia magna mg/L EC50 Static 1983: 48 h Daphnia magna mg/L EC50
ETHYL BENZENE 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 32: 96 h Lepomis macrochirus mg/L LC50 static 9.6: 96 h Poecilia reticulata mg/L LC50 static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static	1.8 - 2.4: 48 h Daphnia magna mg/L EC50
ETHYLBENZENE 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 32: 96 h Lepomis macrochirus mg/L LC50 static 9.6: 96 h Poecilia reticulata mg/L LC50 static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static	1.8 - 2.4: 48 h Daphnia magna mg/L EC50
AMORPHOUS SILICA 7631-86-9	440: 72 h Pseudokirchneriella subcapitata mg/L EC50	5000: 96 h Brachydanio rerio mg/L LC50 static	7600: 48 h Ceriodaphnia dubia mg/L EC50
TRIETHYLENE TETRAMINE 112-24-3	2.5: 72 h Desmodemus subspicatus mg/L EC50 20: 72 h Pseudokirchneriella subcapitata mg/L EC50 3.7: 96 h Pseudokirchneriella subcapitata mg/L EC50	570: 96 h Poecilia reticulata mg/L LC50 semi-static 495: 96 h Pimephales promelas mg/L LC50	31.1: 48 h Daphnia magna mg/L EC50
BENZENE, 1,3-DIMETHYL 108-38-3	4.9: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	14.3 - 18: 96 h Pimephales promelas mg/L LC50 flow-through 8.4: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 12.9: 96 h Poecilia reticulata mg/L LC50 semi-static	2.81 - 5.0: 48 h Daphnia magna mg/L EC50 Static

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

Chemical name	log Pow
XYLENE	2.77



1330-20-7	
N-BUTANOL (SKIN) 71-36-3	0.785
ETHYL BENZENE 100-41-4	3.118
ETHYLBENZENE 100-41-4	3.2
TRIETHYLENE TETRAMINE 112-24-3	-1.4
BENZENE, 1,3-DIMETHYL 108-38-3	3.2

**Other Adverse Effects** No information available

### 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

##### Disposal Methods

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

##### Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
XYLENE 1330-20-7		Included in waste stream: F039		U239
N-BUTANOL (SKIN) 71-36-3		Included in waste stream: F039		U031
ETHYL BENZENE 100-41-4		Included in waste stream: F039		
ETHYLBENZENE 100-41-4		Included in waste stream: F039		

Chemical name	CAWAST
XYLENE 1330-20-7	Toxic Ignitable
N-BUTANOL (SKIN) 71-36-3	Toxic
ETHYL BENZENE 100-41-4	Toxic Ignitable
ETHYLBENZENE 100-41-4	Toxic Ignitable

### 14. TRANSPORT INFORMATION

#### DOT

UN/ID no. 1263  
 Proper Shipping Name PAINT  
 Hazard Class 3  
 Packing Group III  
 Emergency Response Guide Number 128

#### Additional information

Call TNEMEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

### 15. REGULATORY INFORMATION

**International Inventories**

<b>TSCA</b>	Complies
<b>DSL/NDSL</b>	Complies
<b>EINECS/ELINCS</b>	Does Not Comply
<b>ENCS</b>	Does Not Comply
<b>IECSC</b>	Complies
<b>KECL</b>	Complies
<b>PICCS</b>	Does Not Comply
<b>AICS</b>	Complies

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**IECSC** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

**The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):**

<b>Chemical name</b>	<b>HAPS Data</b>
XYLENE	
ETHYL BENZENE	
ETHYLBENZENE	
BENZENE, 1,3-DIMETHYL	

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

Chemical name	SARA 313 - Threshold Values
BARIUM SULFATE (TOTAL DUST) - 7727-43-7	1.0
XYLENE - 1330-20-7	1.0
N-BUTANOL (SKIN) - 71-36-3	1.0
ETHYL BENZENE - 100-41-4	0.1
ETHYLBENZENE - 100-41-4	0.1
BENZENE, 1,3-DIMETHYL - 108-38-3	1.0

**SARA 311/312 Hazardous**

**Categorization**

<b>Acute Health Hazard</b>	Yes
<b>Chronic Health Hazard</b>	Yes
<b>Fire Hazard</b>	Yes
<b>Sudden Release of Pressure Hazard</b>	No
<b>Reactive Hazard</b>	No

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE 1330-20-7	100 lb			X
ETHYL BENZENE 100-41-4	1000 lb	X	X	X
ETHYLBENZENE 100-41-4	1000 lb	X	X	X
BENZENE, 1,3-DIMETHYL 108-38-3				X

Chemical name	Hazardous Substances RQs	CERCLA EHS RQs	RQ
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
N-BUTANOL (SKIN) 71-36-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
ETHYL BENZENE 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

ETHYLBENZENE 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
BENZENE, 1,3-DIMETHYL 108-38-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

**California Prop. 65**

**WARNING:** This product can expose you to the following chemicals which are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Chemical name	California Prop. 65
TITANIUM DIOXIDE (TOTAL DUST) - 13463-67-7	Carcinogen
ETHYL BENZENE - 100-41-4	Carcinogen
ETHYLBENZENE - 100-41-4	Carcinogen
AMORPHOUS SILICA - 7631-86-9	Carcinogen
BENZENE, 1,3-DIMETHYL - 108-38-3	*
BENZENE, 1,4-DIMETHYL - 106-42-3	*
BENZENE, 1,2-DIMETHYL - 95-47-6	*

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Chemical name	New Jersey	Massachusetts	Pennsylvania
BARIUM SULFATE (TOTAL DUST) 7727-43-7	X	X	X
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	X	X	X
TALC (RESPIRABLE DUST) 14807-96-6	X	X	X
XYLENE 1330-20-7	X	X	X
N-BUTANOL (SKIN) 71-36-3	X	X	X
ETHYL BENZENE 100-41-4	X	X	X
ETHYLBENZENE 100-41-4	X	X	X
AMORPHOUS SILICA 7631-86-9		X	X
TRIETHYLENE TETRAMINE 112-24-3	X	X	X
BENZENE, 1,3-DIMETHYL 108-38-3	X	X	X

**16. OTHER INFORMATION**

**NFPA** Health 2 Flammability 3 Instability 1 Physical hazard \*  
**HMIS (Hazardous Material Information System)** Health 2\* Flammability 3 Reactivity 1

Prepared By Tnemec Regulatory Dept: 816-474-3400  
 Revision Date 13-Aug-2018  
 Revision Summary  
 4 5 6 7 10 8 9 11 14 2 13 15


**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot

guarantee that these are the only hazards which exist.

**End of SDS**



# Safety Data Sheet

Issue Date 29-Aug-2018

Revision Date 15-Aug-2018

Revision Number 16

## 1. IDENTIFICATION

### Product identifier

**Product Code** B066-0066B  
**Product Name** 65/66/160/161 CONVERTER

### Other means of identification

**Common Name** SERIES 66/161, PART B  
**UN/ID no.** 1263  
**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372 816-474-3400

#### **Distributor**

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

#### **Emergency telephone number**

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 2
Reproductive Toxicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Flammable Liquids	Category 2

### Label elements

## EMERGENCY OVERVIEW

### **Danger**

#### **Hazard statements**

Causes serious eye irritation  
Suspected of causing cancer  
May damage fertility or the unborn child  
May cause respiratory irritation  
May cause damage to organs through prolonged or repeated exposure  
Highly flammable liquid and vapor

**Appearance** opaque**Physical state** liquid**Odor** Strong aromatic Petroleum distillates**Precautionary Statements****Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Wash face, hands and any exposed skin thoroughly after handling  
 Use only outdoors or in a well-ventilated area  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Keep cool  
 Use explosion-proof electrical/ventilating/lighting/equipment

**Response**

IF exposed or concerned: Get medical advice/attention  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store locked up  
 Store in a well-ventilated place. Keep container tightly closed  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

May be harmful in contact with skin  
 Causes mild skin irritation  
 Toxic to aquatic life with long lasting effects  
 SEE SAFETY DATA SHEET  
 Acute Toxicity

1.115E-05 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
TALC (RESPIRABLE DUST)	14807-96-6	30 - <60%
SOLID EPOXY RESIN	-	10 - <30%
METHYL ISOBUTYL KETONE	108-10-1	10 - <30%
EPOXY RESIN (LER)	25085-99-8	10 - <30%
XYLENE	1330-20-7	1 - <10%
ETHYL BENZENE	100-41-4	1 - <10%

BENZENE, 1,4-DIMETHYL	106-42-3	0.1 - <1%
BENZENE, 1,3-DIMETHYL	108-38-3	0.1 - <1%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

##### Description of first aid measures

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse thoroughly with plenty of water for at least 15 minutes. If eye irritation persists, consult a specialist.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Call a physician immediately.
<b>Inhalation</b>	Remove affected individual to fresh air. Treat symptomatically. If breathing is difficult, administer oxygen. If breathing has stopped give artificial respiration. Consult a physician.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

##### Most important symptoms and effects, both acute and delayed

**Notes to physician** Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

##### Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Aldehydes. Hydrocarbons.

##### Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

#### 6. ACCIDENTAL RELEASE MEASURES

##### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

##### Environmental Precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Handling** Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

**Conditions for safe storage, including any incompatibilities**

**Storage** Store locked up. Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children. Keep away from heat, sparks and flame. VAPORS MAY CAUSE FLASH FIRE. Use only in an area containing flame proof equipment. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation.

**Incompatible products** Incompatible with oxidizing agents. Bases. Acids. Amines.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

**Exposure guidelines**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
TALC (RESPIRABLE DUST) 14807-96-6	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	1000 mg/m <sup>3</sup>
METHYL ISOBUTYL KETONE 108-10-1	TWA: 20 ppm STEL: 75 ppm	TWA: 50 ppm TWA: 205 mg/m <sup>3</sup> STEL: 75 ppm STEL: 300 mg/m <sup>3</sup> TWA: 100 ppm TWA: 410 mg/m <sup>3</sup>	500 ppm
XYLENE 1330-20-7	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 150 ppm STEL: 655 mg/m <sup>3</sup>	
ETHYL BENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>	800 ppm
BENZENE, 1,4-DIMETHYL 106-42-3	TWA: 100 ppm STEL: 150 ppm	-	900 ppm
BENZENE, 1,3-DIMETHYL 108-38-3	TWA: 100 ppm STEL: 150 ppm	-	900 ppm

NIOSH IDLH: *Immediately Dangerous to Life or Health*



**Appropriate engineering controls**

**Engineering measures** Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.

**Skin and body protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection** Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations** Remove and wash contaminated clothing before re-use.

**9. PHYSICAL AND CHEMICAL PROPERTIES****Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	Strong aromatic
<b>Appearance</b>	opaque		Petroleum distillates
<b>Color</b>	No information available	<b>Odor threshold</b>	No information available

<b><u>Property</u></b>	<b><u>Values</u></b>	<b><u>Remarks</u></b>
pH		
<b>Melting point / freezing point</b>	No data available	
<b>Boiling point / boiling range</b>	114 °C / 237.0 °F	
<b>Flash point</b>	18 °C / 64.0 °F	Pensky Martens - Closed Cup
<b>Evaporation rate</b>		
<b>Flammability (solid, gas)</b>	No data available	
<b>Flammability Limit in Air</b>		No data available
<b>Upper flammability limit</b>	N/A	
<b>Lower flammability limit</b>	1.0	
<b>Vapor pressure</b>		
<b>Vapor density</b>		
<b>Specific gravity</b>	1.27974	g/cm3
<b>Water solubility</b>	Insoluble in cold water	
<b>Solubility in other solvents</b>		
<b>Partition coefficient: n-octanol/water</b>		
<b>Autoignition temperature</b>	No data available	
<b>Decomposition temperature</b>		
<b>Kinematic viscosity</b>		
<b>Dynamic viscosity</b>	600 centipoises	

**Other Information**

<b>Density</b>	10.67307 lbs/gal
<b>Volatile organic compounds (VOC) content</b>	2.89454 lbs/gal
<b>Total volatiles weight percent</b>	27.12 %
<b>Total volatiles volume percent</b>	42.01 %
<b>Bulk density</b>	No information available

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Possibility of hazardous reactions

None under normal processing.

### Conditions to avoid

Heat, flames and sparks.

### Incompatible materials

Incompatible with oxidizing agents, Bases, Acids, Amines

### Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Aldehydes. Hydrocarbons.

## 11. TOXICOLOGICAL INFORMATION

### Information on Likely Routes of Exposure

<b>Inhalation</b>	MAY CAUSE DROWSINESS AND DIZZINESS. Inhalation of vapors in high concentration may cause irritation of respiratory system. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Skin contact</b>	Irritating to skin. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.
<b>Ingestion</b>	Harmful if swallowed.

Chemical name	LD50 Oral	LD50 Dermal	LC50 Inhalation
METHYL ISOBUTYL KETONE 108-10-1	= 2080 mg/kg ( Rat )	= 3000 mg/kg ( Rabbit )	= 8.2 mg/L ( Rat ) 4 h
XYLENE 1330-20-7	= 3500 mg/kg ( Rat )	> 1700 mg/kg ( Rabbit ) > 4350 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h = 5000 ppm ( Rat ) 4 h
ETHYL BENZENE 100-41-4	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.4 mg/L ( Rat ) 4 h
BENZENE, 1,4-DIMETHYL 106-42-3	= 4029 mg/kg ( Rat )	-	= 4550 ppm ( Rat ) 4 h = 4740 ppm ( Rat ) 4 h
BENZENE, 1,3-DIMETHYL 108-38-3	= 5 g/kg ( Rat )	= 12.18 g/kg ( Rabbit ) = 14100 µL/kg ( Rabbit )	= 5984 ppm ( Rat ) 6 h

### Information on toxicological effects

**Symptoms** Symptoms of overexposure are dizziness, headache, tiredness, nausea, unconsciousness, cessation of breathing. Serious eye damage/eye irritation.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Chronic Toxicity** NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. May cause cancer. Substances known to impair fertility. Skin sensitizer.

**Sensitization** May cause sensitization of susceptible persons.  
**Mutagenicity** No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
TALC (RESPIRABLE DUST) 14807-96-6		Group 2B Group 3	-	
METHYL ISOBUTYL KETONE 108-10-1	A3	Group 2B	-	X
XYLENE 1330-20-7		Group 3	-	
ETHYL BENZENE 100-41-4	A3	Group 2B	-	X
BENZENE, 1,4-DIMETHYL 106-42-3		Group 3	-	
BENZENE, 1,3-DIMETHYL 108-38-3		Group 3	-	

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

OSHA: (Occupational Safety & Health Administration)

X - Present

**Reproductive effects**

May damage fertility or the unborn child.

**STOT - single exposure**

No information available

**STOT - repeated exposure**

Causes damage to organs through prolonged or repeated exposure

**Target organ effects**

Central nervous system, Central Vascular System (CVS), Eyes, kidney, liver, respiratory system, Skin, blood, Gastrointestinal tract.

**Aspiration hazard**

No information available.

**Acute Toxicity**

1.115E-05 % of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document .

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

Toxic to aquatic life with long lasting effects

28.18454 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
TALC (RESPIRABLE DUST) 14807-96-6		100: 96 h Brachydanio rerio g/L LC50 semi-static	
METHYL ISOBUTYL KETONE 108-10-1	400: 96 h Pseudokirchneriella subcapitata mg/L EC50	496 - 514: 96 h Pimephales promelas mg/L LC50 flow-through	170: 48 h Daphnia magna mg/L EC50
EPOXY RESIN (LER) 25085-99-8	11 mg/L 72 hr	2 mg/L 96 hr Oncorhynchus mykiss	1.8 mg/L 48h
XYLENE 1330-20-7		LC50= 13.4 mg/L Pimephales promelas 96 h LC50 2.661 - 4.093 mg/L Oncorhynchus mykiss 96 h LC50 13.5 - 17.3 mg/L Oncorhynchus mykiss 96 h LC50 13.1 - 16.5 mg/L Lepomis macrochirus 96 h LC50= 19 mg/L Lepomis macrochirus 96 h LC50 7.711 - 9.591 mg/L Lepomis macrochirus 96 h LC50 23.53 - 29.97 mg/L Pimephales promelas 96 h LC50= 780 mg/L Cyprinus carpio 96 h LC50> 780 mg/L Cyprinus carpio 96 h LC50 30.26 - 40.75 mg/L Poecilia reticulata 96 h	EC50 = 3.82 mg/L 48 h LC50 = 0.6 mg/L 48 h
ETHYL BENZENE 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 32: 96 h Lepomis macrochirus mg/L LC50 static 9.6: 96 h Poecilia reticulata mg/L LC50 static 7.55 - 11: 96 h Pimephales	1.8 - 2.4: 48 h Daphnia magna mg/L EC50

	mg/L EC50 static	promelas mg/L LC50 flow-through 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static	
BENZENE, 1,4-DIMETHYL 106-42-3	105.1: 3 h Chlorella vulgaris mg/L EC50 3.2: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	7.2 - 9.9: 96 h Pimephales promelas mg/L LC50 static 2.6: 96 h Oncorhynchus mykiss mg/L LC50 8.8: 96 h Poecilia reticulata mg/L LC50 semi-static 2.6: 96 h Oncorhynchus mykiss mg/L LC50 static	3.55 - 6.31: 48 h Daphnia magna mg/L EC50 Static
BENZENE, 1,3-DIMETHYL 108-38-3	4.9: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	14.3 - 18: 96 h Pimephales promelas mg/L LC50 flow-through 8.4: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 12.9: 96 h Poecilia reticulata mg/L LC50 semi-static	2.81 - 5.0: 48 h Daphnia magna mg/L EC50 Static

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

Chemical name	log Pow
METHYL ISOBUTYL KETONE 108-10-1	1.19
EPOXY RESIN (LER) 25085-99-8	3
XYLENE 1330-20-7	2.77
ETHYL BENZENE 100-41-4	3.118
BENZENE, 1,4-DIMETHYL 106-42-3	3.15
BENZENE, 1,3-DIMETHYL 108-38-3	3.2

**Other Adverse Effects**

No information available

**13. DISPOSAL CONSIDERATIONS****Waste treatment methods****Disposal Methods**

In accordance with local and national regulations. Should not be released into the environment.

**Contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
METHYL ISOBUTYL KETONE 108-10-1		Included in waste stream: F039		U161
XYLENE 1330-20-7		Included in waste stream: F039		U239
ETHYL BENZENE 100-41-4		Included in waste stream: F039		
N-BUTANOL (SKIN) 71-36-3		Included in waste stream: F039		U031
FORMALDEHYDE 50-00-0	U122	Included in waste streams: K009, K010, K038, K040, K156, K157		U122

**California Hazardous Waste Status**

This product contains one or more substances that are listed with the State of California as a hazardous waste

Chemical name	CAWAST
XYLENE 1330-20-7	Toxic Ignitable
ETHYL BENZENE 100-41-4	Toxic Ignitable

#### 14. TRANSPORT INFORMATION

##### DOT

UN/ID no. 1263  
 Proper Shipping Name PAINT  
 Hazard Class 3  
 Packing Group II  
 Emergency Response Guide Number 128

##### Additional information

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

#### 15. REGULATORY INFORMATION

##### International Inventories

TSCA Complies  
 DSL/NDSL Complies  
 EINECS/ELINCS Does Not Comply  
 ENCS Does Not Comply  
 IECSC Complies  
 KECL Complies  
 PICCS Complies  
 AICS Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

Chemical name	HAPS Data
METHYL ISOBUTYL KETONE	
XYLENE	
ETHYL BENZENE	
BENZENE, 1,4-DIMETHYL	
BENZENE, 1,3-DIMETHYL	

##### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

Chemical name	SARA 313 - Threshold Values
METHYL ISOBUTYL KETONE - 108-10-1	1.0
XYLENE - 1330-20-7	1.0
ETHYL BENZENE - 100-41-4	0.1
BENZENE, 1,4-DIMETHYL - 106-42-3	1.0
BENZENE, 1,3-DIMETHYL - 108-38-3	1.0

**SARA 311/312 Hazardous**

**Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**Clean Water Act**

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE 1330-20-7	100 lb			X
ETHYL BENZENE 100-41-4	1000 lb	X	X	X
BENZENE, 1,4-DIMETHYL 106-42-3				X
BENZENE, 1,3-DIMETHYL 108-38-3				X

Chemical name	Hazardous Substances RQs	CERCLA EHS RQs	RQ
METHYL ISOBUTYL KETONE 108-10-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
ETHYL BENZENE 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
BENZENE, 1,4-DIMETHYL 106-42-3	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
BENZENE, 1,3-DIMETHYL 108-38-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

**California Prop. 65**

**WARNING:** This product can expose you to the following chemicals which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Chemical name	California Prop. 65
METHYL ISOBUTYL KETONE - 108-10-1	Carcinogen Developmental
ETHYL BENZENE - 100-41-4	Carcinogen
BENZENE, 1,3-DIMETHYL - 108-38-3	*
BENZENE, 1,2-DIMETHYL - 95-47-6	*
FORMALDEHYDE - 50-00-0	Carcinogen

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Chemical name	New Jersey	Massachusetts	Pennsylvania
TALC (RESPIRABLE DUST) 14807-96-6	X	X	X
METHYL ISOBUTYL KETONE 108-10-1	X	X	X
XYLENE 1330-20-7	X	X	X
ETHYL BENZENE 100-41-4	X	X	X
BENZENE, 1,4-DIMETHYL 106-42-3	X	X	X
BENZENE, 1,3-DIMETHYL 108-38-3	X	X	X

**16. OTHER INFORMATION**

<b>NFPA</b>	Health 2	Flammability 3	Instability 1	Physical hazard *
<b>HMIS (Hazardous Material Information System)</b>	Health 2*	Flammability 3	Reactivity 1	

Prepared By Tnemec Regulatory Dept: 816-474-3400  
Revision Date 15-Aug-2018

Revision Summary  
5 10 11 13 9 14 15

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of SDS**