



# Safety Data Sheet

Issue Date 16-Jul-2015

Revision Date 16-Jul-2015

Revision Number 10

## 1. IDENTIFICATION

### Product identifier

**Product Code** F041-0001  
**Product Name** THINNER CLEAR

### Other means of identification

**Common Name** NO. 1 THINNER

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372

#### **Distributor**

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203 Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable Liquids	Category 3

### Label elements

#### EMERGENCY OVERVIEW

#### **Danger**

#### **Hazard statements**

Causes damage to organs through prolonged or repeated exposure  
May be fatal if swallowed and enters airways  
Flammable liquid and vapor

**Appearance** opaque**Physical state** liquid**Odor** aromatic**Precautionary Statements****Prevention**

Do not breathe dust/fume/gas/mist/vapors/spray  
 Wash face, hands and any exposed skin thoroughly after handling  
 Do not eat, drink or smoke when using this product  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Wear protective gloves/protective clothing/eye protection/face protection

**Response**

Get medical advice/attention if you feel unwell  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do NOT induce vomiting  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store locked up  
 Store in a well-ventilated place. Keep cool  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

May be harmful if swallowed  
 May be harmful in contact with skin  
 Harmful to aquatic life with long lasting effects  
 SEE SAFETY DATA SHEET

Acute Toxicity 0 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight-%
SOLVENT NAPHTHA	64742-88-7	60 - 100%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

**Description of first aid measures**

**General advice** If symptoms persist, call a physician.

<b>Eye contact</b>	Rinse thoroughly with plenty of water for at least 15 minutes. If eye irritation persists, consult a specialist.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
<b>Inhalation</b>	Remove affected individual to fresh air. Treat symptomatically. If breathing is difficult, administer oxygen. If breathing has stopped give artificial respiration. Consult a physician.
<b>Ingestion</b>	Call a physician immediately. Never give anything by mouth to an unconscious person. Do not induce vomiting without medical advice.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

**Most important symptoms and effects, both acute and delayed**

**Notes to physician** Aspiration hazard.

## 5. FIRE-FIGHTING MEASURES

**Suitable extinguishing media**

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** No information available.

**Specific hazards arising from the chemical**

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

**Protective equipment and precautions for firefighters**

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

### Conditions for safe storage, including any incompatibilities

**Storage** Close container after each use. Keep away from heat, sparks and flame. Use only in an area containing flame proof equipment. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation. Keep out of the reach of children.

**Incompatible products** Strong oxidizing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### **Exposure guidelines**

#### **Appropriate engineering controls**

**Engineering measures** Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Safety glasses with side-shields If splashes are likely to occur, wear face-shield.

**Skin and body protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection** Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	liquid	<b>Odor</b>	aromatic
<b>Appearance</b>	opaque	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		
<b>Property</b>	<b>Values</b>	<b>Remarks</b>	
<b>pH</b>		No data available	
<b>Melting point / freezing point</b>		No data available	
<b>Boiling point / boiling range</b>	271 °C / 519 °F		
<b>Flash point</b>	38 °C / 100 °F		
<b>Evaporation rate</b>		Pensky Martens - Closed Cup	
		No data available	

<b>Flammability (solid, gas)</b>		Not applicable
<b>Flammability Limit in Air</b>		No data available
<b>Upper flammability limit</b>	N/A	
<b>Lower flammability limit</b>	1.0	
<b>Vapor pressure</b>		No data available
<b>Vapor density</b>		No data available
<b>Specific gravity</b>	0.77458	g/cm <sup>3</sup>
<b>Water solubility</b>	Insoluble in cold water	
<b>Solubility in other solvents</b>		No data available
<b>Partition coefficient: n-octanol/water</b>		No data available
<b>Autoignition temperature</b>		No data available
<b>Decomposition temperature</b>		No data available
<b>Kinematic viscosity</b>		No data available
<b>Dynamic viscosity</b>		No data available

**Other Information**

<b>Density</b>	6.45999 lbs/gal
<b>Volatile organic compounds (VOC) content</b>	6.45999 lbs/gal
<b>Total volatiles weight percent</b>	100 %
<b>Total volatiles volume percent</b>	100 %

**10. STABILITY AND REACTIVITY****Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Strong oxidizing agents

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

**11. TOXICOLOGICAL INFORMATION****Information on Likely Routes of Exposure**

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye contact</b>	Irritating to eyes.
<b>Skin contact</b>	Irritating to skin.
<b>Ingestion</b>	Harmful if swallowed. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
SOLVENT NAPHTHA 64742-88-7	> 5000 mg/kg ( Rat )	= 3000 mg/kg ( Rabbit )	> 5.28 mg/L ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Eye Damage.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Chronic Toxicity** NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**Sensitization** No information available.

**Mutagenicity** No information available.

**Carcinogenicity** There are no known carcinogenic chemicals in this product.

**Reproductive effects** No information available.

**STOT - single exposure** Skin, Eyes, Central Nervous System (CNS)

**STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure

**Target organ effects** Central nervous system, Eyes, kidney, respiratory system, liver, Skin.

**Aspiration hazard** Risk of serious damage to the lungs (by aspiration).

**Acute Toxicity** 0 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

Toxic to aquatic life with long lasting effects

0 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
SOLVENT NAPHTHA 64742-88-7	450: 96 h Pseudokirchneriella subcapitata mg/L EC50	800: 96 h Pimephales promelas mg/L LC50 static	100: 48 h Daphnia magna mg/L EC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media****Other Adverse Effects**

No information available

## 13. DISPOSAL CONSIDERATIONS

**Waste treatment methods****Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. TRANSPORT INFORMATION

**DOT**

**Proper Shipping Name**

Paint related material

**IATA**

<b>UN/ID no.</b>	1993
<b>Proper Shipping Name</b>	Paint related material
<b>Hazard Class</b>	3
<b>Packing Group</b>	III
<b>ERG Code</b>	366

**Additional information**

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

**15. REGULATORY INFORMATION**

**International Inventories**

<b>TSCA</b>	Complies
<b>DSL/NDSL</b>	Complies
<b>EINECS/ELINCS</b>	Complies
<b>ENCS</b>	Complies
<b>IECSC</b>	Complies
<b>KECL</b>	Complies
<b>PICCS</b>	Complies
<b>AICS</b>	Complies

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**IECSC** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

**United States of America**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

**SARA 311/312 Hazardous**

**Categorization**

<b>Acute Health Hazard</b>	Yes
<b>Chronic Health Hazard</b>	No
<b>Fire Hazard</b>	Yes
<b>Sudden Release of Pressure Hazard</b>	No
<b>Reactive Hazard</b>	No

**CERCLA**

**United States of America**

**California Prop. 65**

This product does not contain any Proposition 65 chemicals

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Component	New Jersey	Massachusetts	Pennsylvania
SOLVENT NAPHTHA 64742-88-7	X		

**16. OTHER INFORMATION**

<b>NFPA</b>	Health 2	Flammability 2	Instability 1	Physical hazard -
<b>HMIS (Hazardous Material Information System)</b>	Health 2	Flammability 2	Reactivity 1	

Prepared By Tnemec Regulatory Dept: 816-474-3400  
 Revision Date 16-Jul-2015  
 Revision Summary  
 9 4 5 7 10 8 11 14 1 15

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**





# Safety Data Sheet

Issue Date 12-Jul-2015

Revision Date 12-Jul-2015

Revision Number 23

## 1. IDENTIFICATION

### Product identifier

**Product Code** F041-0002  
**Product Name** THINNER CLEAR

### Other means of identification

**Common Name** NO. 2 THINNER  
**UN/ID no.** 1307

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372

#### **Distributor**

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203 Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Acute toxicity - Dermal	Category 4
Acute toxicity - Inhalation (Vapors)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable Liquids	Category 3

### Label elements

#### EMERGENCY OVERVIEW

Danger

**Hazard statements**

Harmful if swallowed  
 Harmful in contact with skin  
 Harmful if inhaled  
 Causes skin irritation  
 Causes serious eye irritation  
 Suspected of causing cancer  
 May cause respiratory irritation. May cause drowsiness or dizziness  
 May cause damage to organs through prolonged or repeated exposure  
 May be fatal if swallowed and enters airways  
 Flammable liquid and vapor

**Appearance** opaque**Physical state** liquid**Odor** aromatic**Precautionary Statements****Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Wash face, hands and any exposed skin thoroughly after handling  
 Do not eat, drink or smoke when using this product  
 Use only outdoors or in a well-ventilated area  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Keep cool

**Response**

IF exposed or concerned: Get medical advice/attention  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 Call a POISON CENTER or doctor/physician if you feel unwell  
 If skin irritation occurs: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Rinse mouth  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do NOT induce vomiting  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store locked up  
 Store in a well-ventilated place. Keep container tightly closed  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

Toxic to aquatic life with long lasting effects

SEE SAFETY DATA SHEET

Acute Toxicity

0 % of the mixture consists of ingredient(s) of unknown toxicity.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS-No	Weight-%
XYLENE	1330-20-7	60 - 100%
ETHYL BENZENE	100-41-4	10 - 30%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

**4. FIRST AID MEASURES****Description of first aid measures**

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Flush immediately with large amounts of clean water under low pressure for at least 15 minutes. Consult a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

**Most important symptoms and effects, both acute and delayed**

**Notes to physician** Treat symptomatically.

**5. FIRE-FIGHTING MEASURES****Suitable extinguishing media**

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

**Specific hazards arising from the chemical**

**FLAMMABLE** Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

**Protective equipment and precautions for firefighters**

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Ensure adequate ventilation. Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Prevent product from entering drains.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Handling** Ensure adequate ventilation. Do not breathe vapours or spray mist. Keep away from open flames, hot surfaces and sources of ignition. Avoid contact with eyes, skin and clothing. Take precautionary measures against static discharges. Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Close container after each use.

**Conditions for safe storage, including any incompatibilities**

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep out of the reach of children.

**Incompatible products** Strong oxidizing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters****Exposure guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
XYLENE 1330-20-7	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 150 ppm STEL: 655 mg/m <sup>3</sup>	
ETHYL BENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>	800 ppm

**Appropriate engineering controls**

**Engineering measures** Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Safety glasses with side-shields If splashes are likely to occur, wear face-shield.

**Skin and body protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection** Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	aromatic
<b>Appearance</b>	opaque	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
<b>pH</b>		No data available
<b>Melting point / freezing point</b>		No data available
<b>Boiling point / boiling range</b>	135 °C / 275 °F	
<b>Flash point</b>	26 °C / 78.0 °F	Pensky Martens - Closed Cup
<b>Evaporation rate</b>		No data available
<b>Flammability (solid, gas)</b>		Not applicable
<b>Flammability Limit in Air</b>		No data available
<b>Upper flammability limit</b>	N/A	
<b>Lower flammability limit</b>	1.0	
<b>Vapor pressure</b>		No data available
<b>Vapor density</b>		No data available
<b>Specific gravity</b>	0.86906	g/cm3
<b>Water solubility</b>	Insoluble in cold water	
<b>Solubility in other solvents</b>		No data available
<b>Partition coefficient: n-octanol/water</b>		No data available
<b>Autoignition temperature</b>		No data available
<b>Decomposition temperature</b>		No data available
<b>Kinematic viscosity</b>		No data available
<b>Dynamic viscosity</b>		No data available

**Other Information**

<b>Density</b>	7.248 lbs/gal
<b>Volatile organic compounds (VOC) content</b>	7.248 lbs/gal
<b>Total volatiles weight percent</b>	100 %
<b>Total volatiles volume percent</b>	100 %

## 10. STABILITY AND REACTIVITY

**Reactivity**

None under normal processing

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Strong oxidizing agents

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

<b>11. TOXICOLOGICAL INFORMATION</b>
--------------------------------------

**Information on Likely Routes of Exposure**

<b>Inhalation</b>	Harmful if inhaled. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Aspiration into lungs can produce severe lung damage.
<b>Eye contact</b>	Severely irritating to eyes.
<b>Skin contact</b>	Causes mild skin irritation.
<b>Ingestion</b>	Harmful if swallowed. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
XYLENE 1330-20-7	= 3500 mg/kg ( Rat )	> 1700 mg/kg ( Rabbit ) > 4350 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h = 5000 ppm ( Rat ) 4 h
ETHYL BENZENE 100-41-4	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.2 mg/L ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Eye Damage.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Chronic Toxicity** NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. May cause cancer.

**Sensitization**

No information available.

**Mutagenicity**

No information available.

**Carcinogenicity**

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	ACGIH	IARC	NTP	OSHA
XYLENE 1330-20-7		Group 3		
ETHYL BENZENE 100-41-4	A3	Group 2B		X

**Reproductive effects**

No information available.

**STOT - single exposure**

Central Nervous System (CNS), Respiratory system

**STOT - repeated exposure**

Causes damage to organs through prolonged or repeated exposure

<b>Target organ effects</b>	blood, Central nervous system, Gastrointestinal tract, Eyes, kidney, liver, respiratory system, Skin.
<b>Aspiration hazard</b>	Risk of serious damage to the lungs (by aspiration).
<b>Acute Toxicity</b>	0 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Toxic to aquatic life with long lasting effects

0 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
XYLENE 1330-20-7		LC50= 13.4 mg/L Pimephales promelas 96 h LC50 2.661 - 4.093 mg/L Oncorhynchus mykiss 96 h LC50 13.5 - 17.3 mg/L Oncorhynchus mykiss 96 h LC50 13.1 - 16.5 mg/L Lepomis macrochirus 96 h LC50= 19 mg/L Lepomis macrochirus 96 h LC50 7.711 - 9.591 mg/L Lepomis macrochirus 96 h LC50 23.53 - 29.97 mg/L Pimephales promelas 96 h LC50= 780 mg/L Cyprinus carpio 96 h LC50> 780 mg/L Cyprinus carpio 96 h LC50 30.26 - 40.75 mg/L Poecilia reticulata 96 h	EC50 = 3.82 mg/L 48 h LC50 = 0.6 mg/L 48 h
ETHYL BENZENE 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 32: 96 h Lepomis macrochirus mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 9.6: 96 h Poecilia reticulata mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static	1.8 - 2.4: 48 h Daphnia magna mg/L EC50

### Persistence and degradability

No information available.

### Bioaccumulation

No information available.

### Mobility in Environmental Media

Component	log Pow
XYLENE 1330-20-7	2.77
ETHYL BENZENE 100-41-4	3.118

### Other Adverse Effects

No information available

## 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

#### **Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Component	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
XYLENE 1330-20-7		Included in waste stream: F039		U239
ETHYL BENZENE 100-41-4		Included in waste stream: F039		

Component	CAWAST
XYLENE 1330-20-7	Toxic Ignitable
ETHYL BENZENE 100-41-4	Toxic Ignitable

**14. TRANSPORT INFORMATION**

**DOT**

UN/ID no. 1307  
 Proper Shipping Name XYLENE  
 Hazard Class 3  
 Packing Group III  
 Emergency Response Guide Number 130

**IATA**

UN/ID no. 1307  
 Proper Shipping Name XYLENE  
 Hazard Class 3  
 Packing Group III  
 ERG Code 366

**Additional information**

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

**15. REGULATORY INFORMATION**

**International Inventories**

TSCA Complies  
 DSL/NDL Complies  
 EINECS/ELINCS Complies  
 ENCS Complies  
 IECSC Complies  
 KECL Complies  
 PICCS Complies  
 AICS Complies

- TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
- DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List
- EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
- ENCS - Japan Existing and New Chemical Substances
- IECSC - China Inventory of Existing Chemical Substances
- KECL - Korean Existing and Evaluated Chemical Substances
- PICCS - Philippines Inventory of Chemicals and Chemical Substances
- AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

Component	HAPS Data
XYLENE	
ETHYL BENZENE	



**United States of America**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372:

Component	SARA 313 - Threshold Values
XYLENE - 1330-20-7	1.0
ETHYL BENZENE - 100-41-4	0.1

**SARA 311/312 Hazardous**

**Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE 1330-20-7	100 lb			X
ETHYL BENZENE 100-41-4	1000 lb	X	X	X

**CERCLA**

Component	Hazardous Substances RQs	CERCLA EHS RQs	RQ
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
ETHYL BENZENE 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

**United States of America**

**California Prop. 65**

WARNING! This product contains a chemical known in the State of California to cause cancer

Component	California Prop. 65
ETHYL BENZENE - 100-41-4	Carcinogen

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Component	New Jersey	Massachusetts	Pennsylvania
XYLENE 1330-20-7	X	X	X
ETHYL BENZENE 100-41-4	X	X	X

**16. OTHER INFORMATION**

<b>NFPA</b>	Health 2	Flammability 3	Instability 1	Physical hazard *
<b>HMIS (Hazardous Material Information System)</b>	Health 2*	Flammability 3	Reactivity 1	


Prepared By Tnemec Regulatory Dept: 816-474-3400  
 Revision Date 12-Jul-2015  
 Revision Summary  
 9 4 5 7 10 8 11 14 6 2

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**



# Safety Data Sheet

Issue Date 12-Jul-2015

Revision Date 12-Jul-2015

Revision Number 10

## 1. IDENTIFICATION

### Product identifier

**Product Code** F041-0003  
**Product Name** THINNER CLEAR

### Other means of identification

**Common Name** NO. 3 THINNER

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO  
64120-1372

#### **Distributor**

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203  
Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable Liquids	Category 3

### Label elements

## EMERGENCY OVERVIEW

### **Danger**

#### **Hazard statements**

Causes skin irritation  
Causes serious eye irritation  
May cause genetic defects  
May cause cancer  
May cause respiratory irritation  
May be fatal if swallowed and enters airways  
Flammable liquid and vapor

**Appearance** opaque**Physical state** liquid**Odor** aromatic**Precautionary Statements****Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Wash face, hands and any exposed skin thoroughly after handling  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Use only outdoors or in a well-ventilated area  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Keep cool

**Response**

IF exposed or concerned: Get medical advice/attention  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 If skin irritation occurs: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do NOT induce vomiting  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store locked up  
 Store in a well-ventilated place. Keep container tightly closed  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

Toxic to aquatic life with long lasting effects

SEE SAFETY DATA SHEET

Acute Toxicity

3 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight-%
AROMATIC HYDROCARBON MIXTURE	64742-95-6	30 - 60%
1,2,4-TRIMETHYLBENZENE	95-63-6	30 - 60%
1,3,5-TRIMETHYLBENZENE	108-67-8	1 - 10%

DIETHYLBENZENE	25340-17-4	1 - 10%
XYLENE	1330-20-7	1 - 10%
(1-METHYLETHYL)BENZENE	-	1 - 10%
ETHYL BENZENE	100-41-4	0.1 - 1%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

##### Description of first aid measures

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

##### Most important symptoms and effects, both acute and delayed

**Notes to physician** Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Water. Do not use a solid water stream as it may scatter and spread fire.

##### Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

##### Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

#### 6. ACCIDENTAL RELEASE MEASURES

##### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Ensure adequate ventilation. Use personal protective equipment. Avoid contact with eyes, skin and clothing. Remove all sources of ignition.

##### Environmental Precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Handling** Handle in accordance with good industrial hygiene and safety practice. Wear personal protective equipment. Avoid contact with eyes, skin and clothing. Remove and wash contaminated clothing before re-use. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not breathe vapours or spray mist. Do not ingest. Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

**Conditions for safe storage, including any incompatibilities**

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

**Incompatible products** Strong oxidizing agents. Acids. Alkalis.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters****Exposure guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
XYLENE 1330-20-7	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 150 ppm STEL: 655 mg/m <sup>3</sup>	
(1-METHYLETHYL)BENZENE	TWA: 50 ppm	TWA: 50 ppm TWA: 245 mg/m <sup>3</sup> Skin	900 ppm
ETHYL BENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>	800 ppm

**Appropriate engineering controls**

**Engineering measures** Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Use chemical resistant splash type goggles.

<b>Skin and body protection</b>	Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
<b>Respiratory protection</b>	Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.
<b>General hygiene considerations</b>	Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	liquid	<b>Odor</b>	aromatic
<b>Appearance</b>	opaque	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		
<b><u>Property</u></b>	<b><u>Values</u></b>	<b><u>Remarks</u></b>	
<b>pH</b>		No data available	
<b>Melting point / freezing point</b>		No data available	
<b>Boiling point / boiling range</b>	72 °C / 162 °F		
<b>Flash point</b>	42 °C / 108 °F		
<b>Evaporation rate</b>		Pensky Martens - Closed Cup	
<b>Flammability (solid, gas)</b>		No data available	
<b>Flammability Limit in Air</b>		Not applicable	
<b>Upper flammability limit</b>	N/A	No data available	
<b>Lower flammability limit</b>	1.0		
<b>Vapor pressure</b>		No data available	
<b>Vapor density</b>		No data available	
<b>Specific gravity</b>	0.87179	g/cm <sup>3</sup>	
<b>Water solubility</b>	Insoluble in cold water		
<b>Solubility in other solvents</b>		No data available	
<b>Partition coefficient: n-octanol/water</b>		No data available	
<b>Autoignition temperature</b>		No data available	
<b>Decomposition temperature</b>		No data available	
<b>Kinematic viscosity</b>		No data available	
<b>Dynamic viscosity</b>		No data available	

### Other Information

<b>Density</b>	7.27077 lbs/gal
<b>Volatile organic compounds (VOC) content</b>	7.27077 lbs/gal
<b>Total volatiles weight percent</b>	100 %
<b>Total volatiles volume percent</b>	100 %

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Possibility of hazardous reactions

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Strong oxidizing agents, Acids, Alkalis

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

<b>11. TOXICOLOGICAL INFORMATION</b>
--------------------------------------

**Information on Likely Routes of Exposure**

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. Aspiration into lungs can produce severe lung damage.
<b>Eye contact</b>	Causes serious eye damage.
<b>Skin contact</b>	Irritating to skin.
<b>Ingestion</b>	Harmful if swallowed. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
AROMATIC HYDROCARBON MIXTURE 64742-95-6	= 8400 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	= 3400 ppm ( Rat ) 4 h
1,2,4-TRIMETHYLBENZENE 95-63-6	= 3280 mg/kg ( Rat )	> 3160 mg/kg ( Rabbit )	= 18 g/m <sup>3</sup> ( Rat ) 4 h
1,3,5-TRIMETHYLBENZENE 108-67-8	= 5000 mg/kg ( Rat )		= 24 g/m <sup>3</sup> ( Rat ) 4 h
XYLENE 1330-20-7	= 3500 mg/kg ( Rat )	> 1700 mg/kg ( Rabbit ) > 4350 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h = 5000 ppm ( Rat ) 4 h
(1-METHYLETHYL)BENZENE	= 1400 mg/kg ( Rat )	= 12300 µL/kg ( Rabbit )	> 3577 ppm ( Rat ) 6 h = 39000 mg/m <sup>3</sup> ( Rat ) 4 h
ETHYL BENZENE 100-41-4	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.2 mg/L ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Eye Damage.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Chronic Toxicity** NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. May cause cancer.

**Sensitization** No information available.

**Mutagenicity** May cause genetic defects.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	ACGIH	IARC	NTP	OSHA
XYLENE 1330-20-7		Group 3		
(1-METHYLETHYL)BENZENE		Group 2B	Reasonably Anticipated	X
ETHYL BENZENE 100-41-4	A3	Group 2B		X

**Reproductive effects** No information available.

**STOT - single exposure** Skin, Eyes, Central Nervous System (CNS)

**STOT - repeated exposure** No information available



**Aspiration hazard** Risk of serious damage to the lungs (by aspiration).

**Acute Toxicity** 3 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Toxic to aquatic life with long lasting effects

36 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
AROMATIC HYDROCARBON MIXTURE 64742-95-6		9.22: 96 h Oncorhynchus mykiss mg/L LC50	6.14: 48 h Daphnia magna mg/L EC50
1,2,4-TRIMETHYLBENZENE 95-63-6		7.19 - 8.28: 96 h Pimephales promelas mg/L LC50 flow-through	6.14: 48 h Daphnia magna mg/L EC50
1,3,5-TRIMETHYLBENZENE 108-67-8		3.48: 96 h Pimephales promelas mg/L LC50	50: 24 h Daphnia magna mg/L EC50
XYLENE 1330-20-7		LC50= 13.4 mg/L Pimephales promelas 96 h LC50 2.661 - 4.093 mg/L Oncorhynchus mykiss 96 h LC50 13.5 - 17.3 mg/L Oncorhynchus mykiss 96 h LC50 13.1 - 16.5 mg/L Lepomis macrochirus 96 h LC50= 19 mg/L Lepomis macrochirus 96 h LC50 7.711 - 9.591 mg/L Lepomis macrochirus 96 h LC50 23.53 - 29.97 mg/L Pimephales promelas 96 h LC50= 780 mg/L Cyprinus carpio 96 h LC50> 780 mg/L Cyprinus carpio 96 h LC50 30.26 - 40.75 mg/L Poecilia reticulata 96 h	EC50 = 3.82 mg/L 48 h LC50 = 0.6 mg/L 48 h
(1-METHYLETHYL)BENZENE	2.6: 72 h Pseudokirchneriella subcapitata mg/L EC50	2.7: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 6.04 - 6.61: 96 h Pimephales promelas mg/L LC50 flow-through 4.8: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 5.1: 96 h Poecilia reticulata mg/L LC50 semi-static	0.6: 48 h Daphnia magna mg/L EC50 7.9 - 14.1: 48 h Daphnia magna mg/L EC50 Static
ETHYL BENZENE 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 32: 96 h Lepomis macrochirus mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 9.6: 96 h Poecilia reticulata mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static	1.8 - 2.4: 48 h Daphnia magna mg/L EC50

### Persistence and degradability

No information available.

### Bioaccumulation

No information available.

### Mobility in Environmental Media

Component	log Pow
1,2,4-TRIMETHYLBENZENE 95-63-6	3.63
XYLENE 1330-20-7	2.77
(1-METHYLETHYL)BENZENE	3.55

ETHYL BENZENE 100-41-4	3.118
---------------------------	-------

**Other Adverse Effects** No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal Methods** Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Component	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
XYLENE 1330-20-7		Included in waste stream: F039		U239
(1-METHYLETHYL)BENZENE				U055
ETHYL BENZENE 100-41-4		Included in waste stream: F039		

Component	CAWAST
XYLENE 1330-20-7	Toxic Ignitable
(1-METHYLETHYL)BENZENE	Toxic Ignitable
ETHYL BENZENE 100-41-4	Toxic Ignitable

**14. TRANSPORT INFORMATION**

**DOT**  
**Proper Shipping Name** PAINT & RELATED MATERIAL-(NMFC 149980 SUB 2)

**IATA**  
**UN/ID no.** 1993  
**Proper Shipping Name** Flammable liquid, n.o.s (trimethyl benzene)  
**Hazard Class** 3  
**Packing Group** III  
**ERG Code** 366

**Additional information** Call TNEMEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

**15. REGULATORY INFORMATION**

**International Inventories**  
TSCA Complies  
DSL/NDSL Complies  
EINECS/ELINCS Complies  
ENCS Complies  
IECSC Complies  
KECL Complies  
PICCS Complies  
AICS Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List  
 EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances  
 ENCS - Japan Existing and New Chemical Substances  
 IECSC - China Inventory of Existing Chemical Substances  
 KECL - Korean Existing and Evaluated Chemical Substances  
 PICCS - Philippines Inventory of Chemicals and Chemical Substances  
 AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):  
 Component HAPS Data

XYLENE  
 (1-METHYLETHYL)BENZENE  
 ETHYL BENZENE

### United States of America

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372:

Component	SARA 313 - Threshold Values
1,2,4-TRIMETHYLBENZENE - 95-63-6	1.0
XYLENE - 1330-20-7	1.0
(1-METHYLETHYL)BENZENE -	1.0
ETHYL BENZENE - 100-41-4	0.1

#### **SARA 311/312 Hazardous Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE 1330-20-7	100 lb			X
ETHYL BENZENE 100-41-4	1000 lb	X	X	X

#### **CERCLA**

Component	Hazardous Substances RQs	CERCLA EHS RQs	RQ
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
(1-METHYLETHYL)BENZENE	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
ETHYL BENZENE 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

### United States of America

#### **California Prop. 65**

WARNING! This product contains a chemical known in the State of California to cause cancer

Component	California Prop. 65
(1-METHYLETHYL)BENZENE -	Carcinogen
ETHYL BENZENE - 100-41-4	Carcinogen

#### **California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

#### **State Right-to-Know**

Component	New Jersey	Massachusetts	Pennsylvania
1,2,4-TRIMETHYLBENZENE 95-63-6	X	X	X
1,3,5-TRIMETHYLBENZENE 108-67-8		X	
DIETHYLBENZENE 25340-17-4	X		
XYLENE 1330-20-7	X	X	X
(1-METHYLETHYL)BENZENE	X	X	X
ETHYL BENZENE 100-41-4	X	X	X

## 16. OTHER INFORMATION

**NFPA** Health 2 Flammability 2 Instability 1 Physical hazard \*  
**HMIS (Hazardous Material Information System)** Health 2\* Flammability 2 Reactivity 1


**Prepared By** Tnemec Regulatory Dept: 816-474-3400  
**Revision Date** 12-Jul-2015  
**Revision Summary**  
 9 4 5 7 10 8 11 14 6

### **Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**



# Safety Data Sheet

Issue Date 12-Jul-2015

Revision Date 12-Jul-2015

Revision Number 12

## 1. IDENTIFICATION

### Product identifier

**Product Code** F041-0004  
**Product Name** THINNER CLEAR

### Other means of identification

**Common Name** NO. 4 THINNER  
**UN/ID no.** 1263

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372

#### **Distributor**

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203 Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Vapors)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable Liquids	Category 2

### Label elements

#### EMERGENCY OVERVIEW

Danger

**Hazard statements**

Harmful if swallowed  
 Harmful if inhaled  
 Causes skin irritation  
 Causes serious eye damage  
 Suspected of causing cancer  
 May cause respiratory irritation  
 May cause damage to organs through prolonged or repeated exposure  
 May be fatal if swallowed and enters airways  
 Highly flammable liquid and vapor

**Appearance** clear**Physical state** liquid**Odor** aromatic**Precautionary Statements****Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Wash face, hands and any exposed skin thoroughly after handling  
 Do not eat, drink or smoke when using this product  
 Use only outdoors or in a well-ventilated area  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Keep cool

**Response**

IF exposed or concerned: Get medical advice/attention  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 Immediately call a POISON CENTER or doctor/physician  
 If skin irritation occurs: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Rinse mouth  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do NOT induce vomiting  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store locked up  
 Store in a well-ventilated place. Keep container tightly closed

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

Toxic to aquatic life with long lasting effects

Acute Toxicity

0 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight-%
METHYL ISOBUTYL KETONE	108-10-1	30 - 60%
XYLENE	1330-20-7	30 - 60%
N-BUTANOL (SKIN)	71-36-3	10 - 30%
ETHYL BENZENE	100-41-4	1 - 10%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

#### Description of first aid measures

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Call a physician immediately.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately. Never give anything by mouth to an unconscious person.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

#### Most important symptoms and effects, both acute and delayed

**Most important symptoms and effects** Breathing difficulties.

**Notes to physician** Aspiration hazard.

### 5. FIRE-FIGHTING MEASURES

#### Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

#### Specific hazards arising from the chemical

FLAMMABLE Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

#### Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Ensure adequate ventilation. Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

### Environmental Precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Prevent product from entering drains.

### Methods and material for containment and cleaning up

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Ensure adequate ventilation. Do not breathe vapours or spray mist. Keep away from open flames, hot surfaces and sources of ignition. Avoid contact with eyes, skin and clothing. Take precautionary measures against static discharges. Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Close container after each use.

### Conditions for safe storage, including any incompatibilities

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep out of the reach of children.

**Incompatible products** Strong oxidizing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
METHYL ISOBUTYL KETONE 108-10-1	TWA: 20 ppm STEL: 75 ppm	TWA: 50 ppm TWA: 205 mg/m <sup>3</sup> STEL: 75 ppm STEL: 300 mg/m <sup>3</sup> TWA: 100 ppm TWA: 410 mg/m <sup>3</sup>	500 ppm
XYLENE 1330-20-7	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 150 ppm STEL: 655 mg/m <sup>3</sup>	
N-BUTANOL (SKIN) 71-36-3	TWA: 20 ppm	Skin Ceiling: 50 ppm Ceiling: 150 mg/m <sup>3</sup> TWA: 100 ppm TWA: 300 mg/m <sup>3</sup>	1400 ppm



ETHYL BENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>	800 ppm
---------------------------	-------------	--	---------

**Appropriate engineering controls****Engineering measures**

Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV).

Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.

**Skin and body protection**

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection**

Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations**

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	aromatic
<b>Appearance</b>	clear	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		

**Property****Values****Remarks**

<b>pH</b>		No data available
<b>Melting point / freezing point</b>		No data available
<b>Boiling point / boiling range</b>	114 °C / 237 °F	
<b>Flash point</b>	18 °C / 64 °F	Pensky Martens - Closed Cup
<b>Evaporation rate</b>		No data available
<b>Flammability (solid, gas)</b>		Not applicable
<b>Flammability Limit in Air</b>		No data available
<b>Upper flammability limit</b>	N/A	
<b>Lower flammability limit</b>	1.0	
<b>Vapor pressure</b>		No data available
<b>Vapor density</b>		No data available
<b>Specific gravity</b>	0.8294	g/cm <sup>3</sup>
<b>Water solubility</b>	Insoluble in cold water	
<b>Solubility in other solvents</b>		No data available
<b>Partition coefficient: n-octanol/water</b>		No data available
<b>Autoignition temperature</b>		No data available
<b>Decomposition temperature</b>		No data available
<b>Kinematic viscosity</b>		No data available
<b>Dynamic viscosity</b>		No data available

**Other Information**

<b>Density</b>	6.9172 lbs/gal
----------------	----------------

**Volatile organic compounds (VOC) content** 6.9172 lbs/gal  
**Total volatiles weight percent** 100 %  
**Total volatiles volume percent** 100 %

## 10. STABILITY AND REACTIVITY

### Reactivity

None under normal processing

### Chemical stability

Stable under recommended storage conditions.

### Possibility of hazardous reactions

None under normal processing.

### Conditions to avoid

Heat, flames and sparks.

### Incompatible materials

Strong oxidizing agents

### Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

## 11. TOXICOLOGICAL INFORMATION

### Information on Likely Routes of Exposure

<b>Inhalation</b>	Harmful if inhaled. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Aspiration into lungs can produce severe lung damage.
<b>Eye contact</b>	Causes serious eye damage.
<b>Skin contact</b>	Irritating to skin.
<b>Ingestion</b>	Harmful if swallowed. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
METHYL ISOBUTYL KETONE 108-10-1	= 2080 mg/kg ( Rat )	= 3000 mg/kg ( Rabbit )	= 8.2 mg/L ( Rat ) 4 h
XYLENE 1330-20-7	= 3500 mg/kg ( Rat )	> 1700 mg/kg ( Rabbit ) > 4350 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h = 5000 ppm ( Rat ) 4 h
N-BUTANOL (SKIN) 71-36-3	= 700 mg/kg ( Rat ) = 790 mg/kg ( Rat )	= 3402 mg/kg ( Rabbit ) = 3400 mg/kg ( Rabbit )	> 8000 ppm ( Rat ) 4 h
ETHYL BENZENE 100-41-4	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.2 mg/L ( Rat ) 4 h

### Information on toxicological effects

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Eye Damage.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Corrosivity** Corrosive to the eyes and may cause severe damage including blindness.

**Chronic Toxicity**

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. May cause cancer.

**Sensitization**

No information available.

**Mutagenicity**

No information available.

**Carcinogenicity**

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	ACGIH	IARC	NTP	OSHA
METHYL ISOBUTYL KETONE 108-10-1	A3	Group 2B		X
XYLENE 1330-20-7		Group 3		
ETHYL BENZENE 100-41-4	A3	Group 2B		X

**Reproductive effects**

No information available.

**STOT - single exposure**

Central Nervous System (CNS), Respiratory system

**STOT - repeated exposure**

Causes damage to organs through prolonged or repeated exposure blood, Central nervous system, Gastrointestinal tract, Eyes, kidney, liver, respiratory system, Skin.

**Target organ effects****Aspiration hazard**

Risk of serious damage to the lungs (by aspiration).

**Acute Toxicity**

0 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

Toxic to aquatic life with long lasting effects

0 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
METHYL ISOBUTYL KETONE 108-10-1	400: 96 h Pseudokirchneriella subcapitata mg/L EC50	496 - 514: 96 h Pimephales promelas mg/L LC50 flow-through	170: 48 h Daphnia magna mg/L EC50
XYLENE 1330-20-7		LC50= 13.4 mg/L Pimephales promelas 96 h LC50 2.661 - 4.093 mg/L Oncorhynchus mykiss 96 h LC50 13.5 - 17.3 mg/L Oncorhynchus mykiss 96 h LC50 13.1 - 16.5 mg/L Lepomis macrochirus 96 h LC50= 19 mg/L Lepomis macrochirus 96 h LC50 7.711 - 9.591 mg/L Lepomis macrochirus 96 h LC50 23.53 - 29.97 mg/L Pimephales promelas 96 h LC50= 780 mg/L Cyprinus carpio 96 h LC50 > 780 mg/L Cyprinus carpio 96 h LC50 30.26 - 40.75 mg/L Poecilia reticulata 96 h	EC50 = 3.82 mg/L 48 h LC50 = 0.6 mg/L 48 h
N-BUTANOL (SKIN) 71-36-3	500: 96 h Desmodesmus subspicatus mg/L EC50 500: 72 h Desmodesmus subspicatus mg/L EC50	1740: 96 h Pimephales promelas mg/L LC50 flow-through 1910000: 96 h Pimephales promelas µg/L LC50 static 100000 - 500000: 96 h Lepomis macrochirus µg/L LC50 static 1730 - 1910: 96 h Pimephales promelas mg/L LC50 static	1897 - 2072: 48 h Daphnia magna mg/L EC50 Static 1983: 48 h Daphnia magna mg/L EC50
ETHYL BENZENE 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 32: 96 h Lepomis macrochirus mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 9.6: 96 h Poecilia reticulata mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static	1.8 - 2.4: 48 h Daphnia magna mg/L EC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

Component	log Pow
METHYL ISOBUTYL KETONE 108-10-1	1.19
XYLENE 1330-20-7	2.77
N-BUTANOL (SKIN) 71-36-3	0.785
ETHYL BENZENE 100-41-4	3.118

**Other Adverse Effects**

No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

Component	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
METHYL ISOBUTYL KETONE 108-10-1		Included in waste stream: F039		U161
XYLENE 1330-20-7		Included in waste stream: F039		U239
N-BUTANOL (SKIN) 71-36-3		Included in waste stream: F039		U031
ETHYL BENZENE 100-41-4		Included in waste stream: F039		

Component	CAWAST
XYLENE 1330-20-7	Toxic Ignitable
N-BUTANOL (SKIN) 71-36-3	Toxic
ETHYL BENZENE 100-41-4	Toxic Ignitable

**14. TRANSPORT INFORMATION**

**DOT**

UN/ID no. 1263  
 Proper Shipping Name Paint related material  
 Hazard Class 3  
 Packing Group II  
 Emergency Response Guide Number 128

**IATA**

UNID no. 1263  
 Proper Shipping Name Paint related material  
 Hazard Class 3  
 Packing Group II  
 ERG Code 364

**Additional information** Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

**15. REGULATORY INFORMATION**

**International Inventories**

TSCA Complies  
 DSL/NDSL Complies  
 EINECS/ELINCS Complies  
 ENCS Complies  
 IECSC Complies  
 KECL Complies  
 PICCS Complies  
 AICS Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List  
 EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances  
 ENCS - Japan Existing and New Chemical Substances  
 IECSC - China Inventory of Existing Chemical Substances  
 KECL - Korean Existing and Evaluated Chemical Substances  
 PICCS - Philippines Inventory of Chemicals and Chemical Substances  
 AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

<b>Component</b>	<b>HAPS Data</b>
METHYL ISOBUTYL KETONE	
XYLENE	
ETHYL BENZENE	

**United States of America**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

Component	SARA 313 - Threshold Values
METHYL ISOBUTYL KETONE - 108-10-1	1.0
XYLENE - 1330-20-7	1.0
N-BUTANOL (SKIN) - 71-36-3	1.0
ETHYL BENZENE - 100-41-4	0.1

**SARA 311/312 Hazardous**

**Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**Clean Water Act**

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE 1330-20-7	100 lb			X

ETHYL BENZENE 100-41-4	1000 lb	X	X	X
---------------------------	---------	---	---	---

**CERCLA**

Component	Hazardous Substances RQs	CERCLA EHS RQs	RQ
METHYL ISOBUTYL KETONE 108-10-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
N-BUTANOL (SKIN) 71-36-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
ETHYL BENZENE 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

**United States of America**

**California Prop. 65**

WARNING! This product contains a chemical known in the State of California to cause cancer

Component	California Prop. 65
METHYL ISOBUTYL KETONE - 108-10-1	Carcinogen Developmental
ETHYL BENZENE - 100-41-4	Carcinogen

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Component	New Jersey	Massachusetts	Pennsylvania
METHYL ISOBUTYL KETONE 108-10-1	X	X	X
XYLENE 1330-20-7	X	X	X
N-BUTANOL (SKIN) 71-36-3	X	X	X
ETHYL BENZENE 100-41-4	X	X	X

**16. OTHER INFORMATION**

**NFPA** Health 2 Flammability 3 Instability 1 Physical hazard \*  
**HMIS (Hazardous Material Information System)** Health 2\* Flammability 3 Reactivity 1


Prepared By Tnemec Regulatory Dept: 816-474-3400  
 Revision Date 12-Jul-2015  
 Revision Summary  
 9 4 5 7 10 8 11 14 6 15

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**



# Safety Data Sheet

Issue Date 16-Aug-2017

Revision Date 16-Aug-2017

Revision Number 2

## 1. IDENTIFICATION

### Product identifier

**Product Code** F041-0010  
**Product Name** NO.10 THINNER

### Other means of identification

**Common Name** NO. 10 THINNER  
**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372 816-474-3400

#### **Distributor**

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

#### **Emergency telephone number**

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Flammable Liquids	Category 3

### Label elements

#### EMERGENCY OVERVIEW

#### **Danger**

#### **Hazard statements**

Causes serious eye irritation  
May cause genetic defects  
May cause cancer  
Flammable liquid and vapor



**Appearance** clear**Physical state** liquid**Odor** Slight**Precautionary Statements****Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Wash face, hands and any exposed skin thoroughly after handling  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Use explosion-proof electrical/ventilating/lighting/metal/plastic/equipment

**Response**

IF exposed or concerned: Get medical advice/attention  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store locked up  
 Store in a well-ventilated place. Keep cool  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

SEE SAFETY DATA SHEET

Acute Toxicity

6E-06 % of the mixture consists of ingredient(s) of unknown toxicity.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical name	CAS No	Weight-%
PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE	108-65-6	60 - 100%
ETHYL 3-ETHOXYPROPIONATE	763-69-9	1 - <10%
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE	124-17-4	1 - <10%
PETROLEUM SOLVENT (NAPHTHA)	64742-95-6	0.1 - <1%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

**4. FIRST AID MEASURES****Description of first aid measures****General advice**

If symptoms persist, call a physician.

**Eye contact**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.

**Skin contact**

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.



**Inhalation** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

**Ingestion** If swallowed, do not induce vomiting. Get medical attention immediately.

**Self-protection of the first aider** Use personal protective equipment. Avoid contact with eyes, skin and clothing.

**Most important symptoms and effects, both acute and delayed**

**Notes to physician** Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

**Suitable extinguishing media**

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

**Specific hazards arising from the chemical**

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Sulfur oxides. Phosphorus oxides.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Use personal protective equipment. Avoid contact with eyes, skin and clothing. Ensure adequate ventilation. Remove all sources of ignition.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** Pick up and transfer to properly labelled containers.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Handling** Handle in accordance with good industrial hygiene and safety practice. Wear personal protective equipment. Remove and wash contaminated clothing before re-use. Avoid contact with eyes, skin and clothing. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not breathe vapours or spray mist. Ensure adequate ventilation. In case of insufficient ventilation, wear

suitable respiratory equipment. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

#### Conditions for safe storage, including any incompatibilities

<b>Storage</b>	Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.
<b>Incompatible products</b>	Strong oxidizing agents.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

#### Exposure guidelines

#### Appropriate engineering controls

<b>Engineering measures</b>	Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.
-----------------------------	--

#### Individual protection measures, such as personal protective equipment

<b>Eye/face protection</b>	Safety glasses with side-shields If splashes are likely to occur, wear face-shield.
<b>Skin and body protection</b>	Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
<b>Respiratory protection</b>	Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.
<b>General hygiene considerations</b>	Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

<b>Physical state</b>	liquid	<b>Odor</b>	Slight
<b>Appearance</b>	clear	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		
<b>Property</b>	<b>Values</b>	<b>Remarks</b>	
<b>pH</b>		No data available	
<b>Melting point / freezing point</b>	No data available	No information available	
<b>Boiling point / boiling range</b>		Pensky Martens - Closed Cup	
<b>Flash point</b>	43.33 °C / 110.00 °F	No data available	
<b>Evaporation rate</b>		No data available	
<b>Flammability (solid, gas)</b>	No data available	No data available	
<b>Flammability Limit in Air</b>		No data available	
<b>Upper flammability limit</b>	NA		
<b>Lower flammability limit</b>	NA		
<b>Vapor pressure</b>		No data available	
<b>Vapor density</b>		No data available	
<b>Specific gravity</b>	.96348	g/cm3	
<b>Water solubility</b>	Insoluble in cold water		
<b>Solubility in other solvents</b>		No data available	

<b>Partition coefficient: n-octanol/water</b>		No data available
<b>Autoignition temperature</b>	No data available	No data available
<b>Decomposition temperature</b>		No data available
<b>Kinematic viscosity</b>		No data available
<b>Dynamic viscosity</b>		No data available

**Other Information**

<b>Density</b>	8.025772 lbs/gal
<b>Volatile organic compounds (VOC) content</b>	7.991 lbs/gal
<b>Total volatiles weight percent</b>	99.5685 %
<b>Total volatiles volume percent</b>	99.6663 %
<b>Bulk density</b>	No information available

**10. STABILITY AND REACTIVITY****Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Strong oxidizing agents

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Sulfur oxides. Phosphorous Oxides.

**11. TOXICOLOGICAL INFORMATION****Information on Likely Routes of Exposure**

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Skin contact</b>	May cause irritation.
<b>Ingestion</b>	Harmful if swallowed.

Chemical name	LD50 Oral	LD50 Dermal	LC50 Inhalation
PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE 108-65-6	= 8532 mg/kg ( Rat )	> 5 g/kg ( Rabbit )	-
ETHYL 3-ETHOXYPROPIONATE 763-69-9	= 5 g/kg ( Rat )	= 10 mL/kg ( Rabbit ) > 9500 mg/kg ( Rabbit )	> 5.96 mg/L ( Rat ) 6 h
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE 124-17-4	= 6500 mg/kg ( Rat )	= 14500 mg/kg ( Rabbit )	= 72500 mg/m <sup>3</sup> ( Rat ) 4 h
PETROLEUM SOLVENT (NAPTHA) 64742-95-6	= 8400 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	= 3400 ppm ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** Symptoms of overexposure are dizziness, headache, tiredness, nausea, unconsciousness, cessation of breathing. Irritating to eyes and skin.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Chronic Toxicity** NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid repeated exposure. Substances known to be mutagenic to man. Substances known to be carcinogenic to man.

**Sensitization** No information available.

**Mutagenicity** Substances known to be mutagenic to man.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
PETROLEUM SOLVENT (NAPTHA) 64742-95-6	*	-	-	

**Reproductive effects** No information available.

**STOT - single exposure** No information available

**STOT - repeated exposure** No information available

**Target organ effects** Eyes, Central nervous system, liver, kidney.

**Aspiration hazard** No information available.

**Acute Toxicity** 6E-06 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

0.40608 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE 108-65-6		161: 96 h Pimephales promelas mg/L LC50 static	500: 48 h Daphnia magna mg/L EC50
ETHYL 3-ETHOXYPROPIONATE 763-69-9		62: 96 h Pimephales promelas mg/L LC50 static	970: 48 h Daphnia magna mg/L EC50
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE 124-17-4		50 - 70: 96 h Brachydanio rerio mg/L LC50 static 77: 96 h Pimephales promelas mg/L LC50 static	665: 48 h Daphnia magna mg/L LC50
PETROLEUM SOLVENT (NAPTHA) 64742-95-6		9.22: 96 h Oncorhynchus mykiss mg/L LC50	6.14: 48 h Daphnia magna mg/L EC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

Chemical name	log Pow
PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE 108-65-6	0.43
ETHYL 3-ETHOXYPROPIONATE 763-69-9	1.35
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE 124-17-4	1.77

**Other Adverse Effects**

No information available

### 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

<b>Disposal Methods</b>	It must undergo special treatment, e.g. at suitable disposal site, to comply with local regulations.
<b>Contaminated packaging</b>	Empty containers should be taken to an approved waste handling site for recycling or disposal.

### 14. TRANSPORT INFORMATION

#### DOT

**Proper Shipping Name** PAINT & RELATED MATERIAL Not regulated

#### Additional information

Call TNEMEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

### 15. REGULATORY INFORMATION

#### International Inventories

<b>TSCA</b>	Complies
<b>DSL/NDSL</b>	Complies
<b>EINECS/ELINCS</b>	Complies
<b>ENCS</b>	Does Not Comply
<b>IECSC</b>	Complies
<b>KECL</b>	Complies
<b>PICCS</b>	Complies
<b>AICS</b>	Complies

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

#### **The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):**

Chemical name	HAPS Data
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE	

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372:

Chemical name	SARA 313 - Threshold Values
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE - 124-17-4	1.0

#### **SARA 311/312 Hazardous**

##### Categorization

<b>Acute Health Hazard</b>	Yes
<b>Chronic Health Hazard</b>	Yes
<b>Fire Hazard</b>	Yes
<b>Sudden Release of Pressure Hazard</b>	No

Reactive Hazard

No

**California Prop. 65**

:This product can expose you to the following chemicals which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Chemical name	California Prop. 65
PETROLEUM SOLVENT (NAPHTHA) - 64742-95-6	*

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Chemical name	New Jersey	Massachusetts	Pennsylvania
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE 124-17-4	X		X

**16. OTHER INFORMATION**

**NFPA** Health 2 Flammability 2 Instability 1 Physical hazard \*  
**HMIS (Hazardous Material Information System)** Health 2\* Flammability 2 Reactivity 1

Prepared By Tnemec Regulatory Dept: 816-474-3400  
 Revision Date 16-Aug-2017


Revision Summary  
 1 5 7 10 6 8 9 11 14 15

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of SDS**



# Safety Data Sheet

Issue Date 16-Jul-2015

Revision Date 16-Jul-2015

Revision Number 10

## 1. IDENTIFICATION

### Product identifier

**Product Code** F041-0015  
**Product Name** THINNER CLEAR

### Other means of identification

**Common Name** NO. 15 THINNER  
**UN/ID no.** 1170

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

**Manufacturer Address** Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372  
**Distributor** Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203 Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2B
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Specific target organ toxicity (single exposure)	Category 2
Flammable Liquids	Category 2

### Label elements

#### EMERGENCY OVERVIEW

#### **Danger**

#### **Hazard statements**

Harmful if swallowed  
Causes skin irritation  
Causes eye irritation  
May cause genetic defects  
May cause cancer  
May cause damage to organs  
Highly flammable liquid and vapor

**Appearance** opaque**Physical state** liquid**Odor** aromatic**Precautionary Statements****Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Wash face, hands and any exposed skin thoroughly after handling  
 Do not eat, drink or smoke when using this product  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge

**Response**

IF exposed or concerned: Get medical advice/attention  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 If skin irritation occurs: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell  
 Rinse mouth  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store locked up  
 Store in a well-ventilated place. Keep cool  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

Toxic to aquatic life with long lasting effects  
 Inhalation, ingestion, or skin absorption of methanol can cause blindness  
 SEE SAFETY DATA SHEET

Acute Toxicity

0.0983 % of the mixture consists of ingredient(s) of unknown toxicity.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS-No	Weight-%
ETHYL ALCOHOL	-	60 - 100%
METHYL ALCOHOL	-	1 - 10%
ACETIC ACID ETHYL ESTER	-	1 - 10%
METHYL ISOBUTYL KETONE	108-10-1	1 - 10%



\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

##### Description of first aid measures

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
<b>Inhalation</b>	Remove to fresh air. Oxygen or artificial respiration if needed.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

##### Most important symptoms and effects, both acute and delayed

**Notes to physician** Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Water.

##### Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

##### Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

#### 6. ACCIDENTAL RELEASE MEASURES

##### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

##### Environmental Precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

##### Methods and material for containment and cleaning up

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

### Conditions for safe storage, including any incompatibilities

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

**Incompatible products** Strong oxidizing agents. Acids. Alkaline. Amines.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
ETHYL ALCOHOL	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup>	3300 ppm
METHYL ALCOHOL	TWA: 200 ppm Skin STEL: 250 ppm	TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> STEL: 250 ppm STEL: 325 mg/m <sup>3</sup> Skin	6000 ppm
ACETIC ACID ETHYL ESTER	TWA: 400 ppm	TWA: 400 ppm TWA: 1400 mg/m <sup>3</sup>	2000 ppm
METHYL ISOBUTYL KETONE 108-10-1	TWA: 20 ppm STEL: 75 ppm	TWA: 50 ppm TWA: 205 mg/m <sup>3</sup> STEL: 75 ppm STEL: 300 mg/m <sup>3</sup> TWA: 100 ppm TWA: 410 mg/m <sup>3</sup>	500 ppm

### Appropriate engineering controls

**Engineering measures** Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Use chemical resistant splash type goggles.

<b>Skin and body protection</b>	Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
<b>Respiratory protection</b>	Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.
<b>General hygiene considerations</b>	Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	liquid	<b>Odor</b>	aromatic
<b>Appearance</b>	opaque	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		
<b><u>Property</u></b>	<b><u>Values</u></b>	<b><u>Remarks</u></b>	
<b>pH</b>		No data available	
<b>Melting point / freezing point</b>		No data available	
<b>Boiling point / boiling range</b>	116 °C / 241.0 °F		
<b>Flash point</b>	7 °C / 45 °F		
<b>Evaporation rate</b>		Pensky Martens - Closed Cup	
<b>Flammability (solid, gas)</b>		No data available	
<b>Flammability Limit in Air</b>		Not applicable	
<b>Upper flammability limit</b>	N/A	No data available	
<b>Lower flammability limit</b>	1.0		
<b>Vapor pressure</b>		No data available	
<b>Vapor density</b>		No data available	
<b>Specific gravity</b>	.79377	g/cm <sup>3</sup>	
<b>Water solubility</b>	Insoluble in cold water		
<b>Solubility in other solvents</b>		No data available	
<b>Partition coefficient: n-octanol/water</b>		No data available	
<b>Autoignition temperature</b>		No data available	
<b>Decomposition temperature</b>		No data available	
<b>Kinematic viscosity</b>		No data available	
<b>Dynamic viscosity</b>		No data available	
<b><u>Other Information</u></b>			
<b>Density</b>	6.60533 lbs/gal		
<b>Volatile organic compounds (VOC) content</b>	6.599 lbs/gal		
<b>Total volatiles weight percent</b>	100.0000 %		
<b>Total volatiles volume percent</b>	100.0000 %		

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Possibility of hazardous reactions

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Strong oxidizing agents, Acids, Alkaline, Amines

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

<b>11. TOXICOLOGICAL INFORMATION</b>
--------------------------------------

**Information on Likely Routes of Exposure**

<b>Inhalation</b>	Aspiration into lungs can produce severe lung damage.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Skin contact</b>	CAUSES SKIN IRRITATION.
<b>Ingestion</b>	Harmful if swallowed. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
ETHYL ALCOHOL	= 7060 mg/kg ( Rat )		= 124.7 mg/L ( Rat ) 4 h
METHYL ALCOHOL	= 6200 mg/kg ( Rat )	= 15800 mg/kg ( Rabbit )	= 22500 ppm ( Rat ) 8 h = 64000 ppm ( Rat ) 4 h
ACETIC ACID ETHYL ESTER	= 5620 mg/kg ( Rat )	> 18000 mg/kg ( Rabbit ) > 20 mL/kg ( Rabbit )	
METHYL ISOBUTYL KETONE 108-10-1	= 2080 mg/kg ( Rat )	= 3000 mg/kg ( Rabbit )	= 8.2 mg/L ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritating to eyes and skin.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Chronic Toxicity** May cause cancer. Substances known to be mutagenic to man.  
**Sensitization** No information available.  
**Mutagenicity** May cause genetic defects.  
**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	ACGIH	IARC	NTP	OSHA
ETHYL ALCOHOL	A3	Group 1	Known	X
METHYL ISOBUTYL KETONE 108-10-1	A3	Group 2B		X

**Reproductive effects** No information available.  
**STOT - single exposure** No information available  
**STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure  
**Target organ effects** blood, Central nervous system, Gastrointestinal tract, Eyes, liver, Reproductive System, respiratory system, kidney, Skin.  
**Aspiration hazard** Risk of serious damage to the lungs (by aspiration).

**Acute Toxicity** 0.0983 % of the mixture consists of ingredient(s) of unknown toxicity.

<b>12. ECOLOGICAL INFORMATION</b>
-----------------------------------

**Ecotoxicity**

Toxic to aquatic life with long lasting effects

0.0983 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
ETHYL ALCOHOL		100: 96 h Pimephales promelas mg/L LC50 static 13400 - 15100: 96 h Pimephales promelas mg/L LC50 flow-through 12.0 - 16.0: 96 h Oncorhynchus mykiss mL/L LC50 static	9268 - 14221: 48 h Daphnia magna mg/L LC50 10800: 24 h Daphnia magna mg/L EC50 2: 48 h Daphnia magna mg/L EC50 Static
METHYL ALCOHOL		28200: 96 h Pimephales promelas mg/L LC50 flow-through 100: 96 h Pimephales promelas mg/L LC50 static 19500 - 20700: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 18 - 20: 96 h Oncorhynchus mykiss mL/L LC50 static 13500 - 17600: 96 h Lepomis macrochirus mg/L LC50 flow-through	
ACETIC ACID ETHYL ESTER	3300: 48 h Desmodesmus subspicatus mg/L EC50	352 - 500: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 220 - 250: 96 h Pimephales promelas mg/L LC50 flow-through 484: 96 h Oncorhynchus mykiss mg/L LC50 flow-through	560: 48 h Daphnia magna mg/L EC50 Static
METHYL ISOBUTYL KETONE 108-10-1	400: 96 h Pseudokirchneriella subcapitata mg/L EC50	496 - 514: 96 h Pimephales promelas mg/L LC50 flow-through	170: 48 h Daphnia magna mg/L EC50

#### Persistence and degradability

No information available.

#### Bioaccumulation

No information available.

#### Mobility in Environmental Media

Component	log Pow
ETHYL ALCOHOL	-0.32
METHYL ALCOHOL	-0.77
ACETIC ACID ETHYL ESTER	0.6
METHYL ISOBUTYL KETONE 108-10-1	1.19

#### Other Adverse Effects

No information available

### 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

##### **Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

##### **Contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

Component	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
METHYL ALCOHOL		Included in waste stream: F039		U154
ACETIC ACID ETHYL ESTER		Included in waste stream: F039		U112

METHYL ISOBUTYL KETONE 108-10-1		Included in waste stream: F039		U161
---------------------------------------	--	-----------------------------------	--	------

Component	CAWAST
ETHYL ALCOHOL	Toxic Ignitable
METHYL ALCOHOL	Toxic Ignitable
ACETIC ACID ETHYL ESTER	Toxic Ignitable

#### 14. TRANSPORT INFORMATION

##### DOT

**UN/ID no.** 1170  
**Proper Shipping Name** ETHYL ALCOHOL  
**Hazard Class** 3  
**Packing Group** II  
**Emergency Response Guide Number** 127

##### IATA

**UN/ID no.** 1170  
**Proper Shipping Name** ETHYL ALCOHOL  
**Hazard Class** 3  
**Packing Group** II  
**ERG Code** 364

##### Additional information

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

#### 15. REGULATORY INFORMATION

##### International Inventories

**TSCA** Complies  
**DSL/NDSL** Complies  
**EINECS/ELINCS** Complies  
**ENCS** Complies  
**IECSC** Complies  
**KECL** Complies  
**PICCS** Complies  
**AICS** Complies

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):**

**Component**  
 METHYL ALCOHOL  
 METHYL ISOBUTYL KETONE

**HAPS Data**

##### United States of America

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372:

Component	SARA 313 - Threshold Values
METHYL ALCOHOL -	1.0
METHYL ISOBUTYL KETONE - 108-10-1	1.0

**SARA 311/312 Hazardous**

**Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**CERCLA**

Component	Hazardous Substances RQs	CERCLA EHS RQs	RQ
METHYL ALCOHOL	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
ACETIC ACID ETHYL ESTER	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
METHYL ISOBUTYL KETONE 108-10-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

**United States of America**

**California Prop. 65**

WARNING! This product contains a chemical known in the State of California to cause cancer

Component	California Prop. 65
ETHYL ALCOHOL -	Carcinogen Developmental
METHYL ALCOHOL -	Developmental
METHYL ISOBUTYL KETONE - 108-10-1	Carcinogen Developmental

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Component	New Jersey	Massachusetts	Pennsylvania
ETHYL ALCOHOL	X	X	X
METHYL ALCOHOL	X	X	X
ACETIC ACID ETHYL ESTER	X	X	X
METHYL ISOBUTYL KETONE 108-10-1	X	X	X

**16. OTHER INFORMATION**

<b>NFPA</b>	Health 2	Flammability 3	Instability 1	Physical hazard *
<b>HMIS (Hazardous Material Information System)</b>	Health 2*	Flammability 3	Reactivity 1	

Prepared By  
Revision Date  
Revision Summary  
9 4 5 7 10 8 11 14

Tnemec Regulatory Dept: 816-474-3400  
16-Jul-2015

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**





# Safety Data Sheet

Issue Date 16-Jul-2015

Revision Date 16-Jul-2015

Revision Number 7

## 1. IDENTIFICATION

### Product identifier

**Product Code** F041-0018  
**Product Name** THINNER CLEAR

### Other means of identification

**Common Name** NO. 18 THINNER

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372

#### **Distributor**

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203 Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Inhalation (Vapors)	Category 5
Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3
Flammable Liquids	Category 3

### Label elements

## EMERGENCY OVERVIEW

### **WARNING**

#### **Hazard statements**

May be harmful if inhaled  
Causes serious eye irritation  
May cause respiratory irritation. May cause drowsiness or dizziness  
Flammable liquid and vapor



**Appearance** opaque

**Physical state** liquid

**Odor** aromatic

**Precautionary Statements**

**Prevention**

- Wash face, hands and any exposed skin thoroughly after handling
- Wear protective gloves/protective clothing/eye protection/face protection
- Avoid breathing dust/fume/gas/mist/vapors/spray
- Use only outdoors or in a well-ventilated area
- Keep away from heat/sparks/open flames/hot surfaces. — No smoking
- Keep container tightly closed
- Ground/bond container and receiving equipment
- Use explosion-proof electrical/ventilating/lighting/mixing/equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge
- Keep cool

**Response**

- Get medical advice/attention if you feel unwell
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- If eye irritation persists: Get medical advice/attention
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- Call a POISON CENTER or doctor/physician if you feel unwell
- In case of fire: Use CO2, dry chemical, or foam for extinction

**Storage**

- Store in a well-ventilated place. Keep container tightly closed
- Store locked up
- Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

**Other information**

SEE SAFETY DATA SHEET

Acute Toxicity

0 % of the mixture consists of ingredient(s) of unknown toxicity.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS-No	Weight-%
PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE	108-65-6	60 - 100%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

**4. FIRST AID MEASURES**

**Description of first aid measures**

**General advice** If symptoms persist, call a physician.

---

<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

**Most important symptoms and effects, both acute and delayed**

**Notes to physician** Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

**Suitable extinguishing media**

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

**Specific hazards arising from the chemical**

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

**Protective equipment and precautions for firefighters**

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Ensure adequate ventilation. Use personal protective equipment. Avoid contact with eyes, skin and clothing. Remove all sources of ignition.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Handle in accordance with good industrial hygiene and safety practice. Wear personal protective equipment. Avoid contact with eyes, skin and clothing. Remove and wash contaminated clothing before re-use. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not breathe vapours or spray mist. Do not ingest. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

### Conditions for safe storage, including any incompatibilities

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

**Incompatible products** Strong oxidizing agents. Acids.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure guidelines

#### Appropriate engineering controls

**Engineering measures** Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Safety glasses with side-shields Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.

**Skin and body protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection** Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	liquid	<b>Odor</b>	aromatic
<b>Appearance</b>	opaque	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		
<b>Property</b>	<b>Values</b>	<b>Remarks</b>	
<b>pH</b>		No data available	
<b>Melting point / freezing point</b>		No data available	
<b>Boiling point / boiling range</b>	139 °C / 283 °F		
<b>Flash point</b>	47 °C / 116 °F		Pensky Martens - Closed Cup

Evaporation rate		No data available
Flammability (solid, gas)		Not applicable
Flammability Limit in Air		No data available
Upper flammability limit	N/A	
Lower flammability limit	1.0	
Vapor pressure		No data available
Vapor density		No data available
Specific gravity	0.96283	g/cm <sup>3</sup>
Water solubility	Insoluble in cold water	
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition temperature		No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity		No data available

**Other Information**

Density	8.03 lbs/gal
Volatile organic compounds (VOC) content	8.03 lbs/gal
Total volatiles weight percent	100 %
Total volatiles volume percent	100 %

## 10. STABILITY AND REACTIVITY

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Strong oxidizing agents, Acids

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

## 11. TOXICOLOGICAL INFORMATION

**Information on Likely Routes of Exposure**

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Skin contact</b>	CAUSES SKIN IRRITATION.
<b>Ingestion</b>	Harmful if swallowed.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE 108-65-6	= 8532 mg/kg ( Rat )	> 5 g/kg ( Rabbit )	

**Information on toxicological effects**

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritating to eyes and skin.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Chronic Toxicity** NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**Sensitization** No information available.

**Mutagenicity** No information available.

**Carcinogenicity** There are no known carcinogenic chemicals in this product.

**Reproductive effects** No information available.

**STOT - single exposure** Skin, Eyes, Respiratory system

**STOT - repeated exposure** No information available

**Aspiration hazard** No information available.

**Acute Toxicity** 0 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE 108-65-6		161: 96 h Pimephales promelas mg/L LC50 static	500: 48 h Daphnia magna mg/L EC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

Component	log Pow
PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE 108-65-6	0.43

**Other Adverse Effects** No information available

## 13. DISPOSAL CONSIDERATIONS

**Waste treatment methods**

**Disposal Methods** Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. TRANSPORT INFORMATION

**DOT**

**Proper Shipping Name** Paint related material

**IATA**

**UN/ID no.** 1193  
**Proper Shipping Name** Flammable liquid n.o.s (P. M. Acetate)  
**Hazard Class** 3  
**Packing Group** III  
**ERG Code** 366

**Additional information** Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

<b>15. REGULATORY INFORMATION</b>
-----------------------------------

**International Inventories**

<b>TSCA</b>	Complies
<b>DSL/NDSL</b>	Complies
<b>EINECS/ELINCS</b>	Complies
<b>ENCS</b>	Complies
<b>IECSC</b>	Complies
<b>KECL</b>	Complies
<b>PICCS</b>	Complies
<b>AICS</b>	Complies

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

**United States of America****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372.

**SARA 311/312 Hazardous****Categorization**

<b>Acute Health Hazard</b>	Yes
<b>Chronic Health Hazard</b>	No
<b>Fire Hazard</b>	Yes
<b>Sudden Release of Pressure Hazard</b>	No
<b>Reactive Hazard</b>	No

**CERCLA****United States of America****California Prop. 65**

This product does not contain any Proposition 65 chemicals

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

State Right-to-Know

**16. OTHER INFORMATION**

<u>NFPA</u>	Health 2	Flammability 2	Instability 0	Physical hazard *
<u>HMIS (Hazardous Material Information System)</u>	Health 2	Flammability 2	Reactivity 0	

Prepared By Tnemec Regulatory Dept: 816-474-3400  
 Revision Date 16-Jul-2015  
 Revision Summary  
 9 4 5 7 10 8 11 14 6 15


Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**





# Safety Data Sheet

Issue Date 16-Jul-2015

Revision Date 16-Jul-2015

Revision Number 8

## 1. IDENTIFICATION

### Product identifier

**Product Code** F041-0019  
**Product Name** THINNER CLEAR

### Other means of identification

**Common Name** NO. 19 THINNER  
**UN/ID no.** 1263

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO  
64120-1372

#### **Distributor**

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203  
Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Vapors)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 2
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable Liquids	Category 2

### Label elements

#### EMERGENCY OVERVIEW

Danger

**Hazard statements**

Harmful if swallowed  
Harmful if inhaled  
Causes skin irritation  
Causes serious eye irritation  
Suspected of causing cancer  
Suspected of damaging fertility or the unborn child  
May cause respiratory irritation. May cause drowsiness or dizziness  
May cause damage to organs through prolonged or repeated exposure  
May be fatal if swallowed and enters airways  
Highly flammable liquid and vapor

**Appearance** opaque**Physical state** liquid**Odor** aromatic**Precautionary Statements****Prevention**

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Use personal protective equipment as required  
Wash face, hands and any exposed skin thoroughly after handling  
Do not eat, drink or smoke when using this product  
Use only outdoors or in a well-ventilated area  
Do not breathe dust/fume/gas/mist/vapors/spray  
Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
Keep container tightly closed  
Ground/bond container and receiving equipment  
Use explosion-proof electrical/ventilating/lighting/mixing/equipment  
Use only non-sparking tools  
Take precautionary measures against static discharge  
Keep cool

**Response**

IF exposed or concerned: Get medical advice/attention  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
If eye irritation persists: Get medical advice/attention  
If skin irritation occurs: Get medical advice/attention  
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
Wash contaminated clothing before reuse  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
Rinse mouth  
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
Do NOT induce vomiting  
In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store locked up  
Store in a well-ventilated place. Keep container tightly closed  
Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

**Other information**

Toxic to aquatic life with long lasting effects

May be harmful in contact with skin

SEE SAFETY DATA SHEET

Acute Toxicity

0 % of the mixture consists of ingredient(s) of unknown toxicity.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS-No	Weight-%
TOLUENE	108-88-3	30 - 60%
METHYL ISOBUTYL KETONE	108-10-1	30 - 60%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

**4. FIRST AID MEASURES****Description of first aid measures**

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	Call a physician or poison control center immediately. Aspiration hazard. Do not induce vomiting without medical advice.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

**Most important symptoms and effects, both acute and delayed**

**Notes to physician** Treat symptomatically.

**5. FIRE-FIGHTING MEASURES****Suitable extinguishing media**

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

**Specific hazards arising from the chemical**

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes FLAMMABLE

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

**Protective equipment and precautions for firefighters**

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Handling** Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

**Conditions for safe storage, including any incompatibilities**

**Storage** Keep away from heat, sparks and flame. VAPORS MAY CAUSE FLASH FIRE. Use only in an area containing flame proof equipment. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation. Keep out of the reach of children.

**Incompatible products** Strong oxidizing agents. Strong acids.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters****Exposure guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
TOLUENE 108-88-3	TWA: 20 ppm	TWA: 100 ppm TWA: 375 mg/m <sup>3</sup> STEL: 150 ppm STEL: 560 mg/m <sup>3</sup> TWA: 200 ppm Ceiling: 300 ppm	500 ppm
METHYL ISOBUTYL KETONE 108-10-1	TWA: 20 ppm STEL: 75 ppm	TWA: 50 ppm TWA: 205 mg/m <sup>3</sup> STEL: 75 ppm STEL: 300 mg/m <sup>3</sup> TWA: 100 ppm TWA: 410 mg/m <sup>3</sup>	500 ppm

**Appropriate engineering controls**

**Engineering measures** Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Safety glasses with side-shields If splashes are likely to occur, wear face-shield.

**Skin and body protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection** Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	aromatic
<b>Appearance</b>	opaque	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
<b>pH</b>		No data available
<b>Melting point / freezing point</b>		No data available
<b>Boiling point / boiling range</b>	110 °C / 230 °F	
<b>Flash point</b>	5 °C / 41 °F	Pensky Martens - Closed Cup
<b>Evaporation rate</b>		No data available
<b>Flammability (solid, gas)</b>		Not applicable
<b>Flammability Limit in Air</b>		No data available
<b>Upper flammability limit</b>	N/A	
<b>Lower flammability limit</b>	1.0	
<b>Vapor pressure</b>		No data available
<b>Vapor density</b>		No data available
<b>Specific gravity</b>	0.83453	g/cm3
<b>Water solubility</b>	Insoluble in cold water	
<b>Solubility in other solvents</b>		No data available
<b>Partition coefficient: n-octanol/water</b>		No data available
<b>Autoignition temperature</b>		No data available
<b>Decomposition temperature</b>		No data available
<b>Kinematic viscosity</b>		No data available
<b>Dynamic viscosity</b>		No data available

**Other Information**

<b>Density</b>	6.96 lbs/gal
<b>Volatile organic compounds (VOC) content</b>	6.96 lbs/gal
<b>Total volatiles weight percent</b>	100 %
<b>Total volatiles volume percent</b>	100 %

## 10. STABILITY AND REACTIVITY

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Strong oxidizing agents, Strong acids

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

<b>11. TOXICOLOGICAL INFORMATION</b>
--------------------------------------

**Information on Likely Routes of Exposure**

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Skin contact</b>	CAUSES SKIN IRRITATION. Irritating to skin.
<b>Ingestion</b>	Harmful if swallowed. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
TOLUENE 108-88-3	= 2600 mg/kg ( Rat )	= 12000 mg/kg ( Rabbit )	= 12.5 mg/L ( Rat ) 4 h
METHYL ISOBUTYL KETONE 108-10-1	= 2080 mg/kg ( Rat )	= 3000 mg/kg ( Rabbit )	= 8.2 mg/L ( Rat ) 4 h

**Information on toxicological effects**

<b>Symptoms</b>	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritating to eyes and skin.
-----------------	---

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

<b>Chronic Toxicity</b>	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. May cause cancer. Substances known to impair fertility.
<b>Sensitization</b>	No information available.
<b>Mutagenicity</b>	No information available.
<b>Carcinogenicity</b>	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	ACGIH	IARC	NTP	OSHA
TOLUENE 108-88-3		Group 3		
METHYL ISOBUTYL KETONE 108-10-1	A3	Group 2B		X

<b>Reproductive effects</b>	Suspected of damaging fertility or the unborn child.
<b>STOT - single exposure</b>	Skin, Eyes, Central Nervous System (CNS)
<b>STOT - repeated exposure</b>	Causes damage to organs through prolonged or repeated exposure
<b>Target organ effects</b>	Central nervous system, Eyes, kidney, liver, respiratory system, Skin.

**Aspiration hazard** Risk of serious damage to the lungs (by aspiration).

**Acute Toxicity** 0 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Toxic to aquatic life with long lasting effects

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
TOLUENE 108-88-3	12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 433: 96 h Pseudokirchneriella subcapitata mg/L EC50	5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 12.6: 96 h Pimephales promelas mg/L LC50 static 54: 96 h Oryzias latipes mg/L LC50 static 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static 11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 28.2: 96 h Poecilia reticulata mg/L LC50 semi-static 15.22 - 19.05: 96 h Pimephales promelas mg/L LC50 flow-through 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static	11.5: 48 h Daphnia magna mg/L EC50 5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static
METHYL ISOBUTYL KETONE 108-10-1	400: 96 h Pseudokirchneriella subcapitata mg/L EC50	496 - 514: 96 h Pimephales promelas mg/L LC50 flow-through	170: 48 h Daphnia magna mg/L EC50

### Persistence and degradability

No information available.

### Bioaccumulation

No information available.

### Mobility in Environmental Media

Component	log Pow
TOLUENE 108-88-3	2.65
METHYL ISOBUTYL KETONE 108-10-1	1.19

### Other Adverse Effects

No information available

## 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

#### **Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

#### **Contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

Component	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
TOLUENE 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151		U220
METHYL ISOBUTYL KETONE 108-10-1		Included in waste stream: F039		U161

Component	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
TOLUENE 108-88-3			Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	

Component	CAWAST
TOLUENE 108-88-3	Toxic Ignitable

**14. TRANSPORT INFORMATION**

**DOT**

UN/ID no. 1263  
 Proper Shipping Name Paint related material  
 Hazard Class 3  
 Packing Group II  
 Emergency Response Guide Number 128

**IATA**

UN/ID no. 1263  
 Proper Shipping Name Paint related material  
 Hazard Class 3  
 Packing Group II  
 ERG Code 366

**Additional information**

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

**15. REGULATORY INFORMATION**

**International Inventories**

TSCA Complies  
 DSL/NDSL Complies  
 EINECS/ELINCS Complies  
 ENCS Complies  
 IECSC Complies  
 KECL Complies  
 PICCS Complies  
 AICS Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List  
 EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances  
 ENCS - Japan Existing and New Chemical Substances  
 IECSC - China Inventory of Existing Chemical Substances



KECL - Korean Existing and Evaluated Chemical Substances  
 PICCS - Philippines Inventory of Chemicals and Chemical Substances  
 AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

Component	HAPS Data
TOLUENE	
METHYL ISOBUTYL KETONE	

**United States of America**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

Component	SARA 313 - Threshold Values
TOLUENE - 108-88-3	1.0
METHYL ISOBUTYL KETONE - 108-10-1	1.0

**SARA 311/312 Hazardous**

**Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
TOLUENE 108-88-3	1000 lb	X	X	X

**CERCLA**

Component	Hazardous Substances RQs	CERCLA EHS RQs	RQ
TOLUENE 108-88-3	1000 lb 1 lb		RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ
METHYL ISOBUTYL KETONE 108-10-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

**United States of America**

**California Prop. 65**

WARNING! This product contains a chemical known in the State of California to cause cancer

Component	California Prop. 65
TOLUENE - 108-88-3	Developmental Female Reproductive
METHYL ISOBUTYL KETONE - 108-10-1	Carcinogen Developmental

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Component	New Jersey	Massachusetts	Pennsylvania
TOLUENE 108-88-3	X	X	X
METHYL ISOBUTYL KETONE 108-10-1	X	X	X

**16. OTHER INFORMATION**


<u>NFPA</u>	Health 2	Flammability 3	Instability 0	Physical hazard *
<u>HMIS (Hazardous</u>	Health 2*	Flammability 3	Reactivity 0	
<u>Material Information</u>				
<u>System)</u>				

Prepared By Tnemec Regulatory Dept: 816-474-3400  
Revision Date 16-Jul-2015  
Revision Summary  
9 4 5 7 10 8 11 14

Disclaimer  
For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**



# Safety Data Sheet

Issue Date 16-Jul-2015

Revision Date 16-Jul-2015

Revision Number 8

## 1. IDENTIFICATION

### Product identifier

**Product Code** F041-0024  
**Product Name** THINNER CLEAR

### Other means of identification

**Common Name** NO. 24 THINNER

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372

#### **Distributor**

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203 Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Acute toxicity - Dermal	Category 5
Acute toxicity - Inhalation (Vapors)	Category 4
Serious eye damage/eye irritation	Category 2B
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 2
Flammable Liquids	Category 3


### Label elements

#### EMERGENCY OVERVIEW

#### **WARNING**

##### **Hazard statements**

Harmful if swallowed  
May be harmful in contact with skin  
Harmful if inhaled  
Causes eye irritation  
May cause respiratory irritation. May cause drowsiness or dizziness  
May be harmful if swallowed and enters airways  
Flammable liquid and vapor



**Appearance** opaque
**Physical state** liquid
**Odor** aromatic

**Precautionary Statements**

**Prevention**

- Wash face, hands and any exposed skin thoroughly after handling
- Do not eat, drink or smoke when using this product
- Avoid breathing dust/fume/gas/mist/vapors/spray
- Use only outdoors or in a well-ventilated area
- Keep away from heat/sparks/open flames/hot surfaces. — No smoking
- Keep container tightly closed
- Ground/bond container and receiving equipment
- Use explosion-proof electrical/ventilating/lighting/mixing/equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge
- Wear protective gloves/protective clothing/eye protection/face protection
- Keep cool

**Response**

- Call a POISON CENTER or doctor/physician if you feel unwell
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- If eye irritation persists: Get medical advice/attention
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- Call a POISON CENTER or doctor/physician if you feel unwell
- Rinse mouth
- IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
- Do NOT induce vomiting
- In case of fire: Use CO2, dry chemical, or foam for extinction

**Storage**

- Store locked up
- Store in a well-ventilated place. Keep container tightly closed
- Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

**Other information**

May be harmful in contact with skin  
 SEE SAFETY DATA SHEET  
 Acute Toxicity 0 % of the mixture consists of ingredient(s) of unknown toxicity.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS-No	Weight-%
Trade secret	-	60 - 100%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

##### Description of first aid measures

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	Call a physician or poison control center immediately. Aspiration hazard. Do not induce vomiting without medical advice.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

##### Most important symptoms and effects, both acute and delayed

**Notes to physician** Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

##### Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

##### Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

#### 6. ACCIDENTAL RELEASE MEASURES

##### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

##### Environmental Precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

##### Methods and material for containment and cleaning up

<b>Methods for containment</b>	Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.
<b>Methods for cleaning up</b>	If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

<b>Handling</b>	Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.
-----------------	---

### Conditions for safe storage, including any incompatibilities

<b>Storage</b>	Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.
<b>Incompatible products</b>	Strong oxidizing agents. Strong acids. Alkaline.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
Trade secret	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m <sup>3</sup>	800 ppm

### Appropriate engineering controls

<b>Engineering measures</b>	Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.
-----------------------------	---

### Individual protection measures, such as personal protective equipment

<b>Eye/face protection</b>	Use chemical resistant splash type goggles.
<b>Skin and body protection</b>	Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
<b>Respiratory protection</b>	Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.
<b>General hygiene considerations</b>	Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	aromatic
<b>Appearance</b>	opaque	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
<b>pH</b>		No data available
<b>Melting point / freezing point</b>		No data available
<b>Boiling point / boiling range</b>	147 °C / 297 °F	
<b>Flash point</b>	39 °C / 102 °F	
<b>Evaporation rate</b>		Pensky Martens - Closed Cup
<b>Flammability (solid, gas)</b>		No data available
<b>Flammability Limit in Air</b>		Not applicable
<b>Upper flammability limit</b>	N/A	No data available
<b>Lower flammability limit</b>	1.0	
<b>Vapor pressure</b>		No data available
<b>Vapor density</b>		No data available
<b>Specific gravity</b>	0.81535	g/cm3
<b>Water solubility</b>	Insoluble in cold water	
<b>Solubility in other solvents</b>		No data available
<b>Partition coefficient: n-octanol/water</b>		No data available
<b>Autoignition temperature</b>		No data available
<b>Decomposition temperature</b>		No data available
<b>Kinematic viscosity</b>		No data available
<b>Dynamic viscosity</b>	0.8 mPa s	approx

**Other Information**

<b>Density</b>	6.79999 lbs/gal
<b>Volatile organic compounds (VOC) content</b>	6.79999 lbs/gal
<b>Total volatiles weight percent</b>	100 %
<b>Total volatiles volume percent</b>	100 %

**10. STABILITY AND REACTIVITY****Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Strong oxidizing agents, Strong acids, Alkaline

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

**11. TOXICOLOGICAL INFORMATION****Information on Likely Routes of Exposure****Inhalation**

May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.

<b>Eye contact</b>	Causes serious eye irritation.
<b>Skin contact</b>	May cause irritation.
<b>Ingestion</b>	Harmful if swallowed. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Trade secret	= 1600 mg/kg ( Rat ) = 1670 mg/kg ( Rat )	= 12.6 mL/kg ( Rabbit ) = 12600 µL/kg ( Rabbit )	> 2000 ppm ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

<b>Chronic Toxicity</b>	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
<b>Sensitization</b>	No information available.
<b>Mutagenicity</b>	No information available.
<b>Carcinogenicity</b>	There are no known carcinogenic chemicals in this product.
<b>Reproductive effects</b>	No information available.
<b>STOT - single exposure</b>	Skin, Eyes, Central Nervous System (CNS), Peripheral Nervous System (PNS), Respiratory system
<b>STOT - repeated exposure</b>	No information available
<b>Aspiration hazard</b>	Risk of serious damage to the lungs (by aspiration).
<b>Acute Toxicity</b>	0 % of the mixture consists of ingredient(s) of unknown toxicity.

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

0 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
Trade secret		126 - 137: 96 h Pimephales promelas mg/L LC50 flow-through	

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

Component	log Pow
Trade secret	1.98

**Other Adverse Effects**

No information available

**13. DISPOSAL CONSIDERATIONS****Waste treatment methods****Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.



**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. TRANSPORT INFORMATION

### DOT

**Proper Shipping Name** Paint related material

### IATA

**UN/ID no.** 1263  
**Proper Shipping Name** N-AMYL METHYL KETONE  
**Hazard Class** 3  
**Packing Group** III  
**ERG Code** 366

### Additional information

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

## 15. REGULATORY INFORMATION

### International Inventories

<b>TSCA</b>	Complies
<b>DSL/NDSL</b>	Complies
<b>EINECS/ELINCS</b>	Complies
<b>ENCS</b>	Complies
<b>IECSC</b>	Complies
<b>KECL</b>	Complies
<b>PICCS</b>	Complies
<b>AICS</b>	Complies

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

### United States of America

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372.

#### **SARA 311/312 Hazardous**

##### Categorization

<b>Acute Health Hazard</b>	Yes
<b>Chronic Health Hazard</b>	No
<b>Fire Hazard</b>	Yes
<b>Sudden Release of Pressure Hazard</b>	No
<b>Reactive Hazard</b>	No

### CERCLA

**United States of America**

**California Prop. 65**

This product does not contain any Proposition 65 chemicals

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Component	New Jersey	Massachusetts	Pennsylvania
Trade secret	X	X	X

**16. OTHER INFORMATION**

<b><u>NFPA</u></b>	Health 2	Flammability 2	Instability 0	Physical hazard -
<b><u>HMIS (Hazardous Material Information System)</u></b>	Health 2	Flammability 2	Reactivity 0	


Prepared By Tnemec Regulatory Dept: 816-474-3400  
 Revision Date 16-Jul-2015  
 Revision Summary  
 9 4 5 7 10 8 11 14 15

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**



# Safety Data Sheet

Issue Date 10-Jul-2015

Revision Date 10-Jul-2015

Revision Number 9

## 1. IDENTIFICATION

### Product identifier

**Product Code** F041-0039  
**Product Name** THINNER CLEAR

### Other means of identification

**Common Name** NO. 39 THINNER

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372

#### **Distributor**

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203 Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Serious eye damage/eye irritation	Category 2B
Specific target organ toxicity (single exposure)	Category 3
Flammable Liquids	Category 3

### Label elements

#### EMERGENCY OVERVIEW

#### **WARNING**

#### **Hazard statements**

Harmful if swallowed  
Causes eye irritation  
May cause respiratory irritation. May cause drowsiness or dizziness  
Flammable liquid and vapor

**Appearance** opaque**Physical state** liquid**Odor** aromatic**Precautionary Statements****Prevention**

Wash face, hands and any exposed skin thoroughly after handling  
 Do not eat, drink or smoke when using this product  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Use only outdoors or in a well-ventilated area  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Keep cool

**Response**

Get medical advice/attention if you feel unwell  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Call a POISON CENTER or doctor/physician if you feel unwell  
 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell  
 Rinse mouth  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store in a well-ventilated place. Keep container tightly closed  
 Store locked up  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

Acute Toxicity

14.26497 % of the mixture consists of ingredient(s) of unknown toxicity.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS-No	Weight-%
2-HEPTANONE	-	30 - 60%
ETHYL 3-ETHOXYPROPIONATE	763-69-9	30 - 60%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

**4. FIRST AID MEASURES**

**Description of first aid measures**

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

**Most important symptoms and effects, both acute and delayed**

**Notes to physician** Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

**Suitable extinguishing media**

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Water.

**Specific hazards arising from the chemical**

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

**Protective equipment and precautions for firefighters**

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Ensure adequate ventilation. Use personal protective equipment. Avoid contact with eyes, skin and clothing. Remove all sources of ignition.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Handle in accordance with good industrial hygiene and safety practice. Wear personal protective equipment. Avoid contact with eyes, skin and clothing. Remove and wash contaminated clothing before re-use. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not breathe vapours or spray mist. Ensure adequate ventilation. Wash thoroughly after handling.

### Conditions for safe storage, including any incompatibilities

**Storage** Keep containers tightly closed in a cool, well-ventilated place. Keep out of the reach of children.

**Incompatible products** Strong oxidizing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
2-HEPTANONE	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m <sup>3</sup>	800 ppm

### Appropriate engineering controls

**Engineering measures** Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Use chemical resistant splash type goggles.

**Skin and body protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection** Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	liquid	<b>Odor</b>	aromatic
<b>Appearance</b>	opaque	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
pH		No data available
Melting point / freezing point		No data available
Boiling point / boiling range	72 °C / 162 °F	
Flash point	48 °C / 118 °F	
Evaporation rate		Pensky Martens - Closed Cup
Flammability (solid, gas)		No data available
Flammability Limit in Air		Not applicable
Upper flammability limit	N/A	No data available
Lower flammability limit	1.0	
Vapor pressure		No data available
Vapor density		No data available
Specific gravity	0.87879	g/cm3
Water solubility	Insoluble in cold water	
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition temperature		No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity		No data available

**Other Information**

Density	7.32909 lbs/gal
Volatile organic compounds (VOC) content	6.26417 lbs/gal
Total volatiles weight percent	85.47 %
Total volatiles volume percent	86.26 %

**10. STABILITY AND REACTIVITY****Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Strong oxidizing agents

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

**11. TOXICOLOGICAL INFORMATION****Information on Likely Routes of Exposure**

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye contact</b>	Causes serious eye damage.
<b>Skin contact</b>	CAUSES SKIN IRRITATION.

**Ingestion**

Harmful if swallowed. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
2-HEPTANONE	= 1600 mg/kg ( Rat ) = 1670 mg/kg ( Rat )	= 12.6 mL/kg ( Rabbit ) = 12600 µL/kg ( Rabbit )	> 2000 ppm ( Rat ) 4 h
ETHYL 3-ETHOXYPROPIONATE 763-69-9	= 3200 mg/kg ( Rat )	= 10 mL/kg ( Rabbit )	

**Information on toxicological effects****Symptoms**

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Eye Damage.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure****Sensitization**

No information available.

**Mutagenicity**

No information available.

**Carcinogenicity**

There are no known carcinogenic chemicals in this product.

**Reproductive effects**

No information available.

**STOT - single exposure**

Eyes, Central Nervous System (CNS)

**STOT - repeated exposure**

No information available

**Aspiration hazard**

No information available.

**Acute Toxicity**

14.26497 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

0.84656 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
2-HEPTANONE		126 - 137: 96 h Pimephales promelas mg/L LC50 flow-through	
ETHYL 3-ETHOXYPROPIONATE 763-69-9		62: 96 h Pimephales promelas mg/L LC50 static	970: 48 h Daphnia magna mg/L EC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

Component	log Pow
2-HEPTANONE	1.98
ETHYL 3-ETHOXYPROPIONATE 763-69-9	1.35

**Other Adverse Effects**

No information available

## 13. DISPOSAL CONSIDERATIONS

**Waste treatment methods****Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.



## 14. TRANSPORT INFORMATION

**DOT**

**Proper Shipping Name** PAINT & RELATED MATERIAL-(NMFC 149980 SUB 2)  
**Emergency Response Guide Number** 128

**IATA**

**UN/ID no.** 1993  
**Proper Shipping Name** FLAMMABLE LIQUID N.O.S. (HEXYL ACETATE)  
**Hazard Class** 3  
**Packing Group** III  
**ERG Code** 366

**Additional information**

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

## 15. REGULATORY INFORMATION

**International Inventories**

<b>TSCA</b>	Complies
<b>DSL/NDL</b>	Complies
<b>EINECS/ELINCS</b>	Complies
<b>ENCS</b>	Does not comply
<b>IECSC</b>	Complies
<b>KECL</b>	Does not comply
<b>PICCS</b>	Does not comply
<b>AICS</b>	Does not comply

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

**United States of America****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372.

**SARA 311/312 Hazardous****Categorization**

<b>Acute Health Hazard</b>	Yes
<b>Chronic Health Hazard</b>	No
<b>Fire Hazard</b>	Yes
<b>Sudden Release of Pressure Hazard</b>	No
<b>Reactive Hazard</b>	No

**CERCLA**

**United States of America****California Prop. 65**

This product does not contain any Proposition 65 chemicals

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Component	New Jersey	Massachusetts	Pennsylvania
2-HEPTANONE	X	X	X

<b>16. OTHER INFORMATION</b>
------------------------------

<b><u>NFPA</u></b>	Health 2	Flammability 2	Instability 1	Physical hazard *
<b><u>HMIS (Hazardous Material Information System)</u></b>	Health 2	Flammability 2	Reactivity 1	

Prepared By Tnemec Regulatory Dept: 816-474-3400  
 Revision Date 10-Jul-2015


Revision Summary  
 9 4 5 7 10 8 11 14 6 15

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**



# Safety Data Sheet

Issue Date 16-Jul-2015

Revision Date 16-Jul-2015

Revision Number 9

## 1. IDENTIFICATION

### Product identifier

**Product Code** F041-0042  
**Product Name** THINNER CLEAR

### Other means of identification

**Common Name** NO. 42 THINNER  
**UN/ID no.** 1193

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO  
64120-1372

#### **Distributor**

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203  
Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Flammable Liquids	Category 2


### Label elements

#### EMERGENCY OVERVIEW

#### **Danger**

#### **Hazard statements**

Causes skin irritation  
Causes serious eye irritation  
May cause drowsiness or dizziness  
Highly flammable liquid and vapor



**Appearance** opaque
**Physical state** liquid
**Odor** aromatic

**Precautionary Statements**

**Prevention**

Wash face, hands and any exposed skin thoroughly after handling  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Use only outdoors or in a well-ventilated area  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Keep cool

**Response**

Get medical advice/attention if you feel unwell  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 If skin irritation occurs: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Call a POISON CENTER or doctor/physician if you feel unwell  
 In case of fire: Use CO2, dry chemical, or foam for extinction

**Storage**

Store in a well-ventilated place. Keep container tightly closed  
 Store locked up  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Other information

May be harmful if swallowed  
 SEE SAFETY DATA SHEET  
 Acute Toxicity 0 % of the mixture consists of ingredient(s) of unknown toxicity.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS-No	Weight-%
METHYL ETHYL KETONE	78-93-3	60 - 100%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

**4. FIRST AID MEASURES**

**Description of first aid measures**

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

**Most important symptoms and effects, both acute and delayed**

**Notes to physician** Treat symptomatically.

**5. FIRE-FIGHTING MEASURES****Suitable extinguishing media**

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

**Specific hazards arising from the chemical**

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

**Protective equipment and precautions for firefighters**

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Ensure adequate ventilation. Use personal protective equipment. Avoid contact with eyes, skin and clothing. Remove all sources of ignition.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Handle in accordance with good industrial hygiene and safety practice. Wear personal protective equipment. Avoid contact with eyes, skin and clothing. Remove and wash contaminated clothing before re-use. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not breathe vapours or spray mist. Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

### Conditions for safe storage, including any incompatibilities

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

**Incompatible products** Strong oxidizing agents. copper. Strong acids. Amines.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
METHYL ETHYL KETONE 78-93-3	TWA: 200 ppm STEL: 300 ppm	TWA: 200 ppm TWA: 590 mg/m <sup>3</sup> STEL: 300 ppm STEL: 885 mg/m <sup>3</sup>	3000 ppm

### Appropriate engineering controls

**Engineering measures** Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.

**Skin and body protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection** Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	liquid	<b>Odor</b>	aromatic
<b>Appearance</b>	opaque	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
<b>pH</b>		No data available
<b>Melting point / freezing point</b>		No data available
<b>Boiling point / boiling range</b>	78 °C / 172 °F	
<b>Flash point</b>	-5 °C / 23 °F	
<b>Evaporation rate</b>		Pensky Martens - Closed Cup
<b>Flammability (solid, gas)</b>		No data available
<b>Flammability Limit in Air</b>		Not applicable
<b>Upper flammability limit</b>	N/A	No data available
<b>Lower flammability limit</b>	1.0	
<b>Vapor pressure</b>		No data available
<b>Vapor density</b>		No data available
<b>Specific gravity</b>	0.80456	g/cm3
<b>Water solubility</b>	Insoluble in cold water	
<b>Solubility in other solvents</b>		No data available
<b>Partition coefficient: n-octanol/water</b>		No data available
<b>Autoignition temperature</b>		No data available
<b>Decomposition temperature</b>		No data available
<b>Kinematic viscosity</b>		No data available
<b>Dynamic viscosity</b>		No data available

**Other Information**

<b>Density</b>	6.71001 lbs/gal
<b>Volatile organic compounds (VOC) content</b>	6.71001 lbs/gal
<b>Total volatiles weight percent</b>	100 %
<b>Total volatiles volume percent</b>	100 %

## 10. STABILITY AND REACTIVITY

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Strong oxidizing agents, copper, Strong acids, Amines

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

## 11. TOXICOLOGICAL INFORMATION

**Information on Likely Routes of Exposure**

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye contact</b>	Causes serious eye irritation.

<b>Skin contact</b>	Irritating to skin.
<b>Ingestion</b>	Harmful if swallowed. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
METHYL ETHYL KETONE 78-93-3	= 2737 mg/kg ( Rat ) = 2483 mg/kg ( Rat )	= 5000 mg/kg ( Rabbit ) = 6480 mg/kg ( Rabbit )	= 11700 ppm ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritating to eyes and skin.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

<b>Chronic Toxicity</b>	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
<b>Sensitization</b>	No information available.
<b>Mutagenicity</b>	No information available.
<b>Carcinogenicity</b>	There are no known carcinogenic chemicals in this product.
<b>Reproductive effects</b>	No information available.
<b>STOT - single exposure</b>	Skin, Eyes, Central Nervous System (CNS)
<b>STOT - repeated exposure</b>	No information available
<b>Aspiration hazard</b>	No information available.
<b>Acute Toxicity</b>	0 % of the mixture consists of ingredient(s) of unknown toxicity.

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

0 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
METHYL ETHYL KETONE 78-93-3		3130 - 3320: 96 h Pimephales promelas mg/L LC50 flow-through	5091: 48 h Daphnia magna mg/L EC50 520: 48 h Daphnia magna mg/L EC50 4025 - 6440: 48 h Daphnia magna mg/L EC50 Static

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

Component	log Pow
METHYL ETHYL KETONE 78-93-3	0.29

**Other Adverse Effects**

No information available

**13. DISPOSAL CONSIDERATIONS****Waste treatment methods****Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.



**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Component	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
METHYL ETHYL KETONE 78-93-3	U159	Included in waste streams: F005, F039	200.0 mg/L regulatory level	U159

Component	CAWAST
METHYL ETHYL KETONE 78-93-3	Toxic Ignitable

## 14. TRANSPORT INFORMATION

### DOT

**UN/ID no.** 1193  
**Proper Shipping Name** Methyl ethyl ketone  
**Hazard Class** 3  
**Packing Group** II  
**Emergency Response Guide Number** 127

### IATA

**UN/ID no.** 1193  
**Proper Shipping Name** Methyl ethyl ketone  
**Hazard Class** 3  
**Packing Group** II  
**ERG Code** 364

### Additional information

Call TNEMEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

## 15. REGULATORY INFORMATION

### International Inventories

**TSCA** Complies  
**DSL/NDSL** Complies  
**EINECS/ELINCS** Complies  
**ENCS** Complies  
**IECSC** Complies  
**KECL** Complies  
**PICCS** Complies  
**AICS** Complies

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

### United States of America

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372:

Component	SARA 313 - Threshold Values
METHYL ETHYL KETONE - 78-93-3	1.0

**SARA 311/312 Hazardous Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**CERCLA**

Component	Hazardous Substances RQs	CERCLA EHS RQs	RQ
METHYL ETHYL KETONE 78-93-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

**United States of America**

**California Prop. 65**

This product does not contain any Proposition 65 chemicals

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Component	New Jersey	Massachusetts	Pennsylvania
METHYL ETHYL KETONE 78-93-3	X	X	X

**16. OTHER INFORMATION**

<b>NFPA</b>	Health 2	Flammability 3	Instability 1	Physical hazard -
<b>HMIS (Hazardous Material Information System)</b>	Health 2	Flammability 3	Reactivity 1	

Prepared By Tnemec Regulatory Dept: 816-474-3400

Revision Date 16-Jul-2015


Revision Summary  
9 4 5 7 10 8 11 14 6 15

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**



# Safety Data Sheet

Issue Date 12-Nov-2018

Revision Date 12-Nov-2018

Revision Number 5

## 1. IDENTIFICATION

### Product identifier

**Product Code** F041-0046  
**Product Name** THINNER CLEAR

### Other means of identification

**Common Name** NO. 46 THINNER  
**UN/ID no.** 1263  
**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

**Manufacturer Address** Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372 816-474-3400  
**Distributor** Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2A
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Flammable Liquids	Category 3

### Label elements

## EMERGENCY OVERVIEW

### **Danger**

### **Hazard statements**

Causes serious eye irritation  
May cause genetic defects  
May cause cancer  
May cause respiratory irritation. May cause drowsiness or dizziness  
Flammable liquid and vapor

**Appearance** clear**Physical state** liquid**Odor** Slight**Precautionary Statements****Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Wash face, hands and any exposed skin thoroughly after handling  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Use only outdoors or in a well-ventilated area  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Keep cool

**Response**

IF exposed or concerned: Get medical advice/attention  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store locked up  
 Store in a well-ventilated place. Keep container tightly closed

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

May be harmful in contact with skin  
 Toxic to aquatic life with long lasting effects  
 Acute Toxicity 0 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
P-CHLOROBENZOTRIFLUORIDE	98-56-6	60 - 100%
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE	124-17-4	1 - <10%
ACETONE	67-64-1	1 - <10%
PETROLEUM SOLVENT (NAPTHA)	64742-95-6	0.1 - <1%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

**Description of first aid measures**

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

**Most important symptoms and effects, both acute and delayed**

**Notes to physician** Treat symptomatically.

**5. FIRE-FIGHTING MEASURES****Suitable extinguishing media**

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

**Specific hazards arising from the chemical**

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Chlorine. Fluorine. Carbon oxides. Sulfur oxides. Phosphorus oxides.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Use personal protective equipment. Avoid contact with eyes, skin and clothing. Ensure adequate ventilation. Remove all sources of ignition.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** Pick up and transfer to properly labelled containers.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Handle in accordance with good industrial hygiene and safety practice. Wear personal protective equipment. Remove and wash contaminated clothing before re-use. Avoid contact with eyes, skin and clothing. Do not breathe vapours or spray mist. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

### Conditions for safe storage, including any incompatibilities

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

**Incompatible products** Incompatible with oxidizing agents. Strong acids. Aldehyde. Alkalis. Amines. Ammonia. Reducing agents. Chlorine.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
P-CHLOROBENZOTRIFLUORIDE 98-56-6	TWA: 2.5 mg/m <sup>3</sup>	-	250 mg/m <sup>3</sup>
ACETONE 67-64-1	TWA: 250 ppm STEL: 500 ppm	TWA: 750 ppm TWA: 1800 mg/m <sup>3</sup> STEL: 2400 mg/m <sup>3</sup> STEL: 1000 ppm TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup>	2500 ppm

### Appropriate engineering controls

**Engineering measures** Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Safety glasses with side-shields If splashes are likely to occur, wear face-shield.

**Skin and body protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection** Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

**Physical state** liquid

<b>Appearance</b>	clear	<b>Odor</b>	Slight
<b>Color</b>	clear	<b>Odor threshold</b>	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
pH		
Melting point / freezing point	No data available	
Boiling point / boiling range		
Flash point	27 °C / 80.00 °F	Pensky Martens - Closed Cup
Evaporation rate		
Flammability (solid, gas)	No data available	
Flammability Limit in Air		
Upper flammability limit	NA	
Lower flammability limit	NA	
Vapor pressure		
Vapor density		
Specific gravity	1.31157	g/cm3
Water solubility	Insoluble in cold water	
Solubility in other solvents		
Partition coefficient: n-octanol/water		
Autoignition temperature	No data available	
Decomposition temperature		
Kinematic viscosity		
Dynamic viscosity		

**Other Information**

Density	10.93847 lbs/gal
Volatile organic compounds (VOC) content	7.4852 lbs/gal
Total volatiles weight percent	99.6 %
Total volatiles volume percent	99.58 %
Bulk density	No information available

## 10. STABILITY AND REACTIVITY

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Incompatible with oxidizing agents, Strong acids, Aldehyde, Alkalis, Amines, Ammonia, Reducing agents, Chlorine

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Chlorine. Fluorine. Carbon oxides. Sulfur oxides. Phosphorous Oxides.

## 11. TOXICOLOGICAL INFORMATION

**Information on Likely Routes of Exposure****Inhalation**

May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.

<b>Eye contact</b>	Causes serious eye irritation.
<b>Skin contact</b>	Irritating to skin.
<b>Ingestion</b>	Harmful if swallowed.

Chemical name	LD50 Oral	LD50 Dermal	LC50 Inhalation
P-CHLOROBENZOTRIFLUORIDE 98-56-6	= 13 g/kg ( Rat )	> 2 mL/kg ( Rabbit )	= 33 mg/L ( Rat ) 4 h
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE 124-17-4	= 6500 mg/kg ( Rat )	= 14500 mg/kg ( Rabbit )	= 72500 mg/m <sup>3</sup> ( Rat ) 4 h
ACETONE 67-64-1	= 5800 mg/kg ( Rat )	> 15700 mg/kg ( Rabbit )	= 50100 mg/m <sup>3</sup> ( Rat ) 8 h
PETROLEUM SOLVENT (NAPTHA) 64742-95-6	= 8400 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	= 3400 ppm ( Rat ) 4 h

### Information on toxicological effects

**Symptoms** Symptoms of overexposure are dizziness, headache, tiredness, nausea, unconsciousness, cessation of breathing. Irritating to eyes and skin.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Chronic Toxicity** NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid repeated exposure. Substances known to be mutagenic to man. Substances known to be carcinogenic to man.

**Sensitization**

No information available.

**Mutagenicity**

Substances known to be mutagenic to man.

**Carcinogenicity**

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
PETROLEUM SOLVENT (NAPTHA) 64742-95-6	*	-	-	

**Reproductive effects**

No information available.

**STOT - single exposure**

Respiratory system, Central Nervous System (CNS)

**STOT - repeated exposure**

No information available

**Target organ effects**

Central nervous system, Eyes, respiratory system, Skin, kidney, liver.

**Aspiration hazard**

No information available.

**Acute Toxicity**

0 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Toxic to aquatic life with long lasting effects

0.39497 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
P-CHLOROBENZOTRIFLUORIDE 98-56-6		11.5 - 15.8: 48 h Lepomis macrochirus mg/L LC50 static	3.68: 48 h Daphnia magna mg/L EC50
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE 124-17-4		50 - 70: 96 h Brachydanio rerio mg/L LC50 static 77: 96 h Pimephales promelas mg/L LC50 static	665: 48 h Daphnia magna mg/L LC50
ACETONE 67-64-1		4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L LC50 6210 - 8120: 96 h Pimephales promelas mg/L LC50 static 8300: 96 h Lepomis	10294 - 17704: 48 h Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h Daphnia magna mg/L EC50



		macrochirus mg/L LC50	
PETROLEUM SOLVENT (NAPTHA) 64742-95-6		9.22: 96 h Oncorhynchus mykiss mg/L LC50	6.14: 48 h Daphnia magna mg/L EC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

Chemical name	log Pow
P-CHLOROBENZOTRIFLUORIDE 98-56-6	3.7
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE 124-17-4	1.77
ACETONE 67-64-1	-0.24

**Other Adverse Effects**

No information available

**13. DISPOSAL CONSIDERATIONS****Waste treatment methods****Disposal Methods**

It must undergo special treatment, e.g. at suitable disposal site, to comply with local regulations.

**Contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

**US EPA Waste Number**

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
ACETONE 67-64-1		Included in waste stream: F039		U002

**California Hazardous Waste Status**

Chemical name	CAWAST
ACETONE 67-64-1	Ignitable

**14. TRANSPORT INFORMATION****DOT**

UN/ID no.	1263
Proper Shipping Name	Paint related material
Hazard Class	3
Packing Group	III
Emergency Response Guide Number	128

**Additional information**

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

**15. REGULATORY INFORMATION**

**International Inventories**

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Does Not Comply
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List  
 EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances  
 ENCS - Japan Existing and New Chemical Substances  
 IECSC - China Inventory of Existing Chemical Substances  
 KECL - Korean Existing and Evaluated Chemical Substances  
 PICCS - Philippines Inventory of Chemicals and Chemical Substances  
 AICS - Australian Inventory of Chemical Substances

**The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):**

<b>Chemical name</b>	<b>HAPS Data</b>
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE	

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

Chemical name	SARA 313 - Threshold Values
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE - 124-17-4	1.0

**SARA 311/312 Hazardous**

**Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**CERCLA**

Chemical name	Hazardous Substances RQs	CERCLA EHS RQs	RQ
ACETONE 67-64-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

**California Prop. 65**

**WARNING:** This product can expose you to the following chemicals which are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Chemical name	California Prop. 65
PETROLEUM SOLVENT (NAPTHA) - 64742-95-6	Developmental

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Chemical name	New Jersey	Massachusetts	Pennsylvania
P-CHLOROBENZOTRIFLUORIDE 98-56-6	X		
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE 124-17-4	X		X

ACETONE 67-64-1	X	X	X
--------------------	---	---	---

**16. OTHER INFORMATION**

<b>NFPA</b>	Health 2	Flammability 3	Instability 0	Physical hazard *
<b>HMIS (Hazardous Material Information System)</b>	Health 2*	Flammability 3	Reactivity 0	


**Prepared By** Tnemec Regulatory Dept: 816-474-3400  
**Revision Date** 12-Nov-2018  
**Revision Summary**  
 1 9 5 10 7 6 8 11 13 14 15

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of SDS**



# Safety Data Sheet

Issue Date 16-Jul-2015

Revision Date 16-Jul-2015

Revision Number 7

## 1. IDENTIFICATION

### Product identifier

**Product Code** F041-0048  
**Product Name** THINNER CLEAR

### Other means of identification

**Common Name** NO. 48 THINNER

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO  
64120-1372

#### **Distributor**

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203  
Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Inhalation (Vapors)	Category 5
Serious eye damage/eye irritation	Category 2B
Specific target organ toxicity (single exposure)	Category 3
Flammable Liquids	Category 3

### Label elements

## EMERGENCY OVERVIEW

### **WARNING**

#### **Hazard statements**

May be harmful if inhaled  
Causes eye irritation  
May cause respiratory irritation. May cause drowsiness or dizziness  
Flammable liquid and vapor



**Appearance** opaque

**Physical state** liquid

**Odor** aromatic

**Precautionary Statements**

**Prevention**

- Wash face, hands and any exposed skin thoroughly after handling
- Avoid breathing dust/fume/gas/mist/vapors/spray
- Use only outdoors or in a well-ventilated area
- Keep away from heat/sparks/open flames/hot surfaces. — No smoking
- Keep container tightly closed
- Ground/bond container and receiving equipment
- Use explosion-proof electrical/ventilating/lighting/mixing/equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge
- Wear protective gloves/protective clothing/eye protection/face protection
- Keep cool

**Response**

- Get medical advice/attention if you feel unwell
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- If eye irritation persists: Get medical advice/attention
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- Call a POISON CENTER or doctor/physician if you feel unwell
- In case of fire: Use CO2, dry chemical, or foam for extinction

**Storage**

- Store in a well-ventilated place. Keep container tightly closed
- Store locked up
- Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

**Other information**

- May be harmful if swallowed
- Toxic to aquatic life with long lasting effects
- SEE SAFETY DATA SHEET
- Acute Toxicity 0 % of the mixture consists of ingredient(s) of unknown toxicity.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS-No	Weight-%
HEXYL ACETATE	142-92-7	60 - 100%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

**4. FIRST AID MEASURES**

**Description of first aid measures**

---

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

**Most important symptoms and effects, both acute and delayed**

**Notes to physician** Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

**Suitable extinguishing media**

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

**Specific hazards arising from the chemical**

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

**Protective equipment and precautions for firefighters**

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Close container after each use. Avoid contact with eyes, skin and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

### Conditions for safe storage, including any incompatibilities

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

**Incompatible products** Strong oxidizing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure guidelines

#### Appropriate engineering controls

**Engineering measures** Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Use chemical resistant splash type goggles.

**Skin and body protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection** Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	liquid	<b>Odor</b>	aromatic
<b>Appearance</b>	opaque	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		
<b>Property</b>	<b>Values</b>	<b>Remarks</b>	
<b>pH</b>		No data available	
<b>Melting point / freezing point</b>		No data available	
<b>Boiling point / boiling range</b>	116 °C / 241.0 °F		
<b>Flash point</b>	57 °C / 134 °F		Pensky Martens - Closed Cup
<b>Evaporation rate</b>			No data available

<b>Flammability (solid, gas)</b>		Not applicable
<b>Flammability Limit in Air</b>		No data available
<b>Upper flammability limit</b>	N/A	
<b>Lower flammability limit</b>	1.0	
<b>Vapor pressure</b>		No data available
<b>Vapor density</b>		No data available
<b>Specific gravity</b>	0.8717	g/cm <sup>3</sup>
<b>Water solubility</b>	Insoluble in cold water	
<b>Solubility in other solvents</b>		No data available
<b>Partition coefficient: n-octanol/water</b>		No data available
<b>Autoignition temperature</b>		No data available
<b>Decomposition temperature</b>		No data available
<b>Kinematic viscosity</b>		No data available
<b>Dynamic viscosity</b>		No data available

**Other Information**

<b>Density</b>	7.26998 lbs/gal
<b>Volatile organic compounds (VOC) content</b>	7.26998 lbs/gal
<b>Total volatiles weight percent</b>	100 %
<b>Total volatiles volume percent</b>	100 %

## 10. STABILITY AND REACTIVITY

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Strong oxidizing agents

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

## 11. TOXICOLOGICAL INFORMATION

**Information on Likely Routes of Exposure**

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Skin contact</b>	CAUSES SKIN IRRITATION.
<b>Ingestion</b>	Harmful if swallowed.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
HEXYL ACETATE 142-92-7	= 41500 µL/kg ( Rat )	> 5 g/kg ( Rabbit )	

**Information on toxicological effects**



**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritating to eyes and skin.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Chronic Toxicity** NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**Sensitization** No information available.

**Mutagenicity** No information available.

**Carcinogenicity** There are no known carcinogenic chemicals in this product.

**Reproductive effects** No information available.

**STOT - single exposure** Skin, Eyes, Central Nervous System (CNS)

**STOT - repeated exposure** No information available

**Aspiration hazard** Risk of serious damage to the lungs (by aspiration).

**Acute Toxicity** 0 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

Toxic to aquatic life with long lasting effects

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
HEXYL ACETATE 142-92-7		3.7 - 4.4: 96 h Pimephales promelas mg/L LC50 flow-through	

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

**Other Adverse Effects** No information available

## 13. DISPOSAL CONSIDERATIONS

**Waste treatment methods**

**Disposal Methods** Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. TRANSPORT INFORMATION

**DOT**

**Proper Shipping Name** Paint related material

**IATA**

UNID no.	1993
Proper Shipping Name	FLAMMABLE LIQUID N.O.S. (HEXYL ACETATE)
Hazard Class	3
Packing Group	III
ERG Code	366

**Additional information** Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

## 15. REGULATORY INFORMATION

### International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

### United States of America

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372.

#### **SARA 311/312 Hazardous**

##### Categorization

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

### CERCLA

### United States of America

#### **California Prop. 65**

This product does not contain any Proposition 65 chemicals

#### **California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

### State Right-to-Know

**16. OTHER INFORMATION**

<b>NFPA</b>	Health 2	Flammability 2	Instability 0	Physical hazard -
<b>HMIS (Hazardous Material Information System)</b>	Health 2	Flammability 2	Reactivity 0	


**Prepared By** Tnemec Regulatory Dept: 816-474-3400  
**Revision Date** 16-Jul-2015  
**Revision Summary**  
9 4 5 7 10 8 11 14 15

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**



# Safety Data Sheet

Issue Date 28-Jul-2015

Revision Date 28-Jul-2015

Revision Number 8

## 1. IDENTIFICATION

### Product identifier

**Product Code** F041-0049  
**Product Name** THINNER CLEAR

### Other means of identification

**Common Name** NO. 49 THINNER

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372

#### **Distributor**

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203 Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2B
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Flammable Liquids	Category 3


### Label elements

## EMERGENCY OVERVIEW

### **WARNING**

#### **Hazard statements**

Causes skin irritation  
Causes eye irritation  
May cause respiratory irritation. May cause drowsiness or dizziness  
May cause damage to organs through prolonged or repeated exposure  
Flammable liquid and vapor



**Appearance** opaque
**Physical state** liquid
**Odor** aromatic

**Precautionary Statements**

**Prevention**

- Wash face, hands and any exposed skin thoroughly after handling
- Wear protective gloves/protective clothing/eye protection/face protection
- Use only outdoors or in a well-ventilated area
- Do not breathe dust/fume/gas/mist/vapors/spray
- Keep away from heat/sparks/open flames/hot surfaces. — No smoking
- Keep container tightly closed
- Ground/bond container and receiving equipment
- Use explosion-proof electrical/ventilating/lighting/mixing/equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge
- Keep cool

**Response**

- Get medical advice/attention if you feel unwell
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- If eye irritation persists: Get medical advice/attention
- If skin irritation occurs: Get medical advice/attention
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- Wash contaminated clothing before reuse
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- Call a POISON CENTER or doctor/physician if you feel unwell
- In case of fire: Use CO2, dry chemical, or foam for extinction

**Storage**

- Store in a well-ventilated place. Keep container tightly closed
- Store locked up

**Disposal**

- Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

**Other information**

Acute Toxicity 100 % of the mixture consists of ingredient(s) of unknown toxicity.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS-No	Weight-%
P-CHLOROBENZOTRIFLUORIDE	98-56-6	60 - 100%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

**4. FIRST AID MEASURES**

**Description of first aid measures**

**General advice** If symptoms persist, call a physician.

<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

**Most important symptoms and effects, both acute and delayed**

**Notes to physician** Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

**Suitable extinguishing media**

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

**Specific hazards arising from the chemical**

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Chlorine. Fluorine.

**Protective equipment and precautions for firefighters**

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Avoid contact with eyes, skin and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

### Conditions for safe storage, including any incompatibilities

**Storage** Keep out of the reach of children. Keep container tightly closed in a dry and well-ventilated place.

**Incompatible products** Strong oxidizing agents. Strong acids.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
P-CHLOROBENZOTRIFLUORIDE 98-56-6	TWA: 2.5 mg/m <sup>3</sup>	-	

### Appropriate engineering controls

**Engineering measures** Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Use chemical resistant splash type goggles.

**Skin and body protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection** Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	liquid	<b>Odor</b>	aromatic
<b>Appearance</b>	opaque	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		
<b>Property</b>	<b>Values</b>	<b>Remarks</b>	
<b>pH</b>		No data available	
<b>Melting point / freezing point</b>		No data available	
<b>Boiling point / boiling range</b>	139 °C / 282 °F		
<b>Flash point</b>	40 °C / 104 °F		Pensky Martens - Closed Cup

Evaporation rate		No data available
Flammability (solid, gas)		Not applicable
Flammability Limit in Air		No data available
Upper flammability limit	N/A	
Lower flammability limit	1.0	
Vapor pressure		No data available
Vapor density		No data available
Specific gravity	1.34292	g/cm <sup>3</sup>
Water solubility	Insoluble in cold water	
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition temperature		No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity		No data available

**Other Information**

Density	11.19996 lbs/gal
Volatile organic compounds (VOC) content	.000 lbs/gal
Total volatiles weight percent	100 %
Total volatiles volume percent	100 %

## 10. STABILITY AND REACTIVITY

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Strong oxidizing agents, Strong acids

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Chlorine. Fluorine.

## 11. TOXICOLOGICAL INFORMATION

**Information on Likely Routes of Exposure**

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Skin contact</b>	Irritating to skin.
<b>Ingestion</b>	Harmful if swallowed.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
P-CHLOROBENZOTRIFLUORIDE 98-56-6	= 13 g/kg ( Rat )	> 2 mL/kg ( Rabbit )	= 33 mg/L ( Rat ) 4 h



**Information on toxicological effects**

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritating to eyes and skin.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Chronic Toxicity** NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**Sensitization** No information available.

**Mutagenicity** No information available.

**Carcinogenicity** There are no known carcinogenic chemicals in this product.

**Reproductive effects** No information available.

**STOT - single exposure** Skin, Eyes, Central Nervous System (CNS)

**STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure

**Target organ effects** Eyes, Skin, Central nervous system, liver, kidney.

**Aspiration hazard** No information available.

**Acute Toxicity** 100 % of the mixture consists of ingredient(s) of unknown toxicity.

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

Toxic to aquatic life with long lasting effects

100 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
P-CHLOROBENZOTRIFLUORIDE 98-56-6		11.5 - 15.8: 48 h Lepomis macrochirus mg/L LC50 static	3.68: 48 h Daphnia magna mg/L EC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

Component	log Pow
P-CHLOROBENZOTRIFLUORIDE 98-56-6	3.7

**Other Adverse Effects**

No information available

**13. DISPOSAL CONSIDERATIONS****Waste treatment methods**

**Disposal Methods** Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

**14. TRANSPORT INFORMATION**

**DOT**

**Proper Shipping Name** Paint related material

**IATA**

**UN/ID no.** 1263  
**Proper Shipping Name** Paint related material  
**Hazard Class** 3  
**Packing Group** III  
**ERG Code** 366

**Additional information**

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

<b>15. REGULATORY INFORMATION</b>
-----------------------------------

**International Inventories**

<b>TSCA</b>	Complies
<b>DSL/NDSL</b>	Complies
<b>EINECS/ELINCS</b>	Complies
<b>ENCS</b>	Complies
<b>IECSC</b>	Complies
<b>KECL</b>	Complies
<b>PICCS</b>	Complies
<b>AICS</b>	Complies

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

**United States of America****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372.

**SARA 311/312 Hazardous****Categorization**

<b>Acute Health Hazard</b>	Yes
<b>Chronic Health Hazard</b>	No
<b>Fire Hazard</b>	Yes
<b>Sudden Release of Pressure Hazard</b>	No
<b>Reactive Hazard</b>	No

**CERCLA****United States of America****California Prop. 65**

This product does not contain any Proposition 65 chemicals

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Component	New Jersey	Massachusetts	Pennsylvania
P-CHLOROBENZOTRIFLUORIDE 98-56-6	X		X

**16. OTHER INFORMATION**

<b>NFPA</b>	Health 1	Flammability 2	Instability 0	Physical hazard -
<b>HMIS (Hazardous Material Information System)</b>	Health 1	Flammability 2	Reactivity 0	


**Prepared By** Tnemec Regulatory Dept: 816-474-3400  
**Revision Date** 28-Jul-2015  
**Revision Summary**  
 9 4 5 7 10 8 11 14 15

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**



# Safety Data Sheet

Issue Date 16-Jul-2015

Revision Date 16-Jul-2015

Revision Number 7

## 1. IDENTIFICATION

### Product identifier

**Product Code** F041-0050  
**Product Name** THINNER CLEAR

### Other means of identification

**Common Name** NO. 50 THINNER  
**UN/ID no.** 1263

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO  
64120-1372

#### **Distributor**

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203  
Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Serious eye damage/eye irritation	Category 2B
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Flammable Liquids	Category 2

### Label elements

## EMERGENCY OVERVIEW

### **Danger**

#### **Hazard statements**

Harmful if swallowed  
Causes eye irritation  
May cause respiratory irritation. May cause drowsiness or dizziness  
May cause damage to organs through prolonged or repeated exposure  
Highly flammable liquid and vapor

**Appearance** opaque**Physical state** liquid**Odor** aromatic**Precautionary Statements****Prevention**

Wash face, hands and any exposed skin thoroughly after handling  
 Do not eat, drink or smoke when using this product  
 Use only outdoors or in a well-ventilated area  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Keep cool

**Response**

Get medical advice/attention if you feel unwell  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Call a POISON CENTER or doctor/physician if you feel unwell  
 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell  
 Rinse mouth  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store in a well-ventilated place. Keep container tightly closed  
 Store locked up  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

Causes mild skin irritation  
 SEE SAFETY DATA SHEET  
 Acute Toxicity

0 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight-%
METHYL N-PROPYL KETONE	107-87-9	60 - 100%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

**Description of first aid measures**

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

**Most important symptoms and effects, both acute and delayed**

**Notes to physician** Treat symptomatically.

**5. FIRE-FIGHTING MEASURES****Suitable extinguishing media**

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

**Specific hazards arising from the chemical**

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Formaldehyde.

**Protective equipment and precautions for firefighters**

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

### Conditions for safe storage, including any incompatibilities

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

**Incompatible products** Strong acids. Strong oxidizing agents. Bases. Peroxides. copper. Reducing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
METHYL N-PROPYL KETONE 107-87-9	STEL: 150 ppm	TWA: 200 ppm TWA: 700 mg/m <sup>3</sup> STEL: 250 ppm STEL: 875 mg/m <sup>3</sup>	1500 ppm

### Appropriate engineering controls

**Engineering measures** Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Use chemical resistant splash type goggles.

**Skin and body protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection** Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

**Physical state** liquid

<b>Appearance</b>	opaque	<b>Odor</b>	aromatic
<b>Color</b>	No information available	<b>Odor threshold</b>	No information available
<b>Property</b>	<b>Values</b>	<b>Remarks</b>	
pH		No data available	
Melting point / freezing point		No data available	
Boiling point / boiling range	102 °C / 245 °F		
Flash point	8 °C / 46 °F		
Evaporation rate		Pensky Martens - Closed Cup	
Flammability (solid, gas)		No data available	
Flammability Limit in Air		Not applicable	
Upper flammability limit	N/A	No data available	
Lower flammability limit	1.0		
Vapor pressure		No data available	
Vapor density		No data available	
Specific gravity	0.8057	g/cm3	
Water solubility	Insoluble in cold water		
Solubility in other solvents		No data available	
Partition coefficient: n-octanol/water		No data available	
Autoignition temperature		No data available	
Decomposition temperature		No data available	
Kinematic viscosity		No data available	
Dynamic viscosity		No data available	

**Other Information**

Density	6.71953 lbs/gal
Volatile organic compounds (VOC) content	6.71953 lbs/gal
Total volatiles weight percent	100 %
Total volatiles volume percent	100 %

**10. STABILITY AND REACTIVITY****Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks. Exposure to air or moisture over prolonged periods.

**Incompatible materials**

Strong acids, Strong oxidizing agents, Bases, Peroxides, copper, Reducing agents

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Formaldehyde.

**11. TOXICOLOGICAL INFORMATION****Information on Likely Routes of Exposure**

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye contact</b>	Causes serious eye irritation.



**Skin contact** Irritating to skin.

**Ingestion** Harmful if swallowed.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
METHYL N-PROPYL KETONE 107-87-9	= 1600 mg/kg ( Rat )	= 6480 mg/kg ( Rat ) = 6500 mg/kg ( Rabbit )	= 2000 ppm ( Rat ) 4 h

### Information on toxicological effects

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritating to eyes and skin.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Chronic Toxicity** NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**Sensitization** No information available.

**Mutagenicity** No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

**Reproductive effects** No information available.

**STOT - single exposure** Skin, Eyes, Central Nervous System (CNS)

**STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure

**Target organ effects** Central nervous system, Eyes, respiratory system, Skin.

**Aspiration hazard** No information available.

**Acute Toxicity** 0 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

0 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
METHYL N-PROPYL KETONE 107-87-9		1190 - 1290: 96 h Pimephales promelas mg/L LC50 flow-through	

### Persistence and degradability

No information available.

### Bioaccumulation

No information available.

### Mobility in Environmental Media

Component	log Pow
METHYL N-PROPYL KETONE 107-87-9	0.91

### Other Adverse Effects

No information available

## 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

#### **Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

#### **Contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

Component	CAWAST
METHYL N-PROPYL KETONE 107-87-9	Toxic Ignitable

#### 14. TRANSPORT INFORMATION

##### DOT

UN/ID no.	1263
Proper Shipping Name	Paint related material
Hazard Class	3
Packing Group	II
Emergency Response Guide Number	128

##### IATA

UN/ID no.	1263
Proper Shipping Name	Paint related material
Hazard Class	3
Packing Group	II
ERG Code	364

##### Additional information

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

#### 15. REGULATORY INFORMATION

##### International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

##### United States of America

##### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372.

##### SARA 311/312 Hazardous

##### Categorization

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes

Sudden Release of Pressure Hazard No  
 Reactive Hazard No

CERCLA

United States of America

California Prop. 65

This product does not contain any Proposition 65 chemicals

California SCAQMD Rule 443

Contains Photochemically Reactive Solvent

State Right-to-Know

Component	New Jersey	Massachusetts	Pennsylvania
METHYL N-PROPYL KETONE 107-87-9	X	X	X

**16. OTHER INFORMATION**

NFPA Health 2 Flammability 3 Instability 0 Physical hazard -  
HMIS (Hazardous Health 2 Flammability 3 Reactivity 0  
Material Information  
System)

Prepared By Tnemec Regulatory Dept: 816-474-3400  
 Revision Date 16-Jul-2015


Revision Summary  
 9 4 5 7 10 8 11 14 15

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**



# Safety Data Sheet

Issue Date 24-Aug-2015

Revision Date 24-Aug-2015

Revision Number 8

## 1. IDENTIFICATION

### Product identifier

**Product Code** F041-0051  
**Product Name** THINNER ELECTROSTATIC THINNER

### Other means of identification

**Common Name** NO. 51 THINNER  
**UN/ID no.** 1993

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO  
64120-1372

#### **Distributor**

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203  
Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Specific target organ toxicity (single exposure)	Category 3
Flammable Liquids	Category 2


### Label elements

## EMERGENCY OVERVIEW

#### **Danger**

#### **Hazard statements**

Causes skin irritation  
Causes serious eye damage  
May cause drowsiness or dizziness  
Highly flammable liquid and vapor



**Appearance** opaque
**Physical state** liquid
**Odor** aromatic

**Precautionary Statements**

**Prevention**

- Wash face, hands and any exposed skin thoroughly after handling
- Wear protective gloves/protective clothing/eye protection/face protection
- Avoid breathing dust/fume/gas/mist/vapors/spray
- Use only outdoors or in a well-ventilated area
- Keep away from heat/sparks/open flames/hot surfaces. — No smoking
- Keep container tightly closed
- Ground/bond container and receiving equipment
- Use explosion-proof electrical/ventilating/lighting/mixing/equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge
- Keep cool

**Response**

- Get medical advice/attention if you feel unwell
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- Immediately call a POISON CENTER or doctor/physician
- If skin irritation occurs: Get medical advice/attention
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- Wash contaminated clothing before reuse
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- Call a POISON CENTER or doctor/physician if you feel unwell
- In case of fire: Use CO2, dry chemical, or foam for extinction

**Storage**

- Store in a well-ventilated place. Keep container tightly closed
- Store locked up
- Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Other information

May be harmful if swallowed  
 SEE SAFETY DATA SHEET  
 Acute Toxicity

14.45792 % of the mixture consists of ingredient(s) of unknown toxicity.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS-No	Weight-%
METHYL ETHYL KETONE	78-93-3	60 - 100%
ISOBUTYL ALCOHOL	78-83-1	1 - 10%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

**4. FIRST AID MEASURES**

**Description of first aid measures**

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Call a physician immediately.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

**Most important symptoms and effects, both acute and delayed**

**Notes to physician** Treat symptomatically.

**5. FIRE-FIGHTING MEASURES****Suitable extinguishing media**

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

**Specific hazards arising from the chemical**

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Oxides of nitrogen.

**Protective equipment and precautions for firefighters**

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

### Conditions for safe storage, including any incompatibilities

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

**Incompatible products** Strong oxidizing agents. copper. Strong bases. Amines. Alkaline.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
METHYL ETHYL KETONE 78-93-3	TWA: 200 ppm STEL: 300 ppm	TWA: 200 ppm TWA: 590 mg/m <sup>3</sup> STEL: 300 ppm STEL: 885 mg/m <sup>3</sup>	3000 ppm
ISOBUTYL ALCOHOL 78-83-1	TWA: 50 ppm	TWA: 50 ppm TWA: 150 mg/m <sup>3</sup> TWA: 100 ppm TWA: 300 mg/m <sup>3</sup>	1600 ppm

### Appropriate engineering controls

**Engineering measures** Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Use chemical resistant splash type goggles.

**Skin and body protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection** Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	aromatic
<b>Appearance</b>	opaque	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
pH		No data available
Melting point / freezing point		No data available
Boiling point / boiling range	78 °C / 172 °F	
Flash point	-7 °C / 20 °F	Pensky Martens - Closed Cup
Evaporation rate		No data available
Flammability (solid, gas)		Not applicable
Flammability Limit in Air		No data available
Upper flammability limit	N/A	
Lower flammability limit	1.0	
Vapor pressure		No data available
Vapor density		No data available
Specific gravity	0.83493	g/cm3
Water solubility	Insoluble in cold water	
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition temperature		No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity		No data available

**Other Information**

<b>Density</b>	6.96328 lbs/gal
<b>Volatile organic compounds (VOC) content</b>	5.95639 lbs/gal
<b>Total volatiles weight percent</b>	85.54 %
<b>Total volatiles volume percent</b>	88.78 %

**10. STABILITY AND REACTIVITY****Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Strong oxidizing agents, copper, Strong bases, Amines, Alkaline

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Oxides of nitrogen.

**11. TOXICOLOGICAL INFORMATION****Information on Likely Routes of Exposure**

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
-------------------	---



<b>Eye contact</b>	Causes serious eye damage.
<b>Skin contact</b>	Irritating to skin.
<b>Ingestion</b>	Harmful if swallowed.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
METHYL ETHYL KETONE 78-93-3	= 2483 mg/kg ( Rat ) = 2737 mg/kg ( Rat )	= 6480 mg/kg ( Rabbit ) = 5000 mg/kg ( Rabbit )	= 11700 ppm ( Rat ) 4 h
ISOBUTYL ALCOHOL 78-83-1	= 2460 mg/kg ( Rat )	= 3400 mg/kg ( Rabbit )	> 6.5 mg/L ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Eye Damage.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Chronic Toxicity** NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**Sensitization** No information available.

**Mutagenicity** No information available.

**Carcinogenicity** There are no known carcinogenic chemicals in this product.

**Reproductive effects** No information available.

**STOT - single exposure** Skin, Eyes, Central Nervous System (CNS)

**STOT - repeated exposure** No information available

**Aspiration hazard** No information available.

**Acute Toxicity** 14.45792 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

18.0724 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
METHYL ETHYL KETONE 78-93-3		3130 - 3320: 96 h Pimephales promelas mg/L LC50 flow-through	520: 48 h Daphnia magna mg/L EC50 5091: 48 h Daphnia magna mg/L EC50 4025 - 6440: 48 h Daphnia magna mg/L EC50 Static
ISOBUTYL ALCOHOL 78-83-1	230: 48 h Desmodesmus subspicatus mg/L EC50	1370 - 1670: 96 h Pimephales promelas mg/L LC50 flow-through 375: 96 h Pimephales promelas mg/L LC50 static 1480 - 1730: 96 h Lepomis macrochirus mg/L LC50 flow-through 1120 - 1520: 96 h Oncorhynchus mykiss mg/L LC50 flow-through	1300: 48 h Daphnia magna mg/L EC50 1070 - 1933: 48 h Daphnia magna mg/L EC50 Static

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

Component	log Pow
METHYL ETHYL KETONE 78-93-3	0.29

ISOBUTYL ALCOHOL 78-83-1	0.79
-----------------------------	------

**Other Adverse Effects** No information available

### 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

**Disposal Methods** Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Component	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
METHYL ETHYL KETONE 78-93-3	U159	Included in waste streams: F005, F039	200.0 mg/L regulatory level	U159
ISOBUTYL ALCOHOL 78-83-1	U140	Included in waste streams: F005, F039		U140

Component	CAWAST
METHYL ETHYL KETONE 78-93-3	Toxic Ignitable

### 14. TRANSPORT INFORMATION

#### DOT

UN/ID no. 1993  
 Proper Shipping Name FLAMMABLE LIQUID, N.O.S. (METHYL ETHYL KETONE, ISOBUTYL ALCOHOL),  
 Hazard Class 3  
 Packing Group II  
 Emergency Response Guide Number 128

#### IATA

UN/ID no. 1993  
 Proper Shipping Name FLAMMABLE LIQUID, N.O.S. (METHYL ETHYL KETONE, ISOBUTYL ALCOHOL),  
 Hazard Class 3  
 Packing Group II  
 ERG Code 364

**Additional information** Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

### 15. REGULATORY INFORMATION

#### International Inventories

TSCA Complies  
 DSL/NDSL Complies  
 EINECS/ELINCS Complies  
 ENCS Complies  
 IECSC Complies  
 KECL Complies  
 PICCS Complies  
 AICS Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**IECS** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

### United States of America

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372:

Component	SARA 313 - Threshold Values
METHYL ETHYL KETONE - 78-93-3	1.0

#### SARA 311/312 Hazardous

##### Categorization

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

#### CERCLA

Component	Hazardous Substances RQs	CERCLA EHS RQs	RQ
METHYL ETHYL KETONE 78-93-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
ISOBUTYL ALCOHOL 78-83-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

### United States of America

#### California Prop. 65

This product does not contain any Proposition 65 chemicals

#### California SCAQMD Rule 443

Contains Photochemically Reactive Solvent

#### State Right-to-Know

Component	New Jersey	Massachusetts	Pennsylvania
METHYL ETHYL KETONE 78-93-3	X	X	X
ISOBUTYL ALCOHOL 78-83-1	X	X	X

## 16. OTHER INFORMATION

**NFPA** Health 2 Flammability 3 Instability 1 Physical hazard -  
**HMIS (Hazardous Material Information System)** Health 2 Flammability 3 Reactivity 1

Prepared By  
 Revision Date  
 Revision Summary  
 9 4 5 7 10 8 11 14 15


Tnemec Regulatory Dept: 816-474-3400  
 24-Aug-2015

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of SDS**



# Safety Data Sheet

Issue Date No data available

Revision Date 23-Dec-2014

Revision Number 5

## 1. IDENTIFICATION

### Product identifier

Product Code F041-0052  
Product Name THINNER THINNER

### Other means of identification

Common Name NO. 52 THINNER  
UN/ID no. 1263

### Recommended use of the chemical and restrictions on use

Recommended Use industrial paint.  
Uses advised against Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

Manufacturer Address  
Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372

### Emergency telephone number

Company Phone Number Tnemec Regulatory Dept: 816-474-3400  
24 Hour Emergency Phone Number 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Flammable Liquids	Category 2

### Label elements

## EMERGENCY OVERVIEW

### Danger

#### Hazard statements

Causes skin irritation  
Causes serious eye irritation  
May cause drowsiness or dizziness  
Highly flammable liquid and vapor



**Appearance** Colorless

**Physical state** liquid

**Odor** Strong aromatic

**Precautionary Statements**

**Prevention**

- Wash face, hands and any exposed skin thoroughly after handling
- Wear protective gloves/protective clothing/eye protection/face protection
- Avoid breathing dust/fume/gas/mist/vapors/spray
- Do not eat, drink or smoke when using this product
- Use only outdoors or in a well-ventilated area
- Keep away from heat/sparks/open flames/hot surfaces. — No smoking
- Keep container tightly closed
- Ground/bond container and receiving equipment
- Use explosion-proof electrical/ventilating/lighting/mixing/equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge
- Keep cool

**Response**

- Get medical advice/attention if you feel unwell
- If skin irritation occurs: Get medical advice/attention
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- Wash contaminated clothing before reuse
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- Call a POISON CENTER or doctor/physician if you feel unwell
- In case of fire: Use CO2, dry chemical, or foam for extinction

**Storage**

- Store in a well-ventilated place. Keep container tightly closed
- Store locked up
- Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

**Other information**

May be harmful if swallowed  
 SEE SAFETY DATA SHEET  
 Acute Toxicity

0 % of the mixture consists of ingredient(s) of unknown toxicity.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS-No	Weight-%
METHYL ETHYL KETONE	78-93-3	60 - 100%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

**4. FIRST AID MEASURES**

**Description of first aid measures**

---

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	Drink 1 or 2 glasses of water to dilute. Do not induce vomiting. Consult a physician or poison control center IMMEDIATELY. Treat symptomatically.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

**Most important symptoms and effects, both acute and delayed**

**Notes to physician** Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

**Suitable extinguishing media**

Foam. Water spray. Carbon dioxide (CO<sub>2</sub>). Dry chemical.

**Unsuitable extinguishing media** No information available.

**Specific hazards arising from the chemical**

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon dioxide (CO<sub>2</sub>). Hydrocarbons. Oxides of nitrogen.

**Protective equipment and precautions for firefighters**

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Ensure adequate ventilation.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Ensure adequate ventilation. Avoid contact with eyes, skin and clothing. Handle in accordance with good industrial hygiene and safety practice. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not breathe vapours or spray mist. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

### Conditions for safe storage, including any incompatibilities

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

**Incompatible products** Strong oxidizing agents. copper. Strong acids. Amines. Alkalis.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
METHYL ETHYL KETONE 78-93-3	TWA: 200 ppm STEL: 300 ppm	TWA: 200 ppm TWA: 590 mg/m <sup>3</sup> STEL: 300 ppm STEL: 885 mg/m <sup>3</sup>	3000 ppm

NIOSH IDLH: *Immediately Dangerous to Life or Health*

### Appropriate engineering controls

**Engineering measures** Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Use chemical resistant splash type goggles.

**Skin and body protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection** Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	liquid	<b>Odor</b>	Strong aromatic
<b>Appearance</b>	Colorless	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		



<u>Property</u>	<u>Values</u>	<u>Remarks</u>
pH		No data available
Melting point / freezing point		No data available
Boiling point / boiling range	78 °C / 172.0 °F	
Flash point	-7 °C / 20.0 °F	Pensky Martens - Closed Cup
Evaporation rate		No data available
Flammability (solid, gas)		No information available
Flammability Limit in Air		No data available
Upper flammability limit	N/A	
Lower flammability limit	2.0%	
Vapor pressure		No data available
Vapor density		No data available
Specific gravity	.80759	g/cm3
Water solubility	Insoluble in cold water	
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition temperature		No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity		No data available

**Other Information**

Density	6.72032 lbs/gal
Volatile organic compounds (VOC) content	6.679 lbs/gal
Total volatiles weight percent	99.3900 %
Total volatiles volume percent	99.5430 %

**10. STABILITY AND REACTIVITY****Reactivity**

No data available

**Chemical stability**

Stable.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Strong oxidizing agents, copper, Strong acids, Amines, Alkalis

**Hazardous decomposition products**Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon dioxide (CO<sub>2</sub>). Hydrocarbons.**11. TOXICOLOGICAL INFORMATION****Information on Likely Routes of Exposure**

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye contact</b>	Severely irritating to eyes.
<b>Skin contact</b>	Irritating to skin.

**Ingestion**

Harmful if swallowed.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
METHYL ETHYL KETONE 78-93-3	= 2737 mg/kg ( Rat ) = 2483 mg/kg ( Rat )	= 5000 mg/kg ( Rabbit ) = 6480 mg/kg ( Rabbit )	= 11700 ppm ( Rat ) 4 h

**Information on toxicological effects****Symptoms**

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin disorders.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure****Chronic Toxicity**

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**Sensitization**

No information available.

**Mutagenicity**

No information available.

**Carcinogenicity**

There are no known carcinogenic chemicals in this product.

**Reproductive effects**

No information available.

**STOT - single exposure**

Skin, Eyes, Respiratory system, Central Nervous System (CNS)

**STOT - repeated exposure**

No information available

**Target organ effects**

Central nervous system, Eyes, respiratory system, Skin.

**Aspiration hazard**

Based on product level data, this product does not meet the requirement to be classified as an aspiration hazard. However, this product contains an ingredient that may cause aspiration if swallowed.

**Acute Toxicity**

0 % of the mixture consists of ingredient(s) of unknown toxicity.

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

0 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
METHYL ETHYL KETONE 78-93-3		3130 - 3320: 96 h Pimephales promelas mg/L LC50 flow-through	5091: 48 h Daphnia magna mg/L EC50 520: 48 h Daphnia magna mg/L EC50 4025 - 6440: 48 h Daphnia magna mg/L EC50 Static

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

Component	log Pow
METHYL ETHYL KETONE 78-93-3	0.29

**Other Adverse Effects**

No information available

**13. DISPOSAL CONSIDERATIONS****Waste treatment methods****Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Component	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
METHYL ETHYL KETONE 78-93-3	U159	Included in waste streams: F005, F039	200.0 mg/L regulatory level	U159

#### California Hazardous Waste Status

This product contains one or more substances that are listed with the State of California as a hazardous waste

Component	CAWAST
METHYL ETHYL KETONE 78-93-3	Toxic Ignitable

### 14. TRANSPORT INFORMATION

#### DOT

UN/ID no. 1263  
 Proper Shipping Name Paint related material  
 Hazard Class 3  
 Packing Group II  
 Emergency Response Guide Number 128

#### IATA

UN/ID no. 1263  
 Proper Shipping Name Paint related material  
 Hazard Class 3  
 Packing Group II  
 ERG Code 364

#### Additional information

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

### 15. REGULATORY INFORMATION

#### International Inventories

TSCA Complies  
 DSL/NDL Complies  
 EINECS/ELINCS Complies  
 ENCS Complies  
 IECSC Complies  
 KECL Complies  
 PICCS Complies  
 AICS Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

#### United States of America

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

Component	SARA 313 - Threshold Values
METHYL ETHYL KETONE - 78-93-3	1.0

**SARA 311/312 Hazardous**

**Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**CERCLA**

Component	Hazardous Substances RQs	CERCLA EHS RQs	RQ
METHYL ETHYL KETONE 78-93-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

**United States of America**

**California Prop. 65**

This product does not contain any Proposition 65 chemicals

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Component	New Jersey	Massachusetts	Pennsylvania
METHYL ETHYL KETONE 78-93-3	X	X	X

**16. OTHER INFORMATION**

<b>NFPA</b>	Health 1	Flammability 3	Instability 1	Physical hazard -
<b>HMIS (Hazardous Material Information System)</b>	Health 1	Flammability 3	Reactivity 1	

Prepared By Tnemec Regulatory Dept: 816-474-3400  
 Revision Date 23-Dec-2014


Revision Summary  
 9 14 15

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**



# Safety Data Sheet

Issue Date 16-Jul-2015

Revision Date 16-Jul-2015

Revision Number 7

## 1. IDENTIFICATION

### Product identifier

**Product Code** F041-0056  
**Product Name** THINNER CLEAR

### Other means of identification

**Common Name** NO. 56 THINNER  
**UN/ID no.** 1263

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO  
64120-1372

#### **Distributor**

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203  
Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2B
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Flammable Liquids	Category 3

### Label elements

## EMERGENCY OVERVIEW

### **WARNING**

#### **Hazard statements**

Causes skin irritation  
Causes eye irritation  
May cause respiratory irritation. May cause drowsiness or dizziness  
May cause damage to organs through prolonged or repeated exposure  
Flammable liquid and vapor

**Appearance** opaque**Physical state** liquid**Odor** aromatic**Precautionary Statements****Prevention**

Wash face, hands and any exposed skin thoroughly after handling  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Use only outdoors or in a well-ventilated area  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Keep cool

**Response**

Get medical advice/attention if you feel unwell  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 If skin irritation occurs: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Call a POISON CENTER or doctor/physician if you feel unwell  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store in a well-ventilated place. Keep container tightly closed  
 Store locked up  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

May be harmful if swallowed  
 May be harmful in contact with skin  
 Toxic to aquatic life with long lasting effects  
 SEE SAFETY DATA SHEET  
 Acute Toxicity 84.3068 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight-%
P-CHLORO BENZOTRIFLUORIDE	98-56-6	60 - 100%
Trade secret	-	10 - 30%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

##### Description of first aid measures

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

##### Most important symptoms and effects, both acute and delayed

**Notes to physician** Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

##### Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Chlorine. Fluorine.

##### Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

#### 6. ACCIDENTAL RELEASE MEASURES

##### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

##### Environmental Precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

##### Methods and material for containment and cleaning up

<b>Methods for containment</b>	Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.
<b>Methods for cleaning up</b>	If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

<b>Handling</b>	Close container after each use. Avoid contact with eyes, skin and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.
-----------------	---

### Conditions for safe storage, including any incompatibilities

<b>Storage</b>	Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.
<b>Incompatible products</b>	Strong oxidizing agents. Strong acids. Alkaline.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
P-CHLOROBENZOTRIFLUORIDE 98-56-6	TWA: 2.5 mg/m <sup>3</sup>	-	
Trade secret	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m <sup>3</sup>	800 ppm

### Appropriate engineering controls

<b>Engineering measures</b>	Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.
-----------------------------	--

### Individual protection measures, such as personal protective equipment

<b>Eye/face protection</b>	Use chemical resistant splash type goggles.
<b>Skin and body protection</b>	Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
<b>Respiratory protection</b>	Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.
<b>General hygiene considerations</b>	Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.



## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	liquid	<b>Odor</b>	aromatic
<b>Appearance</b>	opaque	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
pH		No data available
Melting point / freezing point		No data available
Boiling point / boiling range	139 °C / 282 °F	
Flash point	42 °C / 107 °F	
Evaporation rate		Pensky Martens - Closed Cup
Flammability (solid, gas)		No data available
Flammability Limit in Air		Not applicable
Upper flammability limit	N/A	No data available
Lower flammability limit	1.0	
Vapor pressure		No data available
Vapor density		No data available
Specific gravity	1.16894	g/cm3
Water solubility	Insoluble in cold water	
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition temperature		No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity		No data available

### Other Information

Density	9.74899 lbs/gal
Volatile organic compounds (VOC) content	4.20332 lbs/gal
Total volatiles weight percent	89.08 %
Total volatiles volume percent	86.26 %

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Possibility of hazardous reactions

None under normal processing.

### Conditions to avoid

Heat, flames and sparks.

### Incompatible materials

Strong oxidizing agents, Strong acids, Alkaline

### Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Chlorine. Fluorine.

## 11. TOXICOLOGICAL INFORMATION

### Information on Likely Routes of Exposure

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Skin contact</b>	Irritating to skin.
<b>Ingestion</b>	Harmful if swallowed.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
P-CHLOROBENZOTRIFLUORIDE 98-56-6	= 13 g/kg ( Rat )	> 2 mL/kg ( Rabbit )	= 33 mg/L ( Rat ) 4 h
Trade secret	= 1600 mg/kg ( Rat ) = 1670 mg/kg ( Rat )	= 12.6 mL/kg ( Rabbit ) = 12600 µL/kg ( Rabbit )	> 2000 ppm ( Rat ) 4 h

### Information on toxicological effects

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritating to eyes and skin.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Chronic Toxicity** NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**Sensitization** No information available.

**Mutagenicity** No information available.

**Carcinogenicity** There are no known carcinogenic chemicals in this product.

**Reproductive effects** No information available.

**STOT - single exposure** Skin, Eyes, Central Nervous System (CNS)

**STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure

**Target organ effects** Central nervous system, Eyes, Peripheral Nervous System (PNS), respiratory system, Skin.

**Aspiration hazard** No information available.

**Acute Toxicity** 84.3068 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Toxic to aquatic life with long lasting effects

74.21915 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
P-CHLOROBENZOTRIFLUORIDE 98-56-6		11.5 - 15.8: 48 h Lepomis macrochirus mg/L LC50 static	3.68: 48 h Daphnia magna mg/L EC50
Trade secret		126 - 137: 96 h Pimephales promelas mg/L LC50 flow-through	

### Persistence and degradability

No information available.

### Bioaccumulation

No information available.

### Mobility in Environmental Media

Component	log Pow
P-CHLOROBENZOTRIFLUORIDE 98-56-6	3.7
Trade secret	1.98

**Other Adverse Effects** No information available

### 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

**Disposal Methods** Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

### 14. TRANSPORT INFORMATION

#### DOT

<b>UN/ID no.</b>	1263
<b>Proper Shipping Name</b>	Paint related material
<b>Hazard Class</b>	3
<b>Packing Group</b>	III
<b>Emergency Response Guide Number</b>	128

#### IATA

<b>UN/ID no.</b>	1263
<b>Proper Shipping Name</b>	Paint related material
<b>Hazard Class</b>	3
<b>Packing Group</b>	III
<b>ERG Code</b>	366

**Additional information** Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

### 15. REGULATORY INFORMATION

#### International Inventories

<b>TSCA</b>	Complies
<b>DSL/NDSL</b>	Complies
<b>EINECS/ELINCS</b>	Complies
<b>ENCS</b>	Does not comply
<b>IECSC</b>	Complies
<b>KECL</b>	Does not comply
<b>PICCS</b>	Does not comply
<b>AICS</b>	Does not comply

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

#### United States of America

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372.

**SARA 311/312 Hazardous**

**Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**CERCLA**

**United States of America**

**California Prop. 65**

This product does not contain any Proposition 65 chemicals

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Component	New Jersey	Massachusetts	Pennsylvania
P-CHLOROBENZOTRIFLUORIDE 98-56-6	X		X
Trade secret	X	X	X

**16. OTHER INFORMATION**

<b>NFPA</b>	Health 2	Flammability 2	Instability 1	Physical hazard -
<b>HMIS (Hazardous Material Information System)</b>	Health 2	Flammability 2	Reactivity 1	


Prepared By Tnemec Regulatory Dept: 816-474-3400  
 Revision Date 16-Jul-2015  
 Revision Summary  
 9 4 5 7 10 8 11 14 15

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**



# Safety Data Sheet

Issue Date 16-Jul-2015

Revision Date 16-Jul-2015

Revision Number 9

## 1. IDENTIFICATION

### Product identifier

**Product Code** F041-0059  
**Product Name** THINNER GRAY

### Other means of identification

**Common Name** NO. 59 THINNER

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372

#### **Distributor**

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203 Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 5
Acute toxicity - Dermal	Category 5
Serious eye damage/eye irritation	Category 2
Aspiration toxicity	Category 2

### Label elements

## EMERGENCY OVERVIEW

### **WARNING**

#### **Hazard statements**

May be harmful if swallowed  
May be harmful in contact with skin  
Causes serious eye irritation  
May be harmful if swallowed and enters airways

**Appearance** opaque**Physical state** liquid**Odor** aromatic**Precautionary Statements****Prevention**

Wash face, hands and any exposed skin thoroughly after handling  
 Wear protective gloves/protective clothing/eye protection/face protection

**Response**

Call a POISON CENTER or doctor/physician if you feel unwell  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do NOT induce vomiting

**Storage**

Store locked up  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

May be harmful in contact with skin  
 SEE SAFETY DATA SHEET  
 Acute Toxicity

0 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight-%
ETHYLENE GLYCOL MONOPROPYL ETHER (SKIN)	2807-30-9	10 - 30%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

**Description of first aid measures**

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.

**Self-protection of the first aider** Use personal protective equipment. Avoid contact with eyes, skin and clothing.

**Most important symptoms and effects, both acute and delayed**

**Notes to physician** Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

**Suitable extinguishing media**

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Water. Do not use a solid water stream as it may scatter and spread fire.

**Specific hazards arising from the chemical**

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

**Protective equipment and precautions for firefighters**

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Handling** Close container after each use. Avoid contact with eyes, skin and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

**Conditions for safe storage, including any incompatibilities**

<b>Storage</b>	Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.
<b>Incompatible products</b>	Incompatible with strong acids and bases. Strong oxidizing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

### **Exposure guidelines**

#### **Appropriate engineering controls**

<b>Engineering measures</b>	Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.
-----------------------------	--

#### **Individual protection measures, such as personal protective equipment**

<b>Eye/face protection</b>	Safety glasses with side-shields Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.
<b>Skin and body protection</b>	Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
<b>Respiratory protection</b>	Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.
<b>General hygiene considerations</b>	Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### **Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	aromatic
<b>Appearance</b>	opaque	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		
<b>Property</b>	<b>Values</b>	<b>Remarks</b>	
<b>pH</b>		No data available	
<b>Melting point / freezing point</b>		No data available	
<b>Boiling point / boiling range</b>	100 °C / 212 °F		
<b>Flash point</b>	No information available	No information available	
<b>Evaporation rate</b>		No data available	
<b>Flammability (solid, gas)</b>		Not applicable	
<b>Flammability Limit in Air</b>		No data available	
<b>Upper flammability limit</b>	N/A		
<b>Lower flammability limit</b>	1.0		
<b>Vapor pressure</b>		No data available	
<b>Vapor density</b>		No data available	
<b>Specific gravity</b>	.97885	g/cm3	
<b>Water solubility</b>	Insoluble in cold water		
<b>Solubility in other solvents</b>		No data available	
<b>Partition coefficient: n-octanol/water</b>		No data available	
<b>Autoignition temperature</b>		No data available	
<b>Decomposition temperature</b>		No data available	



**Kinematic viscosity** No data available  
**Dynamic viscosity** No data available

**Other Information**

**Density** 8.14547 lbs/gal  
**Volatile organic compounds (VOC) content** 7.601 lbs/gal  
**Total volatiles weight percent** 100.0000 %  
**Total volatiles volume percent** 100.0000 %

## 10. STABILITY AND REACTIVITY

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Incompatible with strong acids and bases, Strong oxidizing agents

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

## 11. TOXICOLOGICAL INFORMATION

**Information on Likely Routes of Exposure**

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Skin contact</b>	Irritating to skin.
<b>Ingestion</b>	Harmful if swallowed. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
ETHYLENE GLYCOL MONOPROPYL ETHER (SKIN) 2807-30-9	= 3089 mg/kg ( Rat )	= 870 mg/kg ( Rabbit ) = 960 µL/kg ( Rabbit )	= 1530 ppm ( Rat ) 7 h

**Information on toxicological effects**

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritating to eyes and skin.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Chronic Toxicity** NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**Sensitization** No information available.  
**Mutagenicity** No information available.

<b>Carcinogenicity</b>	There are no known carcinogenic chemicals in this product.
<b>Reproductive effects</b>	No information available.
<b>STOT - single exposure</b>	No information available
<b>STOT - repeated exposure</b>	No information available
<b>Aspiration hazard</b>	Risk of serious damage to the lungs (by aspiration).
<b>Acute Toxicity</b>	0 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

0 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

### Persistence and degradability

No information available.

### Bioaccumulation

No information available.

### Mobility in Environmental Media

### Other Adverse Effects

No information available

## 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

#### **Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

#### **Contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. TRANSPORT INFORMATION

### DOT

#### **Proper Shipping Name**

paint,water base freezable Not regulated

### IATA

#### **Proper Shipping Name**

Not regulated

### Additional information

Call TNEMEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

## 15. REGULATORY INFORMATION

### International Inventories

<b>TSCA</b>	Complies
<b>DSL/NDSL</b>	Complies
<b>EINECS/ELINCS</b>	Does not comply
<b>ENCS</b>	Complies
<b>IECSC</b>	Complies
<b>KECL</b>	Complies
<b>PICCS</b>	Complies
<b>AICS</b>	Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List  
 EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances  
 ENCS - Japan Existing and New Chemical Substances  
 IECS - China Inventory of Existing Chemical Substances  
 KECL - Korean Existing and Evaluated Chemical Substances  
 PICCS - Philippines Inventory of Chemicals and Chemical Substances  
 AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

<b>Component</b>	<b>HAPS Data</b>
ETHYLENE GLYCOL MONOPROPYL ETHER (SKIN)	

**United States of America**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

Component	SARA 313 - Threshold Values
ETHYLENE GLYCOL MONOPROPYL ETHER (SKIN) - 2807-30-9	1.0

**SARA 311/312 Hazardous**

**Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**CERCLA**

**United States of America**

**California Prop. 65**

This product does not contain any Proposition 65 chemicals

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Component	New Jersey	Massachusetts	Pennsylvania
ETHYLENE GLYCOL MONOPROPYL ETHER (SKIN) 2807-30-9	X		X

**16. OTHER INFORMATION**

<b><u>NFPA</u></b>	Health 2	Flammability 0	Instability 0	Physical hazard -
<b><u>HMIS (Hazardous Material Information System)</u></b>	Health 2	Flammability 0	Reactivity 0	

<b>Prepared By</b>	Tnemec Regulatory Dept: 816-474-3400
<b>Revision Date</b>	16-Jul-2015
<b>Revision Summary</b>	
9 4 5 7 10 8 11 14 15	

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**



# Safety Data Sheet

Issue Date 23-Jul-2015

Revision Date 23-Jul-2015

Revision Number 7

## 1. IDENTIFICATION

### Product identifier

**Product Code** F041-0060  
**Product Name** THINNER CLEAR

### Other means of identification

**Common Name** NO. 60 THINNER  
**UN/ID no.** 1263

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO  
64120-1372

#### **Distributor**

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203  
Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Vapors)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable Liquids	Category 3

### Label elements

#### EMERGENCY OVERVIEW

Danger

**Hazard statements**

Harmful if swallowed  
 Harmful if inhaled  
 Causes skin irritation  
 Causes serious eye irritation  
 May cause genetic defects  
 May cause cancer  
 May cause respiratory irritation  
 May be fatal if swallowed and enters airways  
 Flammable liquid and vapor

**Appearance** opaque**Physical state** liquid**Odor** aromatic**Precautionary Statements****Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Wash face, hands and any exposed skin thoroughly after handling  
 Do not eat, drink or smoke when using this product  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Use only outdoors or in a well-ventilated area  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Keep cool

**Response**

IF exposed or concerned: Get medical advice/attention  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 If skin irritation occurs: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Rinse mouth  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do NOT induce vomiting  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store locked up  
 Store in a well-ventilated place. Keep container tightly closed  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

Toxic to aquatic life with long lasting effects

SEE SAFETY DATA SHEET

Acute Toxicity

1.200178 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight-%
METHYL N-AMYL KETONE	110-43-0	30 - 60%
N-BUTANOL (SKIN)	71-36-3	10 - 30%
AROMATIC HYDROCARBON MIXTURE	64742-95-6	10 - 30%
1,2,4-TRIMETHYLBENZENE	95-63-6	10 - 30%
1,3,5-TRIMETHYLBENZENE	108-67-8	1 - 10%
DIETHYLBENZENE	25340-17-4	1 - 10%
CUMENE (SKIN)	98-82-8	0.1 - 1%
ETHYL BENZENE	100-41-4	0.1 - 1%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

#### Description of first aid measures

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	Call a physician or poison control center immediately. Aspiration hazard. Do not induce vomiting without medical advice.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

#### Most important symptoms and effects, both acute and delayed

**Notes to physician** Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

#### Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

#### Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

**Protective equipment and precautions for firefighters**

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Handling** Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

**Conditions for safe storage, including any incompatibilities**

**Storage** Keep away from heat, sparks and flame. Keep out of the reach of children. Keep container tightly closed in a dry and well-ventilated place.

**Incompatible products** Strong oxidizing agents. Strong acids. Alkaline. Halogenated compounds. Lead.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters****Exposure guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
METHYL N-AMYL KETONE 110-43-0	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m <sup>3</sup>	800 ppm
N-BUTANOL (SKIN) 71-36-3	TWA: 20 ppm	Skin Ceiling: 50 ppm Ceiling: 150 mg/m <sup>3</sup> TWA: 100 ppm TWA: 300 mg/m <sup>3</sup>	1400 ppm



CUMENE (SKIN) 98-82-8	TWA: 50 ppm	TWA: 50 ppm TWA: 245 mg/m <sup>3</sup> Skin	900 ppm
ETHYL BENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>	800 ppm

**Appropriate engineering controls****Engineering measures**

Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.

**Skin and body protection**

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection**

Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations**

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	aromatic
<b>Appearance</b>	opaque	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		
<b>Property</b>	<b>Values</b>	<b>Remarks</b>	
<b>pH</b>		No data available	
<b>Melting point / freezing point</b>		No data available	
<b>Boiling point / boiling range</b>	116 °C / 241.0 °F		
<b>Flash point</b>	37 °C / 98 °F		
<b>Evaporation rate</b>		Pensky Martens - Closed Cup	
<b>Flammability (solid, gas)</b>		No data available	
<b>Flammability Limit in Air</b>		Not applicable	
<b>Upper flammability limit</b>	N/A	No data available	
<b>Lower flammability limit</b>	1.0		
<b>Vapor pressure</b>		No data available	
<b>Vapor density</b>		No data available	
<b>Specific gravity</b>	0.83576	g/cm <sup>3</sup>	
<b>Water solubility</b>	Insoluble in cold water		
<b>Solubility in other solvents</b>		No data available	
<b>Partition coefficient: n-octanol/water</b>		No data available	
<b>Autoignition temperature</b>		No data available	
<b>Decomposition temperature</b>		No data available	

Kinematic viscosity No data available  
 Dynamic viscosity No data available

**Other Information**

Density 6.97021 lbs/gal  
 Volatile organic compounds (VOC) content 6.97021 lbs/gal  
 Total volatiles weight percent 100 %  
 Total volatiles volume percent 100 %

**10. STABILITY AND REACTIVITY****Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Strong oxidizing agents, Strong acids, Alkaline, Halogenated compounds, Lead

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

**11. TOXICOLOGICAL INFORMATION****Information on Likely Routes of Exposure**

**Inhalation** May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.

**Eye contact** Causes serious eye damage. Causes serious eye irritation.

**Skin contact** Irritating to skin.

**Ingestion** May be harmful if swallowed and enters airways. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
METHYL N-AMYL KETONE 110-43-0	= 1600 mg/kg ( Rat ) = 1670 mg/kg ( Rat )	= 12.6 mL/kg ( Rabbit ) = 12600 µL/kg ( Rabbit )	> 2000 ppm ( Rat ) 4 h
N-BUTANOL (SKIN) 71-36-3	= 700 mg/kg ( Rat ) = 790 mg/kg ( Rat )	= 3402 mg/kg ( Rabbit ) = 3400 mg/kg ( Rabbit )	> 8000 ppm ( Rat ) 4 h
AROMATIC HYDROCARBON MIXTURE 64742-95-6	= 8400 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	= 3400 ppm ( Rat ) 4 h
1,2,4-TRIMETHYLBENZENE 95-63-6	= 3280 mg/kg ( Rat )	> 3160 mg/kg ( Rabbit )	= 18 g/m <sup>3</sup> ( Rat ) 4 h
1,3,5-TRIMETHYLBENZENE 108-67-8	= 5000 mg/kg ( Rat )		= 24 g/m <sup>3</sup> ( Rat ) 4 h
CUMENE (SKIN) 98-82-8	= 1400 mg/kg ( Rat )	= 12300 µL/kg ( Rabbit )	> 3577 ppm ( Rat ) 6 h = 39000 mg/m <sup>3</sup> ( Rat ) 4 h
ETHYL BENZENE 100-41-4	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.2 mg/L ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritating to eyes and skin.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Chronic Toxicity** NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Substances known to be mutagenic to man. May cause cancer.

**Sensitization** No information available.

**Mutagenicity** May cause genetic defects.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	ACGIH	IARC	NTP	OSHA
CUMENE (SKIN) 98-82-8		Group 2B	Reasonably Anticipated	X
ETHYL BENZENE 100-41-4	A3	Group 2B		X

**Reproductive effects** No information available.

**STOT - single exposure** Skin, Eyes, Central Nervous System (CNS), Respiratory system

**STOT - repeated exposure** No information available

**Aspiration hazard** Risk of serious damage to the lungs (by aspiration).

**Acute Toxicity** 1.200178 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

Toxic to aquatic life with long lasting effects

14.40097 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
METHYL N-AMYL KETONE 110-43-0		126 - 137: 96 h Pimephales promelas mg/L LC50 flow-through	
N-BUTANOL (SKIN) 71-36-3	500: 96 h Desmodosmus subspicatus mg/L EC50 500: 72 h Desmodosmus subspicatus mg/L EC50	1740: 96 h Pimephales promelas mg/L LC50 flow-through 1910000: 96 h Pimephales promelas µg/L LC50 static 100000 - 500000: 96 h Lepomis macrochirus µg/L LC50 static 1730 - 1910: 96 h Pimephales promelas mg/L LC50 static	1897 - 2072: 48 h Daphnia magna mg/L EC50 Static 1983: 48 h Daphnia magna mg/L EC50
AROMATIC HYDROCARBON MIXTURE 64742-95-6		9.22: 96 h Oncorhynchus mykiss mg/L LC50	6.14: 48 h Daphnia magna mg/L EC50
1,2,4-TRIMETHYLBENZENE 95-63-6		7.19 - 8.28: 96 h Pimephales promelas mg/L LC50 flow-through	6.14: 48 h Daphnia magna mg/L EC50
1,3,5-TRIMETHYLBENZENE 108-67-8		3.48: 96 h Pimephales promelas mg/L LC50	50: 24 h Daphnia magna mg/L EC50
CUMENE (SKIN) 98-82-8	2.6: 72 h Pseudokirchneriella subcapitata mg/L EC50	2.7: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 6.04 - 6.61: 96 h Pimephales promelas mg/L LC50 flow-through 4.8: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 5.1: 96 h Poecilia reticulata mg/L LC50 semi-static	0.6: 48 h Daphnia magna mg/L EC50 7.9 - 14.1: 48 h Daphnia magna mg/L EC50 Static

ETHYL BENZENE 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 32: 96 h Lepomis macrochirus mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 9.6: 96 h Poecilia reticulata mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static	1.8 - 2.4: 48 h Daphnia magna mg/L EC50
---------------------------	--	--	---

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

Component	log Pow
METHYL N-AMYL KETONE 110-43-0	1.98
N-BUTANOL (SKIN) 71-36-3	0.785
1,2,4-TRIMETHYLBENZENE 95-63-6	3.63
CUMENE (SKIN) 98-82-8	3.55
ETHYL BENZENE 100-41-4	3.118

**Other Adverse Effects**

No information available

**13. DISPOSAL CONSIDERATIONS****Waste treatment methods****Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

Component	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
N-BUTANOL (SKIN) 71-36-3		Included in waste stream: F039		U031
CUMENE (SKIN) 98-82-8				U055
ETHYL BENZENE 100-41-4		Included in waste stream: F039		

Component	CAWAST
N-BUTANOL (SKIN) 71-36-3	Toxic
CUMENE (SKIN) 98-82-8	Toxic Ignitable
ETHYL BENZENE 100-41-4	Toxic Ignitable

**14. TRANSPORT INFORMATION****DOT**

UNID no. 1263  
 Proper Shipping Name Paint related material  
 Hazard Class 3  
 Packing Group III  
 Emergency Response Guide Number 128

**IATA**

UNID no. 1263  
 Proper Shipping Name Paint related material  
 Hazard Class 3  
 Packing Group III  
 ERG Code 366

**Additional information**

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

**15. REGULATORY INFORMATION**

**International Inventories**

TSCA Complies  
 DSL/NDSL Complies  
 EINECS/ELINCS Complies  
 ENCS Complies  
 IECSC Complies  
 KECL Complies  
 PICCS Complies  
 AICS Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List  
 EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances  
 ENCS - Japan Existing and New Chemical Substances  
 IECSC - China Inventory of Existing Chemical Substances  
 KECL - Korean Existing and Evaluated Chemical Substances  
 PICCS - Philippines Inventory of Chemicals and Chemical Substances  
 AICS - Australian Inventory of Chemical Substances

**The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):**

<b>Component</b>	<b>HAPS Data</b>
CUMENE (SKIN)	
ETHYL BENZENE	

**United States of America**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

Component	SARA 313 - Threshold Values
N-BUTANOL (SKIN) - 71-36-3	1.0
1,2,4-TRIMETHYLBENZENE - 95-63-6	1.0
CUMENE (SKIN) - 98-82-8	1.0
ETHYL BENZENE - 100-41-4	0.1

**SARA 311/312 Hazardous**

**Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
ETHYL BENZENE 100-41-4	1000 lb	X	X	X

**CERCLA**

Component	Hazardous Substances RQs	CERCLA EHS RQs	RQ
N-BUTANOL (SKIN) 71-36-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
CUMENE (SKIN) 98-82-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
ETHYL BENZENE 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

**United States of America****California Prop. 65**

WARNING! This product contains a chemical known in the State of California to cause cancer

Component	California Prop. 65
CUMENE (SKIN) - 98-82-8	Carcinogen
ETHYL BENZENE - 100-41-4	Carcinogen

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Component	New Jersey	Massachusetts	Pennsylvania
METHYL N-AMYL KETONE 110-43-0	X	X	X
N-BUTANOL (SKIN) 71-36-3	X	X	X
1,2,4-TRIMETHYLBENZENE 95-63-6	X	X	X
1,3,5-TRIMETHYLBENZENE 108-67-8		X	
DIETHYLBENZENE 25340-17-4	X		
CUMENE (SKIN) 98-82-8	X	X	X
ETHYL BENZENE 100-41-4	X	X	X

**16. OTHER INFORMATION**

**NFPA** Health 2 Flammability 3 Instability 1 Physical hazard \*  
**HMIS (Hazardous Material Information System)** Health 2\* Flammability 3 Reactivity 1

Prepared By Tnemec Regulatory Dept: 816-474-3400  
 Revision Date 23-Jul-2015


Revision Summary  
 9 4 5 7 10 8 11 14

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**



# Safety Data Sheet

Issue Date 22-Jul-2015

Revision Date 22-Jul-2015

Revision Number 7

## 1. IDENTIFICATION

### Product identifier

**Product Code** F041-0062  
**Product Name** THINNER CLEAR THINNER

### Other means of identification

**Common Name** NO. 62 THINNER  
**UN/ID no.** 1263

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO  
64120-1372

#### **Distributor**

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203  
Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Flammable Liquids	Category 2

### Label elements


## EMERGENCY OVERVIEW

#### **Danger**

#### **Hazard statements**

Causes skin irritation  
Causes serious eye irritation  
May cause respiratory irritation. May cause drowsiness or dizziness  
May cause damage to organs through prolonged or repeated exposure  
Highly flammable liquid and vapor





**Appearance** opaque
**Physical state** liquid
**Odor** aromatic

**Precautionary Statements**

**Prevention**

- Wash face, hands and any exposed skin thoroughly after handling
- Wear protective gloves/protective clothing/eye protection/face protection
- Use only outdoors or in a well-ventilated area
- Do not breathe dust/fume/gas/mist/vapors/spray
- Keep away from heat/sparks/open flames/hot surfaces. — No smoking
- Keep container tightly closed
- Ground/bond container and receiving equipment
- Use explosion-proof electrical/ventilating/lighting/mixing/equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge
- Keep cool

**Response**

- Get medical advice/attention if you feel unwell
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- If eye irritation persists: Get medical advice/attention
- If skin irritation occurs: Get medical advice/attention
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- Wash contaminated clothing before reuse
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- Call a POISON CENTER or doctor/physician if you feel unwell
- In case of fire: Use CO2, dry chemical, or foam for extinction

**Storage**

- Store in a well-ventilated place. Keep container tightly closed
- Store locked up
- Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Other information

May be harmful if swallowed  
 SEE SAFETY DATA SHEET  
 Acute Toxicity

86.187 % of the mixture consists of ingredient(s) of unknown toxicity.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS-No	Weight-%
P-CHLOROBENZOTRIFLUORIDE	98-56-6	60 - 100%
tert-BUTYL ACETATE	540-88-5	10 - 30%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

**4. FIRST AID MEASURES**

**Description of first aid measures**

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	Drink 1 or 2 glasses of water to dilute. Do not induce vomiting. Consult a physician or poison control center IMMEDIATELY. Treat symptomatically.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

**Most important symptoms and effects, both acute and delayed**

**Notes to physician** Treat symptomatically.

**5. FIRE-FIGHTING MEASURES****Suitable extinguishing media**

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

**Specific hazards arising from the chemical**

FLAMMABLE Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Chlorine. Fluorine.

**Protective equipment and precautions for firefighters**

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up**

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

**Precautions for safe handling****Handling**

Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

**Conditions for safe storage, including any incompatibilities****Storage**

Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

**Incompatible products**

Strong oxidizing agents. Strong acids. Alkaline. Nitrates.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters****Exposure guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
P-CHLOROBENZOTRIFLUORIDE 98-56-6	TWA: 2.5 mg/m <sup>3</sup>	-	
tert-BUTYL ACETATE 540-88-5	TWA: 200 ppm	TWA: 200 ppm TWA: 950 mg/m <sup>3</sup>	1500 ppm

**Appropriate engineering controls****Engineering measures**

Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.

**Skin and body protection**

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection**

Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations**

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	aromatic
<b>Appearance</b>	opaque	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
<b>pH</b>		No data available
<b>Melting point / freezing point</b>		Literary Reference
<b>Boiling point / boiling range</b>	98 °C / 208 °F	
<b>Flash point</b>	6 °C / 42 °F	Pensky Martens - Closed Cup
<b>Evaporation rate</b>		No data available
<b>Flammability (solid, gas)</b>		Not applicable
<b>Flammability Limit in Air</b>		No data available
<b>Upper flammability limit</b>	N/A	
<b>Lower flammability limit</b>	1.0	
<b>Vapor pressure</b>		No data available
<b>Vapor density</b>		No data available
<b>Specific gravity</b>	1.24652	g/cm3
<b>Water solubility</b>	Insoluble in cold water	
<b>Solubility in other solvents</b>		No data available
<b>Partition coefficient: n-octanol/water</b>		No data available
<b>Autoignition temperature</b>		No data available
<b>Decomposition temperature</b>		No data available
<b>Kinematic viscosity</b>		No data available
<b>Dynamic viscosity</b>		No data available

**Other Information**

<b>Density</b>	10.39597 lbs/gal
<b>Volatile organic compounds (VOC) content</b>	.000 lbs/gal
<b>Total volatiles weight percent</b>	100 %
<b>Total volatiles volume percent</b>	100 %

## 10. STABILITY AND REACTIVITY

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks. Extremes of temperature and direct sunlight.

**Incompatible materials**

Strong oxidizing agents, Strong acids, Alkaline, Nitrates

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

## 11. TOXICOLOGICAL INFORMATION

**Information on Likely Routes of Exposure**

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye contact</b>	Causes serious eye damage.

**Skin contact** Irritating to skin.

**Ingestion** Harmful if swallowed.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
P-CHLOROBENZOTRIFLUORIDE 98-56-6	= 13 g/kg ( Rat )	> 2 mL/kg ( Rabbit )	= 33 mg/L ( Rat ) 4 h
tert-BUTYL ACETATE 540-88-5	= 4100 mg/kg ( Rat )	> 2 g/kg ( Rabbit )	> 2230 mg/m <sup>3</sup> ( Rat ) 4 h

### Information on toxicological effects

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritating to eyes and skin.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Chronic Toxicity** NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**Sensitization** No information available.

**Mutagenicity** No information available.

**Carcinogenicity** There are no known carcinogenic chemicals in this product.

**Reproductive effects** No information available.

**STOT - single exposure** Skin, Eyes, Central Nervous System (CNS), Respiratory system

**STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure

**Target organ effects** Central nervous system, Eyes, respiratory system, Skin, liver, kidney, Thyroid, blood, thymus.

**Aspiration hazard** No information available.

**Acute Toxicity** 86.187 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

86.187 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
P-CHLOROBENZOTRIFLUORIDE 98-56-6		11.5 - 15.8: 48 h Lepomis macrochirus mg/L LC50 static	3.68: 48 h Daphnia magna mg/L EC50
tert-BUTYL ACETATE 540-88-5		296 - 362: 96 h Pimephales promelas mg/L LC50 flow-through	

### Persistence and degradability

No information available.

### Bioaccumulation

No information available.

### Mobility in Environmental Media

Component	log Pow
P-CHLOROBENZOTRIFLUORIDE 98-56-6	3.7
tert-BUTYL ACETATE 540-88-5	1.38

**Other Adverse Effects** No information available

## 13. DISPOSAL CONSIDERATIONS

**Waste treatment methods**

<b>Disposal Methods</b>	Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.
<b>Contaminated packaging</b>	Empty containers should be taken to an approved waste handling site for recycling or disposal.

<b>14. TRANSPORT INFORMATION</b>
----------------------------------

**DOT**

<b>UN/ID no.</b>	1263
<b>Proper Shipping Name</b>	Paint related material
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>Emergency Response Guide Number</b>	128

**IATA**

<b>UN/ID no.</b>	1263
<b>Proper Shipping Name</b>	Paint related material
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>ERG Code</b>	364

**Additional information**

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

<b>15. REGULATORY INFORMATION</b>
-----------------------------------

**International Inventories**

<b>TSCA</b>	Complies
<b>DSL/NDSL</b>	Complies
<b>EINECS/ELINCS</b>	Complies
<b>ENCS</b>	Complies
<b>IECSC</b>	Complies
<b>KECL</b>	Complies
<b>PICCS</b>	Complies
<b>AICS</b>	Complies

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):**

**United States of America****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372.

**SARA 311/312 Hazardous**

**Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
tert-BUTYL ACETATE 540-88-5				X

**CERCLA**

Component	Hazardous Substances RQs	CERCLA EHS RQs	RQ
tert-BUTYL ACETATE 540-88-5	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

**United States of America**

**California Prop. 65**

This product does not contain any Proposition 65 chemicals

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Component	New Jersey	Massachusetts	Pennsylvania
P-CHLOROBENZOTRIFLUORIDE 98-56-6	X		X
tert-BUTYL ACETATE 540-88-5	X	X	X

**16. OTHER INFORMATION**

<b>NFPA</b>	Health 2	Flammability 3	Instability 1	Physical hazard -
<b>HMIS (Hazardous Material Information System)</b>	Health 2	Flammability 3	Reactivity 1	


Prepared By Tnemec Regulatory Dept: 816-474-3400  
 Revision Date 22-Jul-2015  
 Revision Summary  
 9 4 5 7 10 8 11 14 15

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of MSDS



# Safety Data Sheet

Issue Date 20-Jul-2015

Revision Date 20-Jul-2015

Revision Number 9

## 1. IDENTIFICATION

### Product identifier

**Product Code** F041-0063  
**Product Name** THINNER CLEAR

### Other means of identification

**Common Name** NO. 63 THINNER

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372

#### **Distributor**

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203 Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2B
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 2
Flammable Liquids	Category 3

### Label elements

## EMERGENCY OVERVIEW

### **WARNING**

#### **Hazard statements**

Causes eye irritation  
May cause respiratory irritation. May cause drowsiness or dizziness  
May be harmful if swallowed and enters airways  
Flammable liquid and vapor



**Appearance** clear**Physical state** liquid**Odor** aromatic**Precautionary Statements****Prevention**

Wash face, hands and any exposed skin thoroughly after handling  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Use only outdoors or in a well-ventilated area  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Keep cool

**Response**

Get medical advice/attention if you feel unwell  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Call a POISON CENTER or doctor/physician if you feel unwell  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do NOT induce vomiting  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store locked up  
 Store in a well-ventilated place. Keep container tightly closed  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

Toxic to aquatic life with long lasting effects

SEE SAFETY DATA SHEET

Acute Toxicity

12.11675 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight-%
HEXYL ACETATE	142-92-7	60 - 100%
METHYL N-AMYL KETONE	110-43-0	1 - 10%
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE	124-17-4	1 - 10%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. FIRST AID MEASURES

### Description of first aid measures

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Flush immediately with large amounts of clean water under low pressure for at least 15 minutes. Consult a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	Aspiration hazard. If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

### Most important symptoms and effects, both acute and delayed

<b>Notes to physician</b>	Treat symptomatically.
---------------------------	------------------------

## 5. FIRE-FIGHTING MEASURES

### Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical. Water spray.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

### Specific hazards arising from the chemical

FLAMMABLE Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Peroxides.

### Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.
-----------------------------	--

### Environmental Precautions

<b>Environmental precautions</b>	Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.
----------------------------------	---

### Methods and material for containment and cleaning up

<b>Methods for containment</b>	Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.
--------------------------------	--

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Avoid contact with eyes, skin and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

### Conditions for safe storage, including any incompatibilities

**Storage** Keep away from heat, sparks and flame. Use only in an area containing flame proof equipment. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation. Keep out of the reach of children.

**Incompatible products** Strong oxidizing agents. Strong acids. Alkalis.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
METHYL N-AMYL KETONE 110-43-0	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m <sup>3</sup>	800 ppm

### Appropriate engineering controls

**Engineering measures** Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Safety glasses with side-shields If splashes are likely to occur, wear face-shield.

**Skin and body protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection** Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	liquid	<b>Odor</b>	aromatic
<b>Appearance</b>	clear	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
pH		No data available
Melting point / freezing point		No data available
Boiling point / boiling range	113 °C / 235 °F	
Flash point	57 °C / 134 °F	Pensky Martens - Closed Cup
Evaporation rate		No data available
Flammability (solid, gas)		Not applicable
Flammability Limit in Air		No data available
Upper flammability limit	N/A	
Lower flammability limit	0.8	
Vapor pressure		No data available
Vapor density		No data available
Specific gravity	0.87915	g/cm3
Water solubility	Insoluble in cold water	
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition temperature		No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity		No data available

**Other Information**

Density	7.31585 lbs/gal
Volatile organic compounds (VOC) content	6.41307 lbs/gal
Total volatiles weight percent	87.66 %
Total volatiles volume percent	88.35 %

**10. STABILITY AND REACTIVITY****Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Strong oxidizing agents, Strong acids, Alkalis

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Peroxides.

**11. TOXICOLOGICAL INFORMATION****Information on Likely Routes of Exposure**

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye contact</b>	Irritating to eyes.
<b>Skin contact</b>	Irritating to skin.

**Ingestion**

May be harmful if swallowed and enters airways. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
HEXYL ACETATE 142-92-7	= 41500 µL/kg ( Rat )	> 5 g/kg ( Rabbit )	
METHYL N-AMYL KETONE 110-43-0	= 1600 mg/kg ( Rat ) = 1670 mg/kg ( Rat )	= 12.6 mL/kg ( Rabbit ) = 12600 µL/kg ( Rabbit )	> 2000 ppm ( Rat ) 4 h
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE 124-17-4	= 6500 mg/kg ( Rat )	= 14500 mg/kg ( Rabbit )	= 72500 mg/m <sup>3</sup> ( Rat ) 4 h

**Information on toxicological effects****Symptoms**

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritating to eyes and skin.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure****Chronic Toxicity**

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**Sensitization**

No information available.

**Mutagenicity**

No information available.

**Carcinogenicity**

There are no known carcinogenic chemicals in this product.

**Reproductive effects**

No information available.

**STOT - single exposure**

Skin, Eyes, Central Nervous System (CNS), Respiratory system, Peripheral Nervous System (PNS)

**STOT - repeated exposure**

No information available

**Aspiration hazard**

May be harmful if swallowed and enters airways.

**Acute Toxicity**

12.11675 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

Toxic to aquatic life with long lasting effects

0.71904 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
HEXYL ACETATE 142-92-7		3.7 - 4.4: 96 h Pimephales promelas mg/L LC50 flow-through	
METHYL N-AMYL KETONE 110-43-0		126 - 137: 96 h Pimephales promelas mg/L LC50 flow-through	
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE 124-17-4		77: 96 h Pimephales promelas mg/L LC50 static 50 - 70: 96 h Brachydanio rerio mg/L LC50 static	665: 48 h Daphnia magna mg/L LC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

Component	log Pow
METHYL N-AMYL KETONE 110-43-0	1.98
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE 124-17-4	1.77

**Other Adverse Effects**

No information available

### 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

<b>Disposal Methods</b>	Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.
<b>Contaminated packaging</b>	Empty containers should be taken to an approved waste handling site for recycling or disposal.

### 14. TRANSPORT INFORMATION

#### DOT

**Proper Shipping Name** Paint related material

#### IATA

**UN/ID no.** 1263  
**Proper Shipping Name** Paint related material  
**Hazard Class** 3  
**Packing Group** III  
**ERG Code** 366

#### Additional information

Call TNEMEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

### 15. REGULATORY INFORMATION

#### International Inventories

<b>TSCA</b>	Complies
<b>DSL/NDSL</b>	Complies
<b>EINECS/ELINCS</b>	Complies
<b>ENCS</b>	Does not comply
<b>IECSC</b>	Complies
<b>KECL</b>	Does not comply
<b>PICCS</b>	Does not comply
<b>AICS</b>	Does not comply

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):**

**Component** DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE

**HAPS Data**

#### United States of America

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372:

Component	SARA 313 - Threshold Values
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE - 124-17-4	1.0

**SARA 311/312 Hazardous**

**Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**CERCLA**

**United States of America**

**California Prop. 65**

This product does not contain any Proposition 65 chemicals

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Component	New Jersey	Massachusetts	Pennsylvania
METHYL N-AMYL KETONE 110-43-0	X	X	X
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE 124-17-4	X		X

**16. OTHER INFORMATION**

<b>NFPA</b>	Health 2	Flammability 2	Instability 1	Physical hazard *
<b>HMIS (Hazardous Material Information System)</b>	Health 2	Flammability 2	Reactivity 1	

Prepared By Tnemec Regulatory Dept: 816-474-3400  
 Revision Date 20-Jul-2015

Revision Summary  
 9 4 5 7 10 8 11 14 15

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**



# Safety Data Sheet

Issue Date 16-Jul-2015

Revision Date 16-Jul-2015

Revision Number 7

## 1. IDENTIFICATION

### Product identifier

**Product Code** F041-0065  
**Product Name** THINNER CLEAR

### Other means of identification

**Common Name** NO. 65 THINNER  
**UN/ID no.** 1263

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372

#### **Distributor**

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203 Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Dermal	Category 4
Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 2
Flammable Liquids	Category 2

### Label elements


#### EMERGENCY OVERVIEW

#### **Danger**

#### **Hazard statements**

Harmful in contact with skin  
Causes serious eye irritation  
May cause respiratory irritation. May cause drowsiness or dizziness  
May be harmful if swallowed and enters airways  
Highly flammable liquid and vapor





**Appearance** opaque
**Physical state** liquid
**Odor** aromatic

**Precautionary Statements**

**Prevention**

Wear protective gloves/protective clothing/eye protection/face protection  
 Wash face, hands and any exposed skin thoroughly after handling  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Use only outdoors or in a well-ventilated area  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Keep cool

**Response**

Get medical advice/attention if you feel unwell  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 Call a POISON CENTER or doctor/physician if you feel unwell  
 Wash contaminated clothing before reuse  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Call a POISON CENTER or doctor/physician if you feel unwell  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do NOT induce vomiting  
 In case of fire: Use CO2, dry chemical, or foam for extinction

**Storage**

Store locked up  
 Store in a well-ventilated place. Keep container tightly closed  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

**Other information**

May be harmful if swallowed  
 SEE SAFETY DATA SHEET  
 Acute Toxicity 0 % of the mixture consists of ingredient(s) of unknown toxicity.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS-No	Weight-%
tert-BUTYL ACETATE	540-88-5	60 - 100%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

##### Description of first aid measures

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

##### Most important symptoms and effects, both acute and delayed

<b>Notes to physician</b>	Treat symptomatically.
---------------------------	------------------------

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Water. Do not use a solid water stream as it may scatter and spread fire.

##### Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

##### Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

#### 6. ACCIDENTAL RELEASE MEASURES

##### Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.
-----------------------------	--

##### Environmental Precautions

<b>Environmental precautions</b>	Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.
----------------------------------	---

##### Methods and material for containment and cleaning up

<b>Methods for containment</b>	Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.
--------------------------------	--

**Methods for cleaning up**

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

**Precautions for safe handling****Handling**

Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

**Conditions for safe storage, including any incompatibilities****Storage**

Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

**Incompatible products**

Strong oxidizing agents. Acids. Alkaline. Nitrates.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters****Exposure guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
tert-BUTYL ACETATE 540-88-5	TWA: 200 ppm	TWA: 200 ppm TWA: 950 mg/m <sup>3</sup>	1500 ppm

**Appropriate engineering controls****Engineering measures**

Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Use chemical resistant splash type goggles.

**Skin and body protection**

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection**

Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations**

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Information on basic physical and chemical properties****Physical state**

liquid

<b>Appearance</b>	opaque	<b>Odor</b>	aromatic
<b>Color</b>	No information available	<b>Odor threshold</b>	No information available
<b>Property</b>	<b>Values</b>	<b>Remarks</b>	
pH		No data available	
Melting point / freezing point		No data available	
Boiling point / boiling range	98 °C / 208 °F		
Flash point	16 °C / 60 °F		
Evaporation rate		Pensky Martens - Closed Cup	
Flammability (solid, gas)		No data available	
Flammability Limit in Air		Not applicable	
Upper flammability limit	N/A	No data available	
Lower flammability limit	1.0		
Vapor pressure		No data available	
Vapor density		No data available	
Specific gravity	0.86091	g/cm3	
Water solubility	Insoluble in cold water		
Solubility in other solvents		No data available	
Partition coefficient: n-octanol/water		No data available	
Autoignition temperature		No data available	
Decomposition temperature		No data available	
Kinematic viscosity		No data available	
Dynamic viscosity		No data available	

**Other Information**

Density	7.17999 lbs/gal
Volatile organic compounds (VOC) content	.000 lbs/gal
Total volatiles weight percent	100 %
Total volatiles volume percent	100 %

**10. STABILITY AND REACTIVITY****Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Strong oxidizing agents, Acids, Alkaline, Nitrates

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

**11. TOXICOLOGICAL INFORMATION****Information on Likely Routes of Exposure**

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye contact</b>	Causes serious eye damage.

<b>Skin contact</b>	Harmful in contact with skin.
<b>Ingestion</b>	Harmful if swallowed. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
tert-BUTYL ACETATE 540-88-5	= 4100 mg/kg ( Rat )	> 2 g/kg ( Rabbit )	> 2230 mg/m <sup>3</sup> ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritating to eyes and skin.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Chronic Toxicity** Avoid repeated exposure.  
**Sensitization** No information available.  
**Mutagenicity** No information available.  
**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.  
**Reproductive effects** No information available.  
**STOT - single exposure** Skin, Eyes, Central Nervous System (CNS)  
**STOT - repeated exposure** No information available  
**Aspiration hazard** Risk of serious damage to the lungs (by aspiration).

**Acute Toxicity** 0 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
tert-BUTYL ACETATE 540-88-5		296 - 362: 96 h Pimephales promelas mg/L LC50 flow-through	

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

Component	log Pow
tert-BUTYL ACETATE 540-88-5	1.38

**Other Adverse Effects**

No information available

## 13. DISPOSAL CONSIDERATIONS

**Waste treatment methods****Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

**14. TRANSPORT INFORMATION**

**DOT**

UN/ID no. 1263  
 Proper Shipping Name Paint related material  
 Hazard Class 3  
 Packing Group II  
 Emergency Response Guide Number 128

**IATA**

UN/ID no. 1263  
 Proper Shipping Name Paint related material  
 Hazard Class 3  
 Packing Group II  
 ERG Code 366

**Additional information** Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

**15. REGULATORY INFORMATION**

**International Inventories**

TSCA Complies  
 DSL/NDSL Complies  
 EINECS/ELINCS Complies  
 ENCS Complies  
 IECSC Complies  
 KECL Complies  
 PICCS Complies  
 AICS Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List  
 EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances  
 ENCS - Japan Existing and New Chemical Substances  
 IECSC - China Inventory of Existing Chemical Substances  
 KECL - Korean Existing and Evaluated Chemical Substances  
 PICCS - Philippines Inventory of Chemicals and Chemical Substances  
 AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

**United States of America**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372.

**SARA 311/312 Hazardous**

**Categorization**

Acute Health Hazard Yes  
 Chronic Health Hazard No  
 Fire Hazard Yes  
 Sudden Release of Pressure Hazard No  
 Reactive Hazard No

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
-----------	-----------------------------	------------------------	---------------------------	----------------------------

tert-BUTYL ACETATE 540-88-5				X
--------------------------------	--	--	--	---

**CERCLA**

Component	Hazardous Substances RQs	CERCLA EHS RQs	RQ
tert-BUTYL ACETATE 540-88-5	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

**United States of America**

**California Prop. 65**

This product does not contain any Proposition 65 chemicals

**California SCAQMD Rule 443**

Does Not Contain Photochemically Reactive Solvent

**State Right-to-Know**

Component	New Jersey	Massachusetts	Pennsylvania
tert-BUTYL ACETATE 540-88-5	X	X	X

**16. OTHER INFORMATION**

<b>NFPA</b>	Health 1	Flammability 3	Instability 0	Physical hazard -
<b>HMIS (Hazardous Material Information System)</b>	Health 1	Flammability 3	Reactivity 0	


**Prepared By** Tnemec Regulatory Dept: 816-474-3400  
**Revision Date** 16-Jul-2015  
**Revision Summary**  
 9 4 5 7 10 8 11 14 15

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**



# Safety Data Sheet

Issue Date 16-Jul-2015

Revision Date 16-Jul-2015

Revision Number 6

## 1. IDENTIFICATION

**Product identifier**

**Product Code** F041-0066  
**Product Name** THINNER TEXANOL THINNER

**Other means of identification**

**Common Name** NO. 66 THINNER

**Recommended use of the chemical and restrictions on use**

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

**Details of the supplier of the safety data sheet**

**Manufacturer Address**  
Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372

**Distributor**  
Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203 Boisbriand, Quebec Canada J7G 2T3

**Emergency telephone number**

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

**Classification**

**OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2
Aspiration toxicity	Category 2

**Label elements**

### EMERGENCY OVERVIEW

**WARNING**

**Hazard statements**

Causes serious eye irritation  
May be harmful if swallowed and enters airways



**Appearance** opaque

**Physical state** liquid

**Odor** aromatic

**Precautionary Statements**



**Prevention**

Wash face, hands and any exposed skin thoroughly after handling  
Wear protective gloves/protective clothing/eye protection/face protection

**Response**

Get medical advice/attention if you feel unwell  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
If eye irritation persists: Get medical advice/attention  
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
Do NOT induce vomiting

**Storage**

Store locked up  
Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

May be harmful if swallowed  
May be harmful if inhaled  
Harmful to aquatic life with long lasting effects  
SEE SAFETY DATA SHEET  
Acute Toxicity 0 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight-%
2,2,4-TRIMETHYL-1,3-PENTANEDIOL MONOISOBUTYRATE	25265-77-4	60 - 100%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

**Description of first aid measures**

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse thoroughly with plenty of water for at least 15 minutes. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

**Most important symptoms and effects, both acute and delayed**

**Notes to physician** Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

**Suitable extinguishing media**

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

**Specific hazards arising from the chemical**

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

**Protective equipment and precautions for firefighters**

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS.

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**7. HANDLING AND STORAGE****Precautions for safe handling**

**Handling** Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

**Conditions for safe storage, including any incompatibilities**

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

**Incompatible products** Strong oxidizing agents.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Control parameters**

**Exposure guidelines****Appropriate engineering controls****Engineering measures**

Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Use chemical resistant splash type goggles.

**Skin and body protection**

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection**

Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations**

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	aromatic
<b>Appearance</b>	opaque	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		

<b><u>Property</u></b>	<b><u>Values</u></b>	<b><u>Remarks</u></b>
<b>pH</b>		No data available
<b>Melting point / freezing point</b>		No data available
<b>Boiling point / boiling range</b>	254 °C / 490 °F	
<b>Flash point</b>	120 °C / 248 °F	Pensky Martens - Closed Cup
<b>Evaporation rate</b>		No data available
<b>Flammability (solid, gas)</b>		Not applicable
<b>Flammability Limit in Air</b>		No data available
<b>Upper flammability limit</b>	N/A	
<b>Lower flammability limit</b>	1.0	
<b>Vapor pressure</b>		No data available
<b>Vapor density</b>		No data available
<b>Specific gravity</b>	0.94724	g/cm <sup>3</sup>
<b>Water solubility</b>	Insoluble in cold water	
<b>Solubility in other solvents</b>		No data available
<b>Partition coefficient: n-octanol/water</b>		No data available
<b>Autoignition temperature</b>		No data available
<b>Decomposition temperature</b>		No data available
<b>Kinematic viscosity</b>		No data available
<b>Dynamic viscosity</b>	13.5 mPa s	approx

**Other Information**

<b>Density</b>	7.90002 lbs/gal
<b>Volatile organic compounds (VOC) content</b>	7.90002 lbs/gal
<b>Total volatiles weight percent</b>	100 %
<b>Total volatiles volume percent</b>	100 %

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Possibility of hazardous reactions

None under normal processing.

### Conditions to avoid

Heat, flames and sparks.

### Incompatible materials

Strong oxidizing agents

### Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

## 11. TOXICOLOGICAL INFORMATION

### Information on Likely Routes of Exposure

<b>Inhalation</b>	Aspiration into lungs can produce severe lung damage.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Skin contact</b>	CAUSES SKIN IRRITATION.
<b>Ingestion</b>	Harmful if swallowed. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
2,2,4-TRIMETHYL-1,3-PENTANEDI OL MONOISOBUTYRATE 25265-77-4	= 3200 mg/kg ( Rat )	> 15200 mg/kg ( Rat )	

### Information on toxicological effects

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritating to eyes and skin.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

<b>Chronic Toxicity</b>	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
<b>Sensitization</b>	No information available.
<b>Mutagenicity</b>	No information available.
<b>Carcinogenicity</b>	There are no known carcinogenic chemicals in this product.
<b>Reproductive effects</b>	No information available.
<b>STOT - single exposure</b>	No information available
<b>STOT - repeated exposure</b>	No information available
<b>Aspiration hazard</b>	Risk of serious damage to the lungs (by aspiration).
<b>Acute Toxicity</b>	0 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Harmful to aquatic life with long lasting effects

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
2,2,4-TRIMETHYL-1,3-PENTANEDIOL MONOISOBUTYRATE 25265-77-4	18.4: 72 h Pseudokirchneriella subcapitata mg/L EC50	30: 96 h Pimephales promelas mg/L LC50	95: 96 h Daphnia magna mg/L LC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

Component	log Pow
2,2,4-TRIMETHYL-1,3-PENTANEDIOL MONOISOBUTYRATE 25265-77-4	3.47

**Other Adverse Effects**

No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

**14. TRANSPORT INFORMATION**

**DOT**

Proper Shipping Name      Paint related material

**IATA**

Proper Shipping Name      Not regulated

**Additional information**

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

**15. REGULATORY INFORMATION**

**International Inventories**

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

-

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List  
 EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances  
 ENCS - Japan Existing and New Chemical Substances  
 IECSC - China Inventory of Existing Chemical Substances  
 KECL - Korean Existing and Evaluated Chemical Substances  
 PICCS - Philippines Inventory of Chemicals and Chemical Substances  
 AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

### United States of America

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372.

#### SARA 311/312 Hazardous

##### Categorization

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

### CERCLA

### United States of America

#### California Prop. 65

This product does not contain any Proposition 65 chemicals

#### California SCAQMD Rule 443

Contains Photochemically Reactive Solvent

#### State Right-to-Know

## 16. OTHER INFORMATION

<u>NFPA</u>	Health 1	Flammability 1	Instability 0	Physical hazard -
<u>HMIS (Hazardous Material Information System)</u>	Health 1	Flammability 1	Reactivity 0	


Prepared By Tnemec Regulatory Dept: 816-474-3400  
 Revision Date 16-Jul-2015  
 Revision Summary  
 9 4 5 7 10 8 11 14 15

#### Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**



# Safety Data Sheet

Issue Date 16-Jul-2015

Revision Date 16-Jul-2015

Revision Number 7

## 1. IDENTIFICATION

### Product identifier

**Product Code** F041-0068  
**Product Name** THINNER CLEAR

### Other means of identification

**Common Name** NO. 68 THINNER  
**UN/ID no.** 1231

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO  
64120-1372

#### **Distributor**

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203  
Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 2
Flammable Liquids	Category 2

### Label elements

## EMERGENCY OVERVIEW

### **Danger**

#### **Hazard statements**

Causes skin irritation  
Causes serious eye irritation  
May cause drowsiness or dizziness  
May be harmful if swallowed and enters airways  
Highly flammable liquid and vapor

**Appearance** opaque**Physical state** liquid**Odor** aromatic**Precautionary Statements****Prevention**

Wash face, hands and any exposed skin thoroughly after handling  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Use only outdoors or in a well-ventilated area  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Keep cool

**Response**

Get medical advice/attention if you feel unwell  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 If skin irritation occurs: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Call a POISON CENTER or doctor/physician if you feel unwell  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do NOT induce vomiting  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store locked up  
 Store in a well-ventilated place. Keep container tightly closed  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

May be harmful if swallowed  
 SEE SAFETY DATA SHEET  
 Acute Toxicity

0 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight-%
METHYL ACETATE	79-20-9	60 - 100%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.



## 4. FIRST AID MEASURES

### Description of first aid measures

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

### Most important symptoms and effects, both acute and delayed

<b>Notes to physician</b>	Treat symptomatically.
---------------------------	------------------------

## 5. FIRE-FIGHTING MEASURES

### Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Water.

### Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

### Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.
-----------------------------	--

### Environmental Precautions

<b>Environmental precautions</b>	Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.
----------------------------------	---

### Methods and material for containment and cleaning up

<b>Methods for containment</b>	Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.
--------------------------------	--

**Methods for cleaning up**

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

**Precautions for safe handling****Handling**

Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

**Conditions for safe storage, including any incompatibilities****Storage**

Vapors may ignite explosively. Keep away from heat, sparks and flame. VAPORS MAY CAUSE FLASH FIRE. Use only in an area containing flame proof equipment. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation.

**Incompatible products**

Peroxides. Strong oxidizing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters****Exposure guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
METHYL ACETATE 79-20-9	TWA: 200 ppm STEL: 250 ppm	TWA: 200 ppm TWA: 610 mg/m <sup>3</sup> STEL: 250 ppm STEL: 760 mg/m <sup>3</sup>	3100 ppm

**Appropriate engineering controls****Engineering measures**

Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Use chemical resistant splash type goggles.

**Skin and body protection**

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection**

Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations**

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	aromatic
<b>Appearance</b>	opaque	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
pH		No data available
Melting point / freezing point		No data available
Boiling point / boiling range	72 °C / 162 °F	
Flash point	-10 °C / 14 °F	Pensky Martens - Closed Cup
Evaporation rate		No data available
Flammability (solid, gas)		Not applicable
Flammability Limit in Air		No data available
Upper flammability limit	N/A	
Lower flammability limit	1.0	
Vapor pressure		No data available
Vapor density		No data available
Specific gravity	0.92926	g/cm3
Water solubility	Insoluble in cold water	
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition temperature		No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity		No data available

**Other Information**

<b>Density</b>	7.75002 lbs/gal
<b>Volatile organic compounds (VOC) content</b>	.000 lbs/gal
<b>Total volatiles weight percent</b>	100 %
<b>Total volatiles volume percent</b>	100 %

**10. STABILITY AND REACTIVITY****Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Peroxides, Strong oxidizing agents

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

**11. TOXICOLOGICAL INFORMATION****Information on Likely Routes of Exposure**

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
-------------------	---

<b>Eye contact</b>	Causes serious eye irritation.
<b>Skin contact</b>	CAUSES SKIN IRRITATION.
<b>Ingestion</b>	Harmful if swallowed. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
METHYL ACETATE 79-20-9	> 5000 mg/kg ( Rat )	> 5 g/kg ( Rabbit )	= 16000 ppm ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritating to eyes and skin.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Chronic Toxicity** NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**Sensitization** No information available.

**Mutagenicity** No information available.

**Carcinogenicity** There are no known carcinogenic chemicals in this product.

**Reproductive effects** No information available.

**STOT - single exposure** Skin, Eyes, Central Nervous System (CNS)

**STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure

**Target organ effects** blood, Central nervous system, Central Vascular System (CVS), Gastrointestinal tract, liver, respiratory system, Skin.

**Aspiration hazard** Risk of serious damage to the lungs (by aspiration).

**Acute Toxicity** 0 % of the mixture consists of ingredient(s) of unknown toxicity.

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
METHYL ACETATE 79-20-9	120: 72 h <i>Desmodesmus subspicatus</i> mg/L EC50	295 - 348: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 250 - 350: 96 h <i>Brachydanio rerio</i> mg/L LC50 static	1026.7: 48 h <i>Daphnia magna</i> mg/L EC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

Component	log Pow
METHYL ACETATE 79-20-9	0.18

**Other Adverse Effects**

No information available

**13. DISPOSAL CONSIDERATIONS****Waste treatment methods**

<b>Disposal Methods</b>	Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.
<b>Contaminated packaging</b>	Empty containers should be taken to an approved waste handling site for recycling or disposal.

Component	CAWAST
METHYL ACETATE 79-20-9	Toxic Ignitable

#### 14. TRANSPORT INFORMATION

##### DOT

<b>UN/ID no.</b>	1231
<b>Proper Shipping Name</b>	Methyl Acetate
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>Emergency Response Guide Number</b>	129

##### IATA

<b>UN/ID no.</b>	1231
<b>Proper Shipping Name</b>	Methyl Acetate
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>ERG Code</b>	364

##### Additional information

Call TNEMEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

#### 15. REGULATORY INFORMATION

##### International Inventories

<b>TSCA</b>	Complies
<b>DSL/NDSL</b>	Complies
<b>EINECS/ELINCS</b>	Complies
<b>ENCS</b>	Complies
<b>IECSC</b>	Complies
<b>KECL</b>	Complies
<b>PICCS</b>	Complies
<b>AICS</b>	Complies

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):**

##### United States of America

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372.

**SARA 311/312 Hazardous**

**Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**CERCLA**

**United States of America**

**California Prop. 65**

This product does not contain any Proposition 65 chemicals

**California SCAQMD Rule 443**

Does Not Contain Photochemically Reactive Solvent

**State Right-to-Know**

Component	New Jersey	Massachusetts	Pennsylvania
METHYL ACETATE 79-20-9	X	X	X

**16. OTHER INFORMATION**

<b>NFPA</b>	Health 1	Flammability 3	Instability 1	Physical hazard -
<b>HMIS (Hazardous Material Information System)</b>	Health 1	Flammability 3	Reactivity 1	


Prepared By Tnemec Regulatory Dept: 816-474-3400  
 Revision Date 16-Jul-2015  
 Revision Summary  
 9 4 5 7 10 8 11 14 15

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**



# Safety Data Sheet

Issue Date 16-Jul-2015

Revision Date 16-Jul-2015

Revision Number 7

## 1. IDENTIFICATION

### Product identifier

**Product Code** F041-0072  
**Product Name** THINNER CLEAR

### Other means of identification

**Common Name** NO. 72 THINNER

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO  
64120-1372

#### **Distributor**

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203  
Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 2
Flammable Liquids	Category 4

### Label elements

#### EMERGENCY OVERVIEW

#### **WARNING**

#### **Hazard statements**

May cause respiratory irritation. May cause drowsiness or dizziness  
May be harmful if swallowed and enters airways  
Combustible liquid

**Appearance** opaque**Physical state** liquid**Odor** aromatic**Precautionary Statements****Prevention**

Avoid breathing dust/fume/gas/mist/vapors/spray  
 Use only outdoors or in a well-ventilated area  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Keep cool

**Response**

Get medical advice/attention if you feel unwell  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Call a POISON CENTER or doctor/physician if you feel unwell  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do NOT induce vomiting  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store locked up  
 Store in a well-ventilated place. Keep container tightly closed  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

May be harmful in contact with skin

SEE SAFETY DATA SHEET

Acute Toxicity

0 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight-%
DIPROPYLENE GLYCOL MONOMETHYL ETHER ACETATE	88917-22-0	60 - 100%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

**Description of first aid measures****General advice**

If symptoms persist, call a physician.

**Eye contact**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.

**Skin contact**

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.



<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	Aspiration hazard. If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

**Most important symptoms and effects, both acute and delayed**

**Notes to physician** Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

**Suitable extinguishing media**

Carbon dioxide. Dry chemical. Foam. Water spray.

**Unsuitable extinguishing media** No information available.

**Specific hazards arising from the chemical**

FLAMMABLE Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

**Protective equipment and precautions for firefighters**

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Handling** Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

**Conditions for safe storage, including any incompatibilities**

**Storage** Keep away from heat, sparks and flame. Use only in an area containing flame proof equipment. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation.

**Incompatible products** Incompatible with strong acids and bases. Oxygen. Strong oxidizing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters**

**Exposure guidelines**  
**Appropriate engineering controls**

**Engineering measures** Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Safety glasses with side-shields

**Skin and body protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection** Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	aromatic
<b>Appearance</b>	opaque	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		

<b><u>Property</u></b>	<b><u>Values</u></b>	<b><u>Remarks</u></b>
<b>pH</b>		No data available
<b>Melting point / freezing point</b>		No data available
<b>Boiling point / boiling range</b>	209 °C / 408 °F	
<b>Flash point</b>	85 °C / 185 °F	
<b>Evaporation rate</b>		Pensky Martens - Closed Cup
<b>Flammability (solid, gas)</b>		No data available
<b>Flammability Limit in Air</b>		Not applicable
<b>Upper flammability limit</b>	N/A	No data available
<b>Lower flammability limit</b>	1.0	

Vapor pressure		No data available
Vapor density		No data available
Specific gravity	.97578	g/cm3
Water solubility	Insoluble in cold water	
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition temperature		No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity		No data available

**Other Information**

Density	8.11998 lbs/gal
Volatile organic compounds (VOC) content	8.120 lbs/gal
Total volatiles weight percent	100.0000 %
Total volatiles volume percent	100.0000 %

**10. STABILITY AND REACTIVITY****Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Incompatible with strong acids and bases, Oxygen, Strong oxidizing agents

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

**11. TOXICOLOGICAL INFORMATION****Information on Likely Routes of Exposure**

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye contact</b>	Irritating to eyes.
<b>Skin contact</b>	Irritating to skin.
<b>Ingestion</b>	May be harmful if swallowed and enters airways. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

**Information on toxicological effects**

<b>Symptoms</b>	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin disorders.
-----------------	--

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

<b>Chronic Toxicity</b>	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
<b>Sensitization</b>	No information available.
<b>Mutagenicity</b>	No information available.
<b>Carcinogenicity</b>	There are no known carcinogenic chemicals in this product.
<b>Reproductive effects</b>	No information available.
<b>STOT - single exposure</b>	Central Nervous System (CNS)
<b>STOT - repeated exposure</b>	Causes damage to organs through prolonged or repeated exposure
<b>Aspiration hazard</b>	May be harmful if swallowed and enters airways. Risk of serious damage to the lungs (by aspiration).
<b>Acute Toxicity</b>	0 % of the mixture consists of ingredient(s) of unknown toxicity.
<b>The following values are calculated based on chapter 3.1 of the GHS document .</b>	

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Toxic to aquatic life with long lasting effects

100 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

### Persistence and degradability

No information available.

### Bioaccumulation

No information available.

### Mobility in Environmental Media

### Other Adverse Effects

No information available

## 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

#### **Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

#### **Contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. TRANSPORT INFORMATION

### DOT

**Proper Shipping Name**

Paint related material

### IATA

**Proper Shipping Name**

Paint related material, Not regulated

### Additional information

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

## 15. REGULATORY INFORMATION

**International Inventories**

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

**United States of America****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372:

**SARA 311/312 Hazardous****Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**CERCLA****United States of America****California Prop. 65**

This product does not contain any Proposition 65 chemicals

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

<b>16. OTHER INFORMATION</b>
------------------------------

<b><u>NFPA</u></b>	Health 1	Flammability 1	Instability 0	Physical hazard *
<b><u>HMIS (Hazardous Material Information System)</u></b>	Health 1	Flammability 1	Reactivity 0	

Prepared By

Revision Date

Revision Summary

9 4 5 7 10 8 11 14 15

Tnemec Regulatory Dept: 816-474-3400


16-Jul-2015

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**



# Safety Data Sheet

Issue Date No data available

Revision Date 07-Jan-2015

Revision Number 5

## 1. IDENTIFICATION

### Product identifier

Product Code F041-0073  
Product Name THINNER CLEAR

### Other means of identification

Common Name NO. 73 THINNER

### Recommended use of the chemical and restrictions on use

Recommended Use industrial paint.  
Uses advised against Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

Manufacturer Address  
Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372

### Emergency telephone number

Company Phone Number Tnemec Regulatory Dept: 816-474-3400  
24 Hour Emergency Phone Number 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable Liquids	Category 3
-------------------	------------

### Label elements

#### EMERGENCY OVERVIEW

#### WARNING

Flammable liquid and vapor



Appearance Colorless

Physical state liquid

Odor Slight

### Precautionary Statements

**Prevention**

Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Wear protective gloves/protective clothing/eye protection/face protection

**Response**

Get medical advice/attention if you feel unwell  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store in a well-ventilated place. Keep cool  
 Store locked up  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

May be harmful if swallowed  
 Harmful to aquatic life with long lasting effects  
 SEE SAFETY DATA SHEET  
 Acute Toxicity 0 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight-%
ETHYL 3-ETHOXYPROPIONATE	763-69-9	60 - 100%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

**Description of first aid measures**

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
<b>Inhalation</b>	Remove to fresh air. Oxygen or artificial respiration if needed.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

**Most important symptoms and effects, both acute and delayed**

**Notes to physician** Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES



**Suitable extinguishing media**

Water spray. Carbon dioxide (CO2). Dry chemical. Foam.

**Unsuitable extinguishing media** No information available.

**Specific hazards arising from the chemical**

FLAMMABLE Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon dioxide (CO2). Hydrocarbons. Peroxides.

**Protective equipment and precautions for firefighters**

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Handling** Close container after each use. Avoid contact with eyes, skin and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

**Conditions for safe storage, including any incompatibilities**

**Storage** Keep away from heat, sparks and flame. Use only in an area containing flame proof equipment. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation.

**Incompatible products** Strong oxidizing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters****Exposure guidelines****Appropriate engineering controls****Engineering measures**

Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Safety glasses with side-shields

**Skin and body protection**

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection**

Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations**

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	Slight
<b>Appearance</b>	Colorless	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		

**Property****Values****Remarks**

<b>pH</b>		No data available
<b>Melting point / freezing point</b>		No data available
<b>Boiling point / boiling range</b>	164 °C / 328.0 °F	
<b>Flash point</b>	61 °C / 142.0 °F	
<b>Evaporation rate</b>		Pensky Martens - Closed Cup
<b>Flammability (solid, gas)</b>		No data available
<b>Flammability Limit in Air</b>		No information available
<b>Upper flammability limit</b>	N/A	No data available
<b>Lower flammability limit</b>	1.0%	
<b>Vapor pressure</b>		No data available
<b>Vapor density</b>		No data available
<b>Specific gravity</b>	.95055	g/cm <sup>3</sup>
<b>Water solubility</b>	Insoluble in cold water	
<b>Solubility in other solvents</b>		No data available
<b>Partition coefficient: n-octanol/water</b>		No data available
<b>Autoignition temperature</b>		No data available
<b>Decomposition temperature</b>		No data available
<b>Kinematic viscosity</b>	1.328 mm <sup>2</sup> /s	
<b>Dynamic viscosity</b>	1.20 mPa s	

**Other Information**

<b>Density</b>	7.91002 lbs/gal
<b>Volatile organic compounds (VOC) content</b>	7.910 lbs/gal
<b>Total volatiles weight percent</b>	100.0000 %

Total volatiles volume percent 100.0000 %

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Possibility of hazardous reactions

Possibility of hazardous reactions.

### Conditions to avoid

Heat, flames and sparks.

### Incompatible materials

Strong oxidizing agents

### Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Peroxides. Carbon dioxide (CO<sub>2</sub>). Hydrocarbons.

## 11. TOXICOLOGICAL INFORMATION

### Information on Likely Routes of Exposure

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye contact</b>	Irritating to eyes.
<b>Skin contact</b>	Irritating to skin.
<b>Ingestion</b>	Harmful if swallowed.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
ETHYL 3-ETHOXYPROPIONATE 763-69-9	= 3200 mg/kg ( Rat )	= 10 mL/kg ( Rabbit )	

### Information on toxicological effects

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin disorders.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

<b>Chronic Toxicity</b>	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
<b>Sensitization</b>	No information available.
<b>Mutagenicity</b>	No information available.
<b>Carcinogenicity</b>	There are no known carcinogenic chemicals in this product.
<b>Reproductive effects</b>	No information available.
<b>STOT - single exposure</b>	No information available
<b>STOT - repeated exposure</b>	No information available
<b>Aspiration hazard</b>	Based on product level data, this product does not meet the requirement to be classified as an aspiration hazard. However, this product contains an ingredient that may cause aspiration if swallowed.
<b>Acute Toxicity</b>	0 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Harmful to aquatic life with long lasting effects

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
ETHYL 3-ETHOXYPROPIONATE 763-69-9		62: 96 h Pimephales promelas mg/L LC50 static	970: 48 h Daphnia magna mg/L EC50

### Persistence and degradability

No information available.

### Bioaccumulation

No information available.

### Mobility in Environmental Media

Component	log Pow
ETHYL 3-ETHOXYPROPIONATE 763-69-9	1.35

### Other Adverse Effects

No information available

## 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

#### **Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

#### **Contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. TRANSPORT INFORMATION

### DOT

Proper Shipping Name      Paint related material

### IATA

Proper Shipping Name      Not regulated

### Additional information

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

## 15. REGULATORY INFORMATION

### International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List  
 EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances  
 ENCS - Japan Existing and New Chemical Substances  
 IECS - China Inventory of Existing Chemical Substances  
 KECL - Korean Existing and Evaluated Chemical Substances  
 PICCS - Philippines Inventory of Chemicals and Chemical Substances  
 AICS - Australian Inventory of Chemical Substances

**United States of America**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372.

**SARA 311/312 Hazardous**

**Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**CERCLA**

**United States of America**

**California Prop. 65**

This product does not contain any Proposition 65 chemicals

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

**16. OTHER INFORMATION**

<b><u>NFPA</u></b>	Health 1	Flammability 2	Instability 1	Physical hazard -
<b><u>HMIS (Hazardous Material Information System)</u></b>	Health 1	Flammability 2	Reactivity 1	

Prepared By Tnemec Regulatory Dept: 816-474-3400  
 Revision Date 07-Jan-2015


Revision Summary  
 9 4 5 7 10 11 14 15

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**



# Safety Data Sheet

Issue Date 28-Jul-2015

Revision Date 28-Jul-2015

Revision Number 6

## 1. IDENTIFICATION

### Product identifier

**Product Code** F041-0074  
**Product Name** THINNER CLEAR

### Other means of identification

**Common Name** NO. 74 THINNER  
**UN/ID no.** 1263

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

**Manufacturer Address** Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372  
**Distributor** Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203 Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 2
Flammable Liquids	Category 2


### Label elements

#### **EMERGENCY OVERVIEW**

#### **Danger**

#### **Hazard statements**

Causes skin irritation  
Causes serious eye irritation  
May cause drowsiness or dizziness  
May be harmful if swallowed and enters airways  
Highly flammable liquid and vapor

		
<b>Appearance</b> Colorless	<b>Physical state</b> liquid	<b>Odor</b> aromatic

**Precautionary Statements****Prevention**

Wash face, hands and any exposed skin thoroughly after handling  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Use only outdoors or in a well-ventilated area  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Keep cool

**Response**

Get medical advice/attention if you feel unwell  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 If skin irritation occurs: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Call a POISON CENTER or doctor/physician if you feel unwell  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do NOT induce vomiting  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store locked up  
 Store in a well-ventilated place. Keep container tightly closed  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

SEE SAFETY DATA SHEET

Acute Toxicity

0 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight-%
ACETONE	67-64-1	60 - 100%
METHYL ACETATE	79-20-9	10 - 30%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

##### Description of first aid measures

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	Aspiration hazard. If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

##### Most important symptoms and effects, both acute and delayed

<b>Notes to physician</b>	Treat symptomatically.
---------------------------	------------------------

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

alcohol-resistant foam. Dry chemical. Carbon dioxide. Water spray.

**Unsuitable extinguishing media** No information available.

##### Specific hazards arising from the chemical

FLAMMABLE Flash back possible over considerable distance Keep product and empty container away from heat and sources of ignition Thermal decomposition can lead to release of irritating gases and vapours

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

**Sensitivity to Static Discharge** yes.

##### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to cool unopened containers. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

#### 6. ACCIDENTAL RELEASE MEASURES

##### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Ensure adequate ventilation. Use personal protective equipment. Avoid contact with eyes, skin and clothing. Remove all sources of ignition.

##### Environmental Precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system.

##### Methods and material for containment and cleaning up



<b>Methods for containment</b>	Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.
<b>Methods for cleaning up</b>	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

## 7. HANDLING AND STORAGE

### Precautions for safe handling

<b>Handling</b>	Close container after each use. Ensure adequate ventilation. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. Wear personal protective equipment. Keep away from open flames, hot surfaces and sources of ignition. Do not burn, or use a cutting torch on, the empty drum. Do not breathe vapours or spray mist. Wash thoroughly after handling.
-----------------	--

### Conditions for safe storage, including any incompatibilities

<b>Storage</b>	Vapors may ignite explosively. Keep away from heat, sparks and flame. VAPORS MAY CAUSE FLASH FIRE. Use only in an area containing flame proof equipment. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation. Keep out of the reach of children.
----------------	---

<b>Incompatible products</b>	Peroxides. Strong oxidizing agents.
------------------------------	-------------------------------------

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
ACETONE 67-64-1	TWA: 500 ppm STEL: 750 ppm	TWA: 750 ppm TWA: 1800 mg/m <sup>3</sup> STEL: 2400 mg/m <sup>3</sup> STEL: 1000 ppm TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup>	2500 ppm
METHYL ACETATE 79-20-9	TWA: 200 ppm STEL: 250 ppm	TWA: 200 ppm TWA: 610 mg/m <sup>3</sup> STEL: 250 ppm STEL: 760 mg/m <sup>3</sup>	3100 ppm

### Appropriate engineering controls

<b>Engineering measures</b>	Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.
-----------------------------	--

### Individual protection measures, such as personal protective equipment

<b>Eye/face protection</b>	Use chemical resistant splash type goggles.
<b>Skin and body protection</b>	Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection**

Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations**

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Information on basic physical and chemical properties**

<b>Physical state</b>	liquid		
<b>Appearance</b>	Colorless	<b>Odor</b>	aromatic
<b>Color</b>	No information available	<b>Odor threshold</b>	No information available
<b>Property</b>	<b>Values</b>	<b>Remarks</b>	
pH		No data available	
Melting point / freezing point		No data available	
Boiling point / boiling range	> = 56 °C / 133 °F		
Flash point	.? - 17 °C / 1.0 °F	Pensky Martens - Closed Cup	
Evaporation rate		No data available	
Flammability (solid, gas)		Not applicable	
Flammability Limit in Air		No data available	
Upper flammability limit	N/A		
Lower flammability limit	1.0		
Vapor pressure		No data available	
Vapor density		No data available	
Specific gravity	0.81980	g/cm3	
Water solubility	Insoluble in cold water		
Solubility in other solvents		No data available	
Partition coefficient: n-octanol/water		No data available	
Autoignition temperature		No data available	
Decomposition temperature		No data available	
Kinematic viscosity		No data available	
Dynamic viscosity		No data available	
<b>Other Information</b>			
Density	6.822 lbs/gal		
Total volatiles weight percent	100 %		
Total volatiles volume percent	100 %		

## 10. STABILITY AND REACTIVITY

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Peroxides, Strong oxidizing agents

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Methanol. acetic acid.

## 11. TOXICOLOGICAL INFORMATION

**Information on Likely Routes of Exposure**

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye contact</b>	Causes serious eye damage.
<b>Skin contact</b>	Irritating to skin. Prolonged contact may cause redness and irritation.
<b>Ingestion</b>	May be harmful if swallowed and enters airways. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
ACETONE 67-64-1	= 5800 mg/kg ( Rat )		= 50100 mg/m <sup>3</sup> ( Rat ) 8 h
METHYL ACETATE 79-20-9	> 5000 mg/kg ( Rat )	> 5 g/kg ( Rabbit )	= 16000 ppm ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin disorders.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Chronic Toxicity** NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**Sensitization** No information available.

**Mutagenicity** No information available.

**Carcinogenicity** There are no known carcinogenic chemicals in this product.

**Reproductive effects** No information available.

**STOT - single exposure** Skin, Eyes, Central Nervous System (CNS)

**STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure, liver, kidney, Blood, Central Nervous System (CNS)

**Target organ effects** Central nervous system, respiratory system, Skin.

**Aspiration hazard** May be harmful if swallowed and enters airways. Risk of serious damage to the lungs (by aspiration).

**Acute Toxicity** 0 % of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document .

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

Toxic to aquatic life with long lasting effects

0 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
ACETONE 67-64-1		4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L LC50 8300: 96 h Lepomis macrochirus mg/L LC50 6210 - 8120: 96 h Pimephales promelas mg/L LC50 static	12600 - 12700: 48 h Daphnia magna mg/L EC50 10294 - 17704: 48 h Daphnia magna mg/L EC50 Static

METHYL ACETATE 79-20-9	120: 72 h <i>Desmodesmus subspicatus</i> mg/L EC50	295 - 348: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 250 - 350: 96 h <i>Brachydanio rerio</i> mg/L LC50 static	1026.7: 48 h <i>Daphnia magna</i> mg/L EC50
---------------------------	--	--	---

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

Component	log Pow
ACETONE 67-64-1	-0.24
METHYL ACETATE 79-20-9	0.18

**Other Adverse Effects**

No information available

**13. DISPOSAL CONSIDERATIONS****Waste treatment methods****Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

Component	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
ACETONE 67-64-1		Included in waste stream: F039		U002

Component	CAWAST
ACETONE 67-64-1	Ignitable
METHYL ACETATE 79-20-9	Toxic Ignitable

**14. TRANSPORT INFORMATION****DOT**

UN/ID no. 1263  
 Proper Shipping Name Paint related material  
 Hazard Class 3  
 Subsidiary Hazard Class II  
 Emergency Response Guide Number 128

**IATA**

UN/ID no. 1263  
 Proper Shipping Name Paint related material  
 Hazard Class 3  
 Packing Group II  
 ERG Code 128

**Additional information**

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

**15. REGULATORY INFORMATION**

**International Inventories**

<b>TSCA</b>	Complies
<b>DSL/NDSL</b>	Complies
<b>EINECS/ELINCS</b>	Complies
<b>ENCS</b>	Complies
<b>IECSC</b>	Complies
<b>KECL</b>	Complies
<b>PICCS</b>	Complies
<b>AICS</b>	Complies

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**IECSC** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

**United States of America**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

**SARA 311/312 Hazardous Categorization**

<b>Acute Health Hazard</b>	Yes
<b>Chronic Health Hazard</b>	Yes
<b>Fire Hazard</b>	Yes
<b>Sudden Release of Pressure Hazard</b>	No
<b>Reactive Hazard</b>	No

**CERCLA**

Component	Hazardous Substances RQs	CERCLA EHS RQs	RQ
ACETONE 67-64-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

**United States of America**

**California Prop. 65**

None of the ingredients are listed with California Proposition 65.

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Component	New Jersey	Massachusetts	Pennsylvania
ACETONE 67-64-1	X	X	X
METHYL ACETATE 79-20-9	X	X	X


**16. OTHER INFORMATION**

<b>NFPA</b>	Health 2	Flammability 3	Instability 0	Physical hazard *
<b>HMIS (Hazardous Material Information System)</b>	Health 2*	Flammability 3	Reactivity 0	

**Prepared By** Tnemec Regulatory Dept: 816-474-3400  
**Revision Date** 28-Jul-2015  
**Revision Summary**  
9 4 5 7 10 8 11 14 13 15

**Disclaimer**  
For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.  
To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**



# Safety Data Sheet

Issue Date 27-Jul-2015

Revision Date 27-Jul-2015

Revision Number 4

## 1. IDENTIFICATION

### Product identifier

Product Code F041-0075  
Product Name THINNER CLEAR

### Other means of identification

Common Name NO. 75 THINNER  
UN/ID no. 1263

### Recommended use of the chemical and restrictions on use

Recommended Use industrial paint.  
Uses advised against Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

**Manufacturer Address**  
Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372

**Distributor**  
Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203  
Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

Company Phone Number Tnemec Regulatory Dept: 816-474-3400  
24 Hour Emergency Phone Number 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Acute toxicity - Dermal	Category 4
Acute toxicity - Inhalation (Vapors)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable Liquids	Category 2

### Label elements

#### EMERGENCY OVERVIEW

Danger

**Hazard statements**

Harmful if swallowed  
Harmful in contact with skin  
Harmful if inhaled  
Causes skin irritation  
Causes serious eye damage  
Suspected of causing cancer  
May cause respiratory irritation. May cause drowsiness or dizziness  
May cause damage to organs through prolonged or repeated exposure  
May be fatal if swallowed and enters airways  
Highly flammable liquid and vapor

**Appearance** opaque**Physical state** liquid**Odor** aromatic**Precautionary Statements****Prevention**

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Use personal protective equipment as required  
Wash face, hands and any exposed skin thoroughly after handling  
Do not eat, drink or smoke when using this product  
Use only outdoors or in a well-ventilated area  
Do not breathe dust/fume/gas/mist/vapors/spray  
Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
Keep container tightly closed  
Ground/bond container and receiving equipment  
Use explosion-proof electrical/ventilating/lighting/mixing/equipment  
Use only non-sparking tools  
Take precautionary measures against static discharge  
Keep cool

**Response**

IF exposed or concerned: Get medical advice/attention  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
Immediately call a POISON CENTER or doctor/physician  
Call a POISON CENTER or doctor/physician if you feel unwell  
If skin irritation occurs: Get medical advice/attention  
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
Wash contaminated clothing before reuse  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
Rinse mouth  
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
Do NOT induce vomiting  
In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store locked up  
Store in a well-ventilated place. Keep container tightly closed  
Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant



**Hazards not otherwise classified (HNOC)****Other information**

Toxic to aquatic life with long lasting effects

SEE SAFETY DATA SHEET

Acute Toxicity

0 % of the mixture consists of ingredient(s) of unknown toxicity.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS-No	Weight-%
Trade secret	-	30 - 60%
XYLENE	1330-20-7	30 - 60%
N-BUTANOL (SKIN)	71-36-3	10 - 30%
ETHYL BENZENE	100-41-4	1 - 10%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

**4. FIRST AID MEASURES****Description of first aid measures**

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
<b>Inhalation</b>	Remove to fresh air. Oxygen or artificial respiration if needed.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

**Most important symptoms and effects, both acute and delayed**

**Notes to physician** Treat symptomatically.

**5. FIRE-FIGHTING MEASURES****Suitable extinguishing media**

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Water.

**Specific hazards arising from the chemical**

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

**Protective equipment and precautions for firefighters**

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

### Environmental Precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

### Methods and material for containment and cleaning up

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

### Conditions for safe storage, including any incompatibilities

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

**Incompatible products** Strong oxidizing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
Trade secret	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m <sup>3</sup>	800 ppm
XYLENE 1330-20-7	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 150 ppm STEL: 655 mg/m <sup>3</sup>	
N-BUTANOL (SKIN) 71-36-3	TWA: 20 ppm	Skin Ceiling: 50 ppm Ceiling: 150 mg/m <sup>3</sup> TWA: 100 ppm TWA: 300 mg/m <sup>3</sup>	1400 ppm

ETHYL BENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>	800 ppm
---------------------------	-------------	--	---------

**Appropriate engineering controls****Engineering measures**

Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV).

Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.

**Skin and body protection**

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection**

Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations**

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	aromatic
<b>Appearance</b>	opaque	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		

**Property****Values****Remarks**

<b>pH</b>		No data available
<b>Melting point / freezing point</b>		No data available
<b>Boiling point / boiling range</b>	116 °C / 241.0 °F	
<b>Flash point</b>	26 °C / 78.0 °F	
<b>Evaporation rate</b>		Pensky Martens - Closed Cup
<b>Flammability (solid, gas)</b>		No data available
<b>Flammability Limit in Air</b>		Not applicable
<b>Upper flammability limit</b>	N/A	No data available
<b>Lower flammability limit</b>	1.0	
<b>Vapor pressure</b>		No data available
<b>Vapor density</b>		No data available
<b>Specific gravity</b>	.83749	g/cm <sup>3</sup>
<b>Water solubility</b>	Insoluble in cold water	
<b>Solubility in other solvents</b>		No data available
<b>Partition coefficient: n-octanol/water</b>		No data available
<b>Autoignition temperature</b>		No data available
<b>Decomposition temperature</b>		No data available
<b>Kinematic viscosity</b>		No data available
<b>Dynamic viscosity</b>		No data available

**Other Information**

<b>Density</b>	6.96920 lbs/gal
----------------	-----------------

**Volatile organic compounds (VOC) content** 6.969 lbs/gal  
**Total volatiles weight percent** 100.0000 %  
**Total volatiles volume percent** 100.0000 %

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Possibility of hazardous reactions

None under normal processing.

### Conditions to avoid

Heat, flames and sparks.

### Incompatible materials

Strong oxidizing agents

### Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

## 11. TOXICOLOGICAL INFORMATION

### Information on Likely Routes of Exposure

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye contact</b>	Causes serious eye damage.
<b>Skin contact</b>	CAUSES SKIN IRRITATION.
<b>Ingestion</b>	Harmful if swallowed. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Trade secret	= 1600 mg/kg ( Rat ) = 1670 mg/kg ( Rat )	= 12.6 mL/kg ( Rabbit ) = 12600 µL/kg ( Rabbit )	> 2000 ppm ( Rat ) 4 h
XYLENE 1330-20-7	= 3500 mg/kg ( Rat )	> 1700 mg/kg ( Rabbit ) > 4350 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h = 5000 ppm ( Rat ) 4 h
N-BUTANOL (SKIN) 71-36-3	= 700 mg/kg ( Rat ) = 790 mg/kg ( Rat )	= 3402 mg/kg ( Rabbit ) = 3400 mg/kg ( Rabbit )	> 8000 ppm ( Rat ) 4 h
ETHYL BENZENE 100-41-4	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.2 mg/L ( Rat ) 4 h

### Information on toxicological effects

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Eye Damage.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization** No information available.

**Mutagenicity** No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	ACGIH	IARC	NTP	OSHA
XYLENE 1330-20-7		Group 3		

ETHYL BENZENE 100-41-4	A3	Group 2B	X
---------------------------	----	----------	---

<b>Reproductive effects</b>	No information available.
<b>STOT - single exposure</b>	Skin, Eyes, Central Nervous System (CNS)
<b>STOT - repeated exposure</b>	Causes damage to organs through prolonged or repeated exposure
<b>Target organ effects</b>	blood, Central nervous system, Gastrointestinal tract, Eyes, kidney, liver, respiratory system, Skin, Peripheral Nervous System (PNS).
<b>Aspiration hazard</b>	Risk of serious damage to the lungs (by aspiration).
<b>Acute Toxicity</b>	0 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Toxic to aquatic life with long lasting effects

0 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
Trade secret		126 - 137: 96 h Pimephales promelas mg/L LC50 flow-through	
XYLENE 1330-20-7		LC50= 13.4 mg/L Pimephales promelas 96 h LC50 2.661 - 4.093 mg/L Oncorhynchus mykiss 96 h LC50 13.5 - 17.3 mg/L Oncorhynchus mykiss 96 h LC50 13.1 - 16.5 mg/L Lepomis macrochirus 96 h LC50= 19 mg/L Lepomis macrochirus 96 h LC50 7.711 - 9.591 mg/L Lepomis macrochirus 96 h LC50 23.53 - 29.97 mg/L Pimephales promelas 96 h LC50= 780 mg/L Cyprinus carpio 96 h LC50> 780 mg/L Cyprinus carpio 96 h LC50 30.26 - 40.75 mg/L Poecilia reticulata 96 h	EC50 = 3.82 mg/L 48 h LC50 = 0.6 mg/L 48 h
N-BUTANOL (SKIN) 71-36-3	500: 96 h Desmodesmus subspicatus mg/L EC50 500: 72 h Desmodesmus subspicatus mg/L EC50	1740: 96 h Pimephales promelas mg/L LC50 flow-through 1910000: 96 h Pimephales promelas µg/L LC50 static 100000 - 500000: 96 h Lepomis macrochirus µg/L LC50 static 1730 - 1910: 96 h Pimephales promelas mg/L LC50 static	1897 - 2072: 48 h Daphnia magna mg/L EC50 Static 1983: 48 h Daphnia magna mg/L EC50
ETHYL BENZENE 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 32: 96 h Lepomis macrochirus mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 9.6: 96 h Poecilia reticulata mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static	1.8 - 2.4: 48 h Daphnia magna mg/L EC50

### Persistence and degradability

No information available.

### Bioaccumulation

No information available.

### Mobility in Environmental Media

Component	log Pow
Trade secret	1.98

XYLENE 1330-20-7	2.77
N-BUTANOL (SKIN) 71-36-3	0.785
ETHYL BENZENE 100-41-4	3.118

**Other Adverse Effects** No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal Methods** Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Component	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
XYLENE 1330-20-7		Included in waste stream: F039		U239
N-BUTANOL (SKIN) 71-36-3		Included in waste stream: F039		U031
ETHYL BENZENE 100-41-4		Included in waste stream: F039		

Component	CAWAST
XYLENE 1330-20-7	Toxic Ignitable
N-BUTANOL (SKIN) 71-36-3	Toxic
ETHYL BENZENE 100-41-4	Toxic Ignitable

**14. TRANSPORT INFORMATION**

**DOT**

UN/ID no. 1263  
 Proper Shipping Name Paint related material  
 Hazard Class 3  
 Packing Group III  
 Emergency Response Guide Number 128

**IATA**

UN/ID no. 1263  
 Proper Shipping Name Paint related material  
 Hazard Class 3  
 Packing Group III  
 ERG Code 366

**Additional information** Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

**15. REGULATORY INFORMATION**

**International Inventories**

TSCA Complies  
 DSL/NDSL Complies

<b>EINECS/ELINCS</b>	Complies
<b>ENCS</b>	Complies
<b>IECSC</b>	Complies
<b>KECL</b>	Complies
<b>PICCS</b>	Complies
<b>AICS</b>	Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List  
 EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances  
 ENCS - Japan Existing and New Chemical Substances  
 IECSC - China Inventory of Existing Chemical Substances  
 KECL - Korean Existing and Evaluated Chemical Substances  
 PICCS - Philippines Inventory of Chemicals and Chemical Substances  
 AICS - Australian Inventory of Chemical Substances

**The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):**

<b>Component</b>	<b>HAPS Data</b>
XYLENE	
ETHYL BENZENE	

**United States of America**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

Component	SARA 313 - Threshold Values
XYLENE - 1330-20-7	1.0
N-BUTANOL (SKIN) - 71-36-3	1.0
ETHYL BENZENE - 100-41-4	0.1

**SARA 311/312 Hazardous**

**Categorization**

<b>Acute Health Hazard</b>	Yes
<b>Chronic Health Hazard</b>	Yes
<b>Fire Hazard</b>	Yes
<b>Sudden Release of Pressure Hazard</b>	No
<b>Reactive Hazard</b>	No

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE 1330-20-7	100 lb			X
ETHYL BENZENE 100-41-4	1000 lb	X	X	X

**CERCLA**

Component	Hazardous Substances RQs	CERCLA EHS RQs	RQ
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
N-BUTANOL (SKIN) 71-36-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
ETHYL BENZENE 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

**United States of America**

**California Prop. 65**

WARNING! This product contains a chemical known in the State of California to cause cancer

Component	California Prop. 65
ETHYL BENZENE - 100-41-4	Carcinogen

**California SCAQMD Rule 443**  
 Contains Photochemically Reactive Solvent

**State Right-to-Know**

Component	New Jersey	Massachusetts	Pennsylvania
Trade secret	X	X	X
XYLENE 1330-20-7	X	X	X
N-BUTANOL (SKIN) 71-36-3	X	X	X
ETHYL BENZENE 100-41-4	X	X	X

**16. OTHER INFORMATION**

<b>NFPA</b>	Health 2	Flammability 3	Instability 1	Physical hazard *
<b>HMIS (Hazardous Material Information System)</b>	Health 2*	Flammability 3	Reactivity 1	

**Prepared By** Tnemec Regulatory Dept: 816-474-3400  
**Revision Date** 27-Jul-2015  
**Revision Summary**  
 9 4 5 7 10 8 11 14

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**





# Safety Data Sheet

Issue Date 16-Jul-2015

Revision Date 16-Jul-2015

Revision Number 5

## 1. IDENTIFICATION

### Product identifier

**Product Code** F041-0078  
**Product Name** THINNER GRAY

### Other means of identification

**Common Name** NO. 78 THINNER  
**UN/ID no.** 1263

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

**Manufacturer Address** Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372  
**Distributor** Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203 Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 2
Flammable Liquids	Category 2

### Label elements

#### **EMERGENCY OVERVIEW**

#### **Danger**

#### **Hazard statements**

Harmful if swallowed  
Causes skin irritation  
Causes serious eye irritation  
May cause respiratory irritation. May cause drowsiness or dizziness  
May cause damage to organs through prolonged or repeated exposure  
May be harmful if swallowed and enters airways  
Highly flammable liquid and vapor

**Appearance** clear**Physical state** liquid**Odor** aromatic**Precautionary Statements****Prevention**

Wash face, hands and any exposed skin thoroughly after handling  
 Do not eat, drink or smoke when using this product  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Use only outdoors or in a well-ventilated area  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Keep cool

**Response**

Get medical advice/attention if you feel unwell  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 If skin irritation occurs: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Call a POISON CENTER or doctor/physician if you feel unwell  
 Rinse mouth  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do NOT induce vomiting  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store locked up  
 Store in a well-ventilated place. Keep container tightly closed  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

SEE SAFETY DATA SHEET

Acute Toxicity

48.55031999 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight-%
tert-BUTYL ACETATE	540-88-5	30 - 60%
P-CHLOROBENZOTRIFLUORIDE	98-56-6	30 - 60%
METHYL N-AMYL KETONE	110-43-0	1 - 10%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

##### Description of first aid measures

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water. Consult a physician if necessary.
<b>Inhalation</b>	Remove to fresh air. If not breathing, give artificial respiration. Consult a physician.
<b>Ingestion</b>	Aspiration hazard. Drink 1 or 2 glasses of water. Do not induce vomiting without medical advice. Consult a physician. Never give anything by mouth to an unconscious person.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

##### Most important symptoms and effects, both acute and delayed

**Notes to physician** Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

alcohol-resistant foam. Carbon dioxide. Dry chemical.

**Unsuitable extinguishing media** Water.

##### Specific hazards arising from the chemical

FLAMMABLE Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

##### Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

#### 6. ACCIDENTAL RELEASE MEASURES

##### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition. Pay attention to flashback. Ensure adequate ventilation.

##### Environmental Precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

##### Methods and material for containment and cleaning up

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Close container after each use. Avoid contact with eyes, skin and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Do not burn, or use a cutting torch on, the empty drum. Wear personal protective equipment. Do not breathe vapours or spray mist.

### Conditions for safe storage, including any incompatibilities

**Storage** Keep away from heat, sparks and flame. Use only in an area containing flame proof equipment. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation.

**Incompatible products** Strong oxidizing agents. Incompatible with strong acids and bases. Alkalis.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
tert-BUTYL ACETATE 540-88-5	TWA: 200 ppm	TWA: 200 ppm TWA: 950 mg/m <sup>3</sup>	1500 ppm
P-CHLOROBENZOTRIFLUORIDE 98-56-6	TWA: 2.5 mg/m <sup>3</sup>	-	
METHYL N-AMYL KETONE 110-43-0	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m <sup>3</sup>	800 ppm

### Appropriate engineering controls

**Engineering measures** Ensure adequate ventilation, especially in confined areas. Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Use chemical resistant splash type goggles.

**Skin and body protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection** Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice.  
Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	liquid	<b>Odor</b>	aromatic
<b>Appearance</b>	clear	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
<b>pH</b>		No data available
<b>Melting point / freezing point</b>		No data available
<b>Boiling point / boiling range</b>	98 °C / 208 °F	
<b>Flash point</b>	16 °C / 60 °F	Pensky Martens - Closed Cup
<b>Evaporation rate</b>		No data available
<b>Flammability (solid, gas)</b>		Not applicable
<b>Flammability Limit in Air</b>		No data available
<b>Upper flammability limit</b>	N/A	
<b>Lower flammability limit</b>	1.1	
<b>Vapor pressure</b>		No data available
<b>Vapor density</b>		No data available
<b>Specific gravity</b>	1.01718	g/cm3
<b>Water solubility</b>	Insoluble in cold water	
<b>Solubility in other solvents</b>		No data available
<b>Partition coefficient: n-octanol/water</b>		No data available
<b>Autoignition temperature</b>		No data available
<b>Decomposition temperature</b>		No data available
<b>Kinematic viscosity</b>		No data available
<b>Dynamic viscosity</b>		No data available

### Other Information

<b>Density</b>	8.46449 lbs/gal
<b>Volatile organic compounds (VOC) content</b>	4.19929 lbs/gal
<b>Total volatiles weight percent</b>	93.71 %
<b>Total volatiles volume percent</b>	93.13 %

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Possibility of hazardous reactions

None under normal processing.

### Conditions to avoid

Heat, flames and sparks.

### Incompatible materials

Strong oxidizing agents, Incompatible with strong acids and bases, Alkalis

### Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

## 11. TOXICOLOGICAL INFORMATION

### Information on Likely Routes of Exposure

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye contact</b>	Severely irritating to eyes.
<b>Skin contact</b>	Irritating to skin.
<b>Ingestion</b>	May be harmful if swallowed and enters airways. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
tert-BUTYL ACETATE 540-88-5	= 4100 mg/kg ( Rat )	> 2 g/kg ( Rabbit )	> 2230 mg/m <sup>3</sup> ( Rat ) 4 h
P-CHLOROBENZOTRIFLUORIDE 98-56-6	= 13 g/kg ( Rat )	> 2 mL/kg ( Rabbit )	= 33 mg/L ( Rat ) 4 h
METHYL N-AMYL KETONE 110-43-0	= 1600 mg/kg ( Rat ) = 1670 mg/kg ( Rat )	= 12.6 mL/kg ( Rabbit ) = 12600 µL/kg ( Rabbit )	> 2000 ppm ( Rat ) 4 h

### Information on toxicological effects

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin disorders.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization** No information available.  
**Mutagenicity** No information available.  
**Carcinogenicity** There are no known carcinogenic chemicals in this product.  
**Reproductive effects** No information available.  
**STOT - single exposure** Skin, Eyes, Central Nervous System (CNS)  
**STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure  
**Target organ effects** Central nervous system, Eyes, Peripheral Nervous System (PNS), respiratory system, Skin, liver, kidney.  
**Aspiration hazard** Risk of serious damage to the lungs (by aspiration).  
**Acute Toxicity** 48.55031999 % of the mixture consists of ingredient(s) of unknown toxicity.  
**The following values are calculated based on chapter 3.1 of the GHS document .**

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Toxic to aquatic life with long lasting effects

42.74111 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
tert-BUTYL ACETATE 540-88-5		296 - 362: 96 h Pimephales promelas mg/L LC50 flow-through	
P-CHLOROBENZOTRIFLUORIDE 98-56-6		11.5 - 15.8: 48 h Lepomis macrochirus mg/L LC50 static	3.68: 48 h Daphnia magna mg/L EC50
METHYL N-AMYL KETONE 110-43-0		126 - 137: 96 h Pimephales promelas mg/L LC50 flow-through	

### Persistence and degradability

No information available.

### Bioaccumulation

No information available.

**Mobility in Environmental Media**

Component	log Pow
tert-BUTYL ACETATE 540-88-5	1.38
P-CHLOROBENZOTRIFLUORIDE 98-56-6	3.7
METHYL N-AMYL KETONE 110-43-0	1.98

**Other Adverse Effects** No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal Methods** Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

**14. TRANSPORT INFORMATION**

**DOT**

UN/ID no. 1263  
 Proper Shipping Name Paint related material  
 Hazard Class 3  
 Packing Group II  
 Emergency Response Guide Number 128

**IATA**

UN/ID no. 1263  
 Proper Shipping Name Paint related material  
 Hazard Class 3  
 Packing Group II  
 ERG Code 364

**Additional information** Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

**15. REGULATORY INFORMATION**

**International Inventories**

TSCA Complies  
 DSL/NDSL Complies  
 EINECS/ELINCS Complies  
 ENCS Does not comply  
 IECSC Complies  
 KECL Does not comply  
 PICCS Does not comply  
 AICS Does not comply

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**IECSC** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

**United States of America**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

**SARA 311/312 Hazardous Categorization**

**Acute Health Hazard** Yes  
**Chronic Health Hazard** No Yes  
**Fire Hazard** Yes  
**Sudden Release of Pressure Hazard** No  
**Reactive Hazard** No

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
tert-BUTYL ACETATE 540-88-5				X

**CERCLA**

Component	Hazardous Substances RQs	CERCLA EHS RQs	RQ
tert-BUTYL ACETATE 540-88-5	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

**United States of America**

**California Prop. 65**

None of the ingredients are listed with California Proposition 65.

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Component	New Jersey	Massachusetts	Pennsylvania
tert-BUTYL ACETATE 540-88-5	X	X	X
P-CHLOROBENZOTRIFLUORIDE 98-56-6	X		X
METHYL N-AMYL KETONE 110-43-0	X	X	X

**16. OTHER INFORMATION**

**NFPA** Health 2 Flammability 3 Instability 1 Physical hazard \*  
**HMIS (Hazardous Material Information System)** Health 2\* Flammability 3 Reactivity 1

Prepared By Tnemec Regulatory Dept: 816-474-3400  
 Revision Date 16-Jul-2015  
 Revision Summary  
 9 4 5 7 10 8 11 14 15




**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**



# Safety Data Sheet

Issue Date 02-Jun-2017

Revision Date 02-Jun-2017

Revision Number 3

## 1. IDENTIFICATION

### Product identifier

**Product Code** F041-0080  
**Product Name** NO. 80 THINNER

### Other means of identification

**Common Name** NO. 80 THINNER  
**UN/ID no.** 1263  
**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

**Manufacturer Address** Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372 816-474-3400  
**Distributor** Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

### OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Aspiration toxicity	Category 1
Flammable Liquids	Category 2

### Label elements

## EMERGENCY OVERVIEW

### **Danger**

### **Hazard statements**

Causes skin irritation  
Causes serious eye irritation  
May be fatal if swallowed and enters airways  
Highly flammable liquid and vapor

**Appearance** clear**Physical state** liquid**Odor** Strong aromatic**Precautionary Statements****Prevention**

Wash face, hands and any exposed skin thoroughly after handling  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment

**Response**

Get medical advice/attention if you feel unwell  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 If skin irritation occurs: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do NOT induce vomiting  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store locked up  
 Store in a well-ventilated place. Keep cool  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

May be harmful in contact with skin  
 Toxic to aquatic life with long lasting effects  
 SEE SAFETY DATA SHEET

Acute Toxicity

3 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
ALIPHATIC PETROLEUM DISTILATES	-	30 - <60%
PETROLEUM SOLVENT (NAPHTHA)	64742-95-6	10 - <30%
TRIMETHYLBENZENES	25551-13-7	10 - <30%
1,2,4-TRIMETHYLBENZENE	95-63-6	10 - <30%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

**Description of first aid measures**

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	Aspiration hazard. If swallowed, do not induce vomiting. Get medical attention immediately. Never give anything by mouth to an unconscious person.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

**Most important symptoms and effects, both acute and delayed**

<b>Notes to physician</b>	Treat symptomatically.
---------------------------	------------------------

**5. FIRE-FIGHTING MEASURES****Suitable extinguishing media**

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

**Specific hazards arising from the chemical**

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon dioxide.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Use personal protective equipment. Avoid contact with eyes, skin and clothing. Ensure adequate ventilation. Remove all sources of ignition.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated

absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

#### Handling

Wear personal protective equipment. Avoid contact with eyes, skin and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not ingest. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

### Conditions for safe storage, including any incompatibilities

#### Storage

Keep containers tightly closed in a cool, well-ventilated place. Keep out of the reach of children.

#### Incompatible products

Incompatible with oxidizing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
TRIMETHYLBENZENES 25551-13-7	TWA: 25 ppm	TWA: 25 ppm TWA: 125 mg/m <sup>3</sup>	

### Appropriate engineering controls

#### Engineering measures

Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Chemical goggles or safety glasses with side-shields.

#### Skin and body protection

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

#### Respiratory protection

Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

#### General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Physical state  
Appearance  
Color

liquid  
clear  
No information available

Odor  
Odor threshold

Strong aromatic  
No information available

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
pH		No data available
Melting point / freezing point	No data available	No data available
Boiling point / boiling range		No information available
Flash point	18.33 °C / 65.00 °F	Pensky Martens - Closed Cup
Evaporation rate		No data available
Flammability (solid, gas)	No data available	
Flammability Limit in Air		No data available
Upper flammability limit	8.0%	
Lower flammability limit	1.0	
Vapor pressure		No data available
Vapor density	4.1	No data available
Specific gravity	0.820774467	g/cm3
Water solubility	Insoluble in cold water	
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition temperature	No data available	No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity		No data available

**Other Information**

Density	6.83938 lbs/gal
Volatile organic compounds (VOC) content	6.839 lbs/gal
Total volatiles weight percent	100.00 %
Total volatiles volume percent	100.00 %
Bulk density	No information available

**10. STABILITY AND REACTIVITY****Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Incompatible with oxidizing agents

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

**11. TOXICOLOGICAL INFORMATION****Information on Likely Routes of Exposure**

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. Aspiration into lungs can produce severe lung damage.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Skin contact</b>	Irritating to skin.

**Ingestion**

Harmful if swallowed. Potential for aspiration if swallowed.

Chemical name	LD50 Oral	LD50 Dermal	LC50 Inhalation
ALIPHATIC PETROLEUM DISTILATES	-	= 3000 mg/kg ( Rabbit )	-
PETROLEUM SOLVENT (NAPTHA) 64742-95-6	= 8400 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	= 3400 ppm ( Rat ) 4 h
TRIMETHYLBENZENES 25551-13-7	= 8970 mg/kg ( Rat )	-	-
1,2,4-TRIMETHYLBENZENE 95-63-6	= 3280 mg/kg ( Rat )	> 3160 mg/kg ( Rabbit )	= 18 g/m <sup>3</sup> ( Rat ) 4 h

**Information on toxicological effects****Symptoms**

Simple asphyxiant. May cause suffocation by displacing the oxygen in the air. Exposure to oxygen-deficient atmosphere (<19.5%) may cause dizziness, drowsiness, nausea, vomiting, excess salivation, diminished mental alertness, loss of consciousness and death. Exposure to atmospheres containing 8-10% or less oxygen will bring about unconsciousness without warning and so quickly that the individuals cannot help or protect themselves. Lack of sufficient oxygen may cause serious injury or death. Irritating to eyes and skin.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure****Skin corrosion/irritation**

Irritating to skin.

**Eye damage/irritation**

Irritating to eyes.

**Sensitization**

No information available.

**Mutagenicity**

No information available.

**Carcinogenicity**

The table below indicates whether each agency has listed any ingredient as a carcinogen.

**Reproductive effects**

No information available.

**STOT - single exposure**

No information available

**STOT - repeated exposure**

Causes damage to organs through prolonged or repeated exposure

**Target organ effects**

Eyes, Skin, liver, kidney, blood, Central nervous system.

**Aspiration hazard**

Risk of serious damage to the lungs (by aspiration).

**Acute Toxicity**

3 % of the mixture consists of ingredient(s) of unknown toxicity.

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

Toxic to aquatic life with long lasting effects

3 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
ALIPHATIC PETROLEUM DISTILATES	4700: 72 h Pseudokirchneriella subcapitata mg/L EC50		
PETROLEUM SOLVENT (NAPTHA) 64742-95-6		9.22: 96 h Oncorhynchus mykiss mg/L LC50	6.14: 48 h Daphnia magna mg/L EC50
TRIMETHYLBENZENES 25551-13-7		7.72: 96 h Pimephales promelas mg/L LC50 flow-through	
1,2,4-TRIMETHYLBENZENE 95-63-6		7.19 - 8.28: 96 h Pimephales promelas mg/L LC50 flow-through	6.14: 48 h Daphnia magna mg/L EC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

Chemical name	log Pow
1,2,4-TRIMETHYLBENZENE 95-63-6	3.63

**Other Adverse Effects** No information available

### 13. DISPOSAL CONSIDERATIONS

**Waste treatment methods**

**Disposal Methods** It must undergo special treatment, e.g. at suitable disposal site, to comply with local regulations.

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

### 14. TRANSPORT INFORMATION

**DOT**

<b>UN/ID no.</b>	1263
<b>Proper Shipping Name</b>	Paint related material
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>Emergency Response Guide Number</b>	128

**Additional information** Call TNEMEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

### 15. REGULATORY INFORMATION

**International Inventories**

<b>TSCA</b>	Complies
<b>DSL/NDSL</b>	Does not comply
<b>EINECS/ELINCS</b>	Does not comply
<b>ENCS</b>	Does not comply
<b>IECSC</b>	Does not comply
<b>KECL</b>	Does not comply
<b>PICCS</b>	Does not comply
<b>AICS</b>	Does not comply

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical



or chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372:

Chemical name	SARA 313 - Threshold Values
1,2,4-TRIMETHYLBENZENE - 95-63-6	1.0

**SARA 311/312 Hazardous**

**Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**California Prop. 65**

This product does not contain any Proposition 65 chemicals

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Chemical name	New Jersey	Massachusetts	Pennsylvania
TRIMETHYLBENZENES 25551-13-7	X	X	X
1,2,4-TRIMETHYLBENZENE 95-63-6	X	X	X

**16. OTHER INFORMATION**

<b>NFPA</b>	Health 1	Flammability 3	Instability 0	Physical hazard -
<b>HMIS (Hazardous Material Information System)</b>	Health 1	Flammability 3	Reactivity 0	

**Prepared By** Tnemec Regulatory Dept: 816-474-3400  
**Revision Date** 02-Jun-2017


**Revision Summary**  
 1 9 4 5 6 7 10 8 11 14 15

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of SDS**



# Safety Data Sheet

Issue Date 10-May-2017

Revision Date 10-May-2017

Revision Number 2

## 1. IDENTIFICATION

### Product identifier

**Product Code** F041-0081  
**Product Name** NO. 81 THINNER

### Other means of identification

**Common Name** NO. 81 THINNER  
**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

**Manufacturer Address** Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372 816-474-3400  
**Distributor** Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 2
Aspiration toxicity	Category 1
Flammable Liquids	Category 3

### Label elements

#### EMERGENCY OVERVIEW

#### **Danger**

#### **Hazard statements**

Causes skin irritation  
Causes serious eye irritation  
Suspected of causing cancer  
May be fatal if swallowed and enters airways  
Flammable liquid and vapor

**Appearance** clear**Physical state** liquid**Odor** Solvent**Precautionary Statements****Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Wash face, hands and any exposed skin thoroughly after handling  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Use explosion-proof electrical/ventilating/lighting/metal/plastic/equipment

**Response**

IF exposed or concerned: Get medical advice/attention  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 If skin irritation occurs: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do NOT induce vomiting  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store locked up  
 Store in a well-ventilated place. Keep cool  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

May be harmful if swallowed  
 May be harmful in contact with skin  
 Toxic to aquatic life with long lasting effects

SEE SAFETY DATA SHEET

Acute Toxicity

0 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
PETROLEUM SOLVENT (NAPHTHA)	64742-95-6	30 - <60%
TRIMETHYLBENZENES	25551-13-7	30 - <60%
1,2,4-TRIMETHYLBENZENE	95-63-6	10 - <30%
SOLVENT NAPHTHA (PETROLEUM) HEAVY AROMATIC	64742-94-5	1 - <10%
XYLENE	1330-20-7	1 - <10%

CUMENE (SKIN)	98-82-8	1 - <10%
---------------	---------	----------

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

##### Description of first aid measures

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

##### Most important symptoms and effects, both acute and delayed

**Notes to physician** Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

##### Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides.

##### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

#### 6. ACCIDENTAL RELEASE MEASURES

##### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Use personal protective equipment. Avoid contact with eyes, skin and clothing. Ensure adequate ventilation. Remove all sources of ignition.

##### Environmental Precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

##### Methods and material for containment and cleaning up

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for

proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up**

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

**Precautions for safe handling****Handling**

Wear personal protective equipment. Avoid contact with eyes, skin and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not breathe vapours or spray mist. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

**Conditions for safe storage, including any incompatibilities****Storage**

Keep in a dry, cool and well-ventilated place. Keep out of the reach of children.

**Incompatible products**

Incompatible with oxidizing agents. Strong acids.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters****Exposure guidelines**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
TRIMETHYLBENZENES 25551-13-7	TWA: 25 ppm	TWA: 25 ppm TWA: 125 mg/m <sup>3</sup>	
XYLENE 1330-20-7	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 150 ppm STEL: 655 mg/m <sup>3</sup>	
CUMENE (SKIN) 98-82-8	TWA: 50 ppm	TWA: 50 ppm TWA: 245 mg/m <sup>3</sup> Skin	900 ppm

**Appropriate engineering controls****Engineering measures**

Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Safety glasses with side-shields If splashes are likely to occur, wear face-shield.

**Skin and body protection**

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection**

Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable

limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	liquid	<b>Odor</b>	Solvent
<b>Appearance</b>	clear	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
pH		No data available
Melting point / freezing point	No data available	
Boiling point / boiling range		No information available
Flash point	25.0 °C / 77 °F	Pensky Martens - Closed Cup
Evaporation rate		No data available
Flammability (solid, gas)	No data available	
Flammability Limit in Air		No data available
Upper flammability limit	NA	
Lower flammability limit	NA	
Vapor pressure		No data available
Vapor density		No data available
Specific gravity	0.873491224	g/cm3
Water solubility	Insoluble in cold water	
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition temperature	No data available	No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity		No data available

### Other Information

<b>Density</b>	7.29 lbs/gal
<b>Volatile organic compounds (VOC) content</b>	7.29 lbs/gal
<b>Total volatiles weight percent</b>	100 %
<b>Total volatiles volume percent</b>	100 %
<b>Bulk density</b>	No information available

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Possibility of hazardous reactions

None under normal processing.

### Conditions to avoid

Heat, flames and sparks.

### Incompatible materials

Incompatible with oxidizing agents, Strong acids

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides.

**11. TOXICOLOGICAL INFORMATION****Information on Likely Routes of Exposure**

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. Aspiration into lungs can produce severe lung damage.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Skin contact</b>	Irritating to skin.
<b>Ingestion</b>	Harmful if swallowed. Potential for aspiration if swallowed.

Chemical name	LD50 Oral	LD50 Dermal	LC50 Inhalation
PETROLEUM SOLVENT (NAPHTHA) 64742-95-6	= 8400 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	= 3400 ppm ( Rat ) 4 h
TRIMETHYLBENZENES 25551-13-7	= 8970 mg/kg ( Rat )	-	-
1,2,4-TRIMETHYLBENZENE 95-63-6	= 3280 mg/kg ( Rat )	> 3160 mg/kg ( Rabbit )	= 18 g/m <sup>3</sup> ( Rat ) 4 h
SOLVENT NAPHTHA (PETROLEUM) HEAVY AROMATIC 64742-94-5	> 5000 mg/kg ( Rat )	> 2 mL/kg ( Rabbit )	> 590 mg/m <sup>3</sup> ( Rat ) 4 h
XYLENE 1330-20-7	= 3500 mg/kg ( Rat )	> 4350 mg/kg ( Rabbit ) > 1700 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h = 5000 ppm ( Rat ) 4 h
CUMENE (SKIN) 98-82-8	= 1400 mg/kg ( Rat )	= 12300 µL/kg ( Rabbit )	= 39000 mg/m <sup>3</sup> ( Rat ) 4 h > 3577 ppm ( Rat ) 6 h

**Information on toxicological effects**

**Symptoms** Symptoms of overexposure are dizziness, headache, tiredness, nausea, unconsciousness, cessation of breathing. Irritating to eyes and skin.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Chronic Toxicity** NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid repeated exposure. May cause cancer.

**Sensitization** No information available.

**Mutagenicity** No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
PETROLEUM SOLVENT (NAPHTHA) 64742-95-6	.	-	-	
XYLENE 1330-20-7		Group 3	-	
CUMENE (SKIN) 98-82-8		Group 2B	Reasonably Anticipated	X

**Reproductive effects** No information available.

**STOT - single exposure** No information available

**STOT - repeated exposure** No information available

**Aspiration hazard** Based on product level data, this product does not meet the requirement to be classified as an aspiration hazard. However, this product contains an ingredient that may cause aspiration if swallowed.

**Acute Toxicity** 0 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Toxic to aquatic life with long lasting effects

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
PETROLEUM SOLVENT (NAPHTHA) 64742-95-6		9.22: 96 h Oncorhynchus mykiss mg/L LC50	6.14: 48 h Daphnia magna mg/L EC50
TRIMETHYLBENZENES 25551-13-7		7.72: 96 h Pimephales promelas mg/L LC50 flow-through	
1,2,4-TRIMETHYLBENZENE 95-63-6		7.19 - 8.28: 96 h Pimephales promelas mg/L LC50 flow-through	6.14: 48 h Daphnia magna mg/L EC50
SOLVENT NAPHTHA (PETROLEUM) HEAVY AROMATIC 64742-94-5	2.5: 72 h Skeletonema costatum mg/L EC50	1740: 96 h Lepomis macrochirus mg/L LC50 static 19: 96 h Pimephales promelas mg/L LC50 static 2.34: 96 h Oncorhynchus mykiss mg/L LC50 41: 96 h Pimephales promelas mg/L LC50 45: 96 h Pimephales promelas mg/L LC50 flow-through	0.95: 48 h Daphnia magna mg/L EC50
XYLENE 1330-20-7		LC50= 13.4 mg/L Pimephales promelas 96 h LC50 2.661 - 4.093 mg/L Oncorhynchus mykiss 96 h LC50 13.5 - 17.3 mg/L Oncorhynchus mykiss 96 h LC50 13.1 - 16.5 mg/L Lepomis macrochirus 96 h LC50= 19 mg/L Lepomis macrochirus 96 h LC50 7.711 - 9.591 mg/L Lepomis macrochirus 96 h LC50 23.53 - 29.97 mg/L Pimephales promelas 96 h LC50= 780 mg/L Cyprinus carpio 96 h LC50 > 780 mg/L Cyprinus carpio 96 h LC50 30.26 - 40.75 mg/L Poecilia reticulata 96 h	EC50 = 3.82 mg/L 48 h LC50 = 0.6 mg/L 48 h
CUMENE (SKIN) 98-82-8	2.6: 72 h Pseudokirchneriella subcapitata mg/L EC50	6.04 - 6.61: 96 h Pimephales promelas mg/L LC50 flow-through 2.7: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 4.8: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 5.1: 96 h Poecilia reticulata mg/L LC50 semi-static	7.9 - 14.1: 48 h Daphnia magna mg/L EC50 Static 0.6: 48 h Daphnia magna mg/L EC50

### Persistence and degradability

No information available.

### Bioaccumulation

No information available.

### Mobility in Environmental Media

Chemical name	log Pow
1,2,4-TRIMETHYLBENZENE 95-63-6	3.63
SOLVENT NAPHTHA (PETROLEUM) HEAVY AROMATIC 64742-94-5	2.9
XYLENE 1330-20-7	2.77
CUMENE (SKIN) 98-82-8	3.55

### Other Adverse Effects

No information available



### 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

**Disposal Methods** It must undergo special treatment, e.g. at suitable disposal site, to comply with local regulations.

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
CUMENE (SKIN) 98-82-8				U055
XYLENE 1330-20-7		Included in waste stream: F039		U239

Chemical name	CAWAST
XYLENE 1330-20-7	Toxic Ignitable
CUMENE (SKIN) 98-82-8	Toxic Ignitable

### 14. TRANSPORT INFORMATION

#### DOT

**Proper Shipping Name** Paint related material Not regulated

#### Additional information

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

### 15. REGULATORY INFORMATION

#### International Inventories

<b>TSCA</b>	Complies
<b>DSL/NDL</b>	Complies
<b>EINECS/ELINCS</b>	Complies
<b>ENCS</b>	Does not comply
<b>IECSC</b>	Complies
<b>KECL</b>	Complies
<b>PICCS</b>	Complies
<b>AICS</b>	Complies

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):**

Chemical name	HAPS Data
XYLENE	
CUMENE (SKIN)	

#### United States of America

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

Chemical name	SARA 313 - Threshold Values
1,2,4-TRIMETHYLBENZENE - 95-63-6	1.0
XYLENE - 1330-20-7	1.0
CUMENE (SKIN) - 98-82-8	1.0

**SARA 311/312 Hazardous Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE 1330-20-7	100 lb			X

**CERCLA**

Chemical name	Hazardous Substances RQs	CERCLA EHS RQs	RQ
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
CUMENE (SKIN) 98-82-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

**United States of America**

**California Prop. 65**

:This product can expose you to the following chemicals which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Chemical name	California Prop. 65
PETROLEUM SOLVENT (NAPHTHA) - 64742-95-6	.
CUMENE (SKIN) - 98-82-8	Carcinogen

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Chemical name	New Jersey	Massachusetts	Pennsylvania
TRIMETHYLBENZENES 25551-13-7	X	X	X
1,2,4-TRIMETHYLBENZENE 95-63-6	X	X	X
XYLENE 1330-20-7	X	X	X
CUMENE (SKIN) 98-82-8	X	X	X

**16. OTHER INFORMATION**

<b>NFPA</b>	Health 2	Flammability 2	Instability 0	Physical hazard *
<b>HMIS (Hazardous Material Information System)</b>	Health 2*	Flammability 2	Reactivity 0	

Prepared By  
Revision Date  
Revision Summary  
1 3 9 5 6 7 10 8 11 14 15

Tnemec Regulatory Dept: 816-474-3400  
10-May-2017

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of SDS**



# Safety Data Sheet

Issue Date 09-May-2017

Revision Date 09-May-2017

Revision Number 2

## 1. IDENTIFICATION

### Product identifier

**Product Code** F041-0082  
**Product Name** NO. 82 THINNER

### Other means of identification

**Common Name** NO. 82 THINNER  
**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

**Manufacturer Address** Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372 816-474-3400  
**Distributor** Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable Liquids

Category 3

### Label elements

#### EMERGENCY OVERVIEW

#### **WARNING**

Flammable liquid and vapor



**Appearance** clear

**Physical state** liquid

**Odor** Strong aromatic

#### **Precautionary Statements**

##### **Prevention**

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Use explosion-proof electrical/ventilating/lighting/./equipment  
 Wear protective gloves/protective clothing/eye protection/face protection

**Response**

Get medical advice/attention if you feel unwell  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 In case of fire: Use CO2, dry chemical, or foam for extinction

**Storage**

Store in a well-ventilated place. Keep cool  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

May be harmful in contact with skin

SEE SAFETY DATA SHEET

Acute Toxicity

0 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
PROPYLENE GLYCOL MONOMETHYL ETHER	108-65-6	60 - 100%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

**Description of first aid measures**

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately. Never give anything by mouth to an unconscious person.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

**Most important symptoms and effects, both acute and delayed**

**Notes to physician**                      Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

**Suitable extinguishing media**

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

**Specific hazards arising from the chemical**

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

**Protective equipment and precautions for firefighters**

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Ensure adequate ventilation. Use personal protective equipment. Avoid contact with eyes, skin and clothing. Remove all sources of ignition.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Handling** Handle in accordance with good industrial hygiene and safety practice. Wear personal protective equipment. Avoid contact with eyes, skin and clothing. Remove and wash contaminated clothing before re-use. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not breathe vapours or spray mist. Do not ingest. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

**Conditions for safe storage, including any incompatibilities**

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

**Incompatible products** Strong oxidizing agents. Acids.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters**

**Exposure guidelines****Appropriate engineering controls****Engineering measures**

Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Safety glasses with side-shields Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.

**Skin and body protection**

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection**

Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations**

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	Strong aromatic
<b>Appearance</b>	clear	<b>Odor threshold</b>	No information available
<b>Color</b>	Colorless		
<b><u>Property</u></b>	<b><u>Values</u></b>	<b><u>Remarks</u></b>	
<b>pH</b>		No data available	
<b>Melting point / freezing point</b>		No data available	
<b>Boiling point / boiling range</b>	139 °C / 283 °F		
<b>Flash point</b>	41 °C / 106 °F	Pensky Martens - Closed Cup	
<b>Evaporation rate</b>		No data available	
<b>Flammability (solid, gas)</b>	No data available	Not applicable	
<b>Flammability Limit in Air</b>		No data available	
<b>Upper flammability limit</b>	N/A		
<b>Lower flammability limit</b>	1.0		
<b>Vapor pressure</b>	3.8	mmHg @ 25C	
<b>Vapor density</b>	4.6		
<b>Specific gravity</b>	0.96797	g/cm3	
<b>Water solubility</b>	No data available		
<b>Solubility in other solvents</b>		No data available	
<b>Partition coefficient: n-octanol/water</b>		No data available	
<b>Autoignition temperature</b>		No data available	
<b>Decomposition temperature</b>		No data available	
<b>Kinematic viscosity</b>		No data available	
<b>Dynamic viscosity</b>		No data available	
<b><u>Other Information</u></b>			
<b>Density</b>	8.08 lbs/gal		
<b>Volatile organic compounds (VOC) content</b>	8.08 lbs/gal		
<b>Total volatiles weight percent</b>	100 %		
<b>Total volatiles volume percent</b>	100 %		

**Bulk density** No information available

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Possibility of hazardous reactions

None under normal processing.

### Conditions to avoid

Heat, flames and sparks.

### Incompatible materials

Strong oxidizing agents, Acids

### Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons.

## 11. TOXICOLOGICAL INFORMATION

### Information on Likely Routes of Exposure

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye contact</b>	May cause slight irritation.
<b>Skin contact</b>	May cause skin irritation and/or dermatitis.
<b>Ingestion</b>	Harmful if swallowed.

Chemical name	LD50 Oral	LD50 Dermal	LC50 Inhalation
PROPYLENE GLYCOL MONOMETHYL ETHER 108-65-6	= 8532 mg/kg ( Rat )	> 5 g/kg ( Rabbit )	-

### Information on toxicological effects

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritating to eyes and skin.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

<b>Chronic Toxicity</b>	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
<b>Sensitization</b>	No information available.
<b>Mutagenicity</b>	No information available.
<b>Carcinogenicity</b>	There are no known carcinogenic chemicals in this product.
<b>Reproductive effects</b>	No information available.
<b>STOT - single exposure</b>	Skin, Eyes, Respiratory system
<b>STOT - repeated exposure</b>	No information available
<b>Target organ effects</b>	Eyes, kidney, Lungs, Reproductive System.
<b>Aspiration hazard</b>	No information available.

**Acute Toxicity** 0 % of the mixture consists of ingredient(s) of unknown toxicity.  
**The following values are calculated based on chapter 3.1 of the GHS document .**



## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
PROPYLENE GLYCOL MONOMETHYL ETHER 108-65-6		161: 96 h Pimephales promelas mg/L LC50 static	500: 48 h Daphnia magna mg/L EC50

### Persistence and degradability

No information available.

### Bioaccumulation

No information available.

### Mobility in Environmental Media

Chemical name	log Pow
PROPYLENE GLYCOL MONOMETHYL ETHER 108-65-6	0.43

### Other Adverse Effects

No information available

## 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

#### **Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

#### **Contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. TRANSPORT INFORMATION

### DOT

**Proper Shipping Name** Paint related material Not regulated

**UN/ID no.** 3272

**Proper Shipping Name** Esters, n.o.s, (Propylene Glycol Monomethyl Ether Acetate)

**Hazard Class** 3

**Packing Group** III

**ERG Code** 366

### Additional information

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

## 15. REGULATORY INFORMATION

### International Inventories

**TSCA** Complies

**DSL/NDSL** Complies

**EINECS/ELINCS** Complies

**ENCS** Complies

IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List  
EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances  
ENCS - Japan Existing and New Chemical Substances  
IECSC - China Inventory of Existing Chemical Substances  
KECL - Korean Existing and Evaluated Chemical Substances  
PICCS - Philippines Inventory of Chemicals and Chemical Substances  
AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

**United States of America**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372.

**SARA 311/312 Hazardous**

**Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**CERCLA**

**United States of America**

**California Prop. 65**

None of the ingredients are listed with California Proposition 65.

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

**16. OTHER INFORMATION**

<b><u>NFPA</u></b>	Health 2	Flammability 2	Instability 0	Physical hazard *
<b><u>HMIS (Hazardous Material Information System)</u></b>	Health 2	Flammability 2	Reactivity 0	

**Prepared By** Tnemec Regulatory Dept: 816-474-3400  
**Revision Date** 09-May-2017

**Revision Summary**  
 9 4 5 7 10 8 11 14 6 15 1


**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained

herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of SDS**



# Safety Data Sheet

Issue Date 05-Jun-2017

Revision Date 05-Jun-2017

Revision Number 3

## 1. IDENTIFICATION

### Product identifier

**Product Code** F041-0083  
**Product Name** NO .83 THINNER

### Other means of identification

**Common Name** NO. 83 THINNER  
**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

**Manufacturer Address** Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372 816-474-3400  
**Distributor** Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Flammable Liquids	Category 4

### Label elements

#### EMERGENCY OVERVIEW

#### WARNING



**Appearance** clear

**Physical state** liquid

**Odor** Slight

#### **Precautionary Statements**

#### **Prevention**

Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep cool  
 Wash hands thoroughly after handling  
 Wear protective gloves/protective clothing/eye protection/face protection

**Response**

Get medical advice/attention if you feel unwell  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 IF ON SKIN: Wash with plenty of soap and water  
 Take off contaminated clothing and wash before reuse  
 If skin irritation occurs: Get medical advice/attention  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Keep away from children  
 Store in a well-ventilated place

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

May be harmful if swallowed  
 May be harmful in contact with skin  
 Harmful to aquatic life with long lasting effects  
 SEE SAFETY DATA SHEET  
 Acute Toxicity 0 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
DIMETHYL GLUTERATE	1119-40-0	60 - 100%
DIMETHYL SUCCINATE	106-65-0	10 - <30%
DIMETHYL ADIPATE	627-93-0	10 - <30%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

**Description of first aid measures**

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately. Never give anything by mouth to an unconscious person.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

**Most important symptoms and effects, both acute and delayed**

**Notes to physician** Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

### **Suitable extinguishing media**

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

### **Specific hazards arising from the chemical**

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides.

### **Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

### **Personal precautions, protective equipment and emergency procedures**

#### **Personal precautions**

Use personal protective equipment. Avoid contact with eyes, skin and clothing. Ensure adequate ventilation. Remove all sources of ignition.

#### **Environmental Precautions**

#### **Environmental precautions**

Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

### **Methods and material for containment and cleaning up**

#### **Methods for containment**

Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

#### **Methods for cleaning up**

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

### **Precautions for safe handling**

#### **Handling**

Wear personal protective equipment. Avoid contact with eyes, skin and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not breathe vapours or spray mist. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

### **Conditions for safe storage, including any incompatibilities**

#### **Storage**

Keep tightly closed in a dry and cool place. Keep out of the reach of children.

#### **Incompatible products**

No information available.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### **Exposure guidelines**

#### **Appropriate engineering controls**

#### **Engineering measures**

Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

#### **Individual protection measures, such as personal protective equipment**

#### **Eye/face protection**

Safety glasses with side-shields If splashes are likely to occur, wear face-shield.

#### **Skin and body protection**

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

#### **Respiratory protection**

Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

#### **General hygiene considerations**

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### **Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	Slight
<b>Appearance</b>	clear	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		

#### **Property**

#### **Values**

#### **Remarks**

<b>pH</b>	No data available	No data available
<b>Melting point / freezing point</b>	No data available	
<b>Boiling point / boiling range</b>		No information available
<b>Flash point</b>	96 °C / 205.00 °F	Pensky Martens - Closed Cup
<b>Evaporation rate</b>		No data available
<b>Flammability (solid, gas)</b>	No data available	
<b>Flammability Limit in Air</b>		No data available
<b>Upper flammability limit</b>	9%	
<b>Lower flammability limit</b>	1%	
<b>Vapor pressure</b>		No data available
<b>Vapor density</b>		No data available
<b>Specific gravity</b>	1.89168069	g/cm3
<b>Water solubility</b>	Insoluble in cold water	
<b>Solubility in other solvents</b>		No data available
<b>Partition coefficient: n-octanol/water</b>		No data available
<b>Autoignition temperature</b>	No data available	No data available
<b>Decomposition temperature</b>		No data available
<b>Kinematic viscosity</b>		No data available
<b>Dynamic viscosity</b>		No data available

#### **Other Information**

<b>Density</b>	9.09 lbs/gal
<b>Total volatiles weight percent</b>	100 %

Total volatiles volume percent 100 %  
Bulk density No information available

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Possibility of hazardous reactions

None under normal processing.

### Conditions to avoid

Heat, flames and sparks.

### Incompatible materials

No information available

### Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

### Information on Likely Routes of Exposure

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Skin contact</b>	May cause irritation.
<b>Ingestion</b>	May be harmful if swallowed.

Chemical name	LD50 Oral	LD50 Dermal	LC50 Inhalation
DIMETHYL GLUTERATE 1119-40-0	> 5000 mg/kg ( Rat )	> 5000 mg/kg ( Rabbit )	> 5.6 mg/L ( Rat ) 4 h
DIMETHYL SUCCINATE 106-65-0	> 5 g/kg ( Rat )	> 5 g/kg ( Rabbit )	-
DIMETHYL ADIPATE 627-93-0	> 5000 mg/kg ( Rat )	> 5000 mg/kg ( Rabbit )	-

### Information on toxicological effects

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritating to eyes and skin.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

<b>Skin corrosion/irritation</b>	Irritating to skin.
<b>Eye damage/irritation</b>	Irritating to eyes.
<b>Chronic Toxicity</b>	Avoid repeated exposure.
<b>Sensitization</b>	No information available.
<b>Mutagenicity</b>	No information available.
<b>Carcinogenicity</b>	Not classifiable as a human carcinogen.
<b>Reproductive effects</b>	No information available.
<b>STOT - single exposure</b>	No information available
<b>STOT - repeated exposure</b>	No information available
<b>Aspiration hazard</b>	No information available.



**Acute Toxicity** 0 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Harmful to aquatic life with long lasting effects

17 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
DIMETHYL GLUTERATE 1119-40-0		19.6 - 26.2: 96 h Pimephales promelas mg/L LC50 static	122.1 - 163.5: 48 h Daphnia magna mg/L EC50
DIMETHYL SUCCINATE 106-65-0		50 - 100: 96 h Brachydanio rerio mg/L LC50 static	

### Persistence and degradability

No information available.

### Bioaccumulation

No information available.

### Mobility in Environmental Media

Chemical name	log Pow
DIMETHYL SUCCINATE 106-65-0	0.19

### Other Adverse Effects

No information available

## 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

#### **Disposal Methods**

It must undergo special treatment, e.g. at suitable disposal site, to comply with local regulations.

#### **Contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. TRANSPORT INFORMATION

### DOT

#### **Proper Shipping Name**

PAINT & RELATED MATERIAL - Not regulated

### Additional information

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

## 15. REGULATORY INFORMATION

### International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies

**PICCS** Complies  
**AICS** Complies

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**IECSC** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

**SARA 311/312 Hazardous**

**Categorization**

<b>Acute Health Hazard</b>	Yes
<b>Chronic Health Hazard</b>	No
<b>Fire Hazard</b>	No
<b>Sudden Release of Pressure Hazard</b>	No
<b>Reactive Hazard</b>	No

**California Prop. 65**

This product does not contain any Proposition 65 chemicals

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

**16. OTHER INFORMATION**

<b>NFPA</b>	Health 2	Flammability 1	Instability 0	Physical hazard -
<b>HMIS (Hazardous Material Information System)</b>	Health 2	Flammability 1	Reactivity 0	


**Prepared By** Tnemec Regulatory Dept: 816-474-3400  
**Revision Date** 05-Jun-2017  
**Revision Summary**  
 1 9 5 6 7 10 8 11 14 15 4

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of SDS**



# Safety Data Sheet

Issue Date 02-Jun-2017

Revision Date 02-Jun-2017

Revision Number 3

## 1. IDENTIFICATION

### Product identifier

**Product Code** F041-0084  
**Product Name** NO. 84 THINNER

### Other means of identification

**Common Name** NO. 84 THINNER  
**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372 816-474-3400

#### **Distributor**

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

#### **Emergency telephone number**

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Inhalation (Vapors)	Category 3
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Carcinogenicity	Category 2
Aspiration toxicity	Category 1

### Label elements

## EMERGENCY OVERVIEW

### **Danger**

#### **Hazard statements**

Toxic if inhaled  
Causes skin irritation  
Causes serious eye irritation  
Suspected of causing cancer  
May be fatal if swallowed and enters airways

**Appearance** clear**Physical state** liquid**Odor** Strong aromatic**Precautionary Statements****Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Use only outdoors or in a well-ventilated area  
 Wash face, hands and any exposed skin thoroughly after handling

**Response**

IF exposed or concerned: Get medical advice/attention  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 IF ON SKIN: Wash with plenty of soap and water  
 If skin irritation occurs: Get medical advice/attention  
 Take off contaminated clothing and wash before reuse  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Call a POISON CENTER or doctor/physician  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do NOT induce vomiting

**Storage**

Store locked up  
 Store in a well-ventilated place. Keep container tightly closed  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

May be harmful if swallowed  
 May be harmful in contact with skin  
 Very toxic to aquatic life with long lasting effects  
 SEE SAFETY DATA SHEET  
 Acute Toxicity 0 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
SOLVENT NAPHTHA (PETROLEUM) HEAVY AROMATIC	64742-94-5	60 - 100%
NAPHTHALENE	91-20-3	1 - <10%
CUMENE (SKIN)	98-82-8	1 - <10%
1,3,5-TRIMETHYLBENZENE	108-67-8	1 - <10%
1,2,4-TRIMETHYLBENZENE	95-63-6	1 - <10%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

##### Description of first aid measures

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
<b>Inhalation</b>	Call a physician or poison control center immediately. Remove from exposure, lie down. Artificial respiration and/or oxygen may be necessary.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately. Never give anything by mouth to an unconscious person.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

##### Most important symptoms and effects, both acute and delayed

<b>Notes to physician</b>	Treat symptomatically.
---------------------------	------------------------

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

##### Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon dioxide.

##### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to cool unopened containers.

#### 6. ACCIDENTAL RELEASE MEASURES

##### Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing. Ensure adequate ventilation. Remove all sources of ignition. Keep people away from and upwind of spill/leak.
-----------------------------	---

##### Environmental Precautions

<b>Environmental precautions</b>	Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.
----------------------------------	---

##### Methods and material for containment and cleaning up

<b>Methods for containment</b>	Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer
--------------------------------	---

absorbent material to suitable containers for proper disposal.

**Methods for cleaning up**

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

**Precautions for safe handling****Handling**

Wear personal protective equipment. Avoid contact with eyes, skin and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not breathe vapours or spray mist. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

**Conditions for safe storage, including any incompatibilities****Storage**

Keep in a dry, cool and well-ventilated place. Keep out of the reach of children. Store locked up.

**Incompatible products**

No information available.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters****Exposure guidelines**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
NAPHTHALENE 91-20-3	TWA: 10 ppm Skin	TWA: 10 ppm TWA: 50 mg/m <sup>3</sup> STEL: 15 ppm STEL: 75 mg/m <sup>3</sup>	250 ppm
CUMENE (SKIN) 98-82-8	TWA: 50 ppm	TWA: 50 ppm TWA: 245 mg/m <sup>3</sup> Skin	900 ppm

**Appropriate engineering controls****Engineering measures**

Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Chemical goggles or safety glasses with side-shields. If splashes are likely to occur, wear face-shield.

**Skin and body protection**

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection**

Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice.  
Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	liquid	<b>Odor</b>	Strong aromatic
<b>Appearance</b>	clear	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
pH		No data available
Melting point / freezing point	No data available	
Boiling point / boiling range		No information available
Flash point	66 °C / 150.00 °F	Pensky Martens - Closed Cup
Evaporation rate		No data available
Flammability (solid, gas)	No data available	
Flammability Limit in Air		No data available
Upper flammability limit	6.5%	
Lower flammability limit	0.9%	
Vapor pressure		No data available
Vapor density		No data available
Specific gravity	0.896257113	g/cm3
Water solubility	Insoluble in cold water	
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition temperature	No data available	No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity		No data available

### Other Information

Density	7.47994 lbs/gal
Volatile organic compounds (VOC) content	7.480 lbs/gal
Total volatiles weight percent	100.00 %
Total volatiles volume percent	100.00 %
Bulk density	No information available

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Possibility of hazardous reactions

None under normal processing.

### Conditions to avoid

Heat, flames and sparks.

### Incompatible materials

No information available

### Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke).

Carbon monoxide. Unidentified organic and inorganic compounds. Carbon dioxide. Hydrocarbons.

## 11. TOXICOLOGICAL INFORMATION

### Information on Likely Routes of Exposure

<b>Inhalation</b>	Toxic by inhalation. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. Aspiration into lungs can produce severe lung damage.
<b>Eye contact</b>	May cause irritation.
<b>Skin contact</b>	May cause irritation.
<b>Ingestion</b>	May be harmful if swallowed. Potential for aspiration if swallowed.

Chemical name	LD50 Oral	LD50 Dermal	LC50 Inhalation
SOLVENT NAPHTHA (PETROLEUM) HEAVY AROMATIC 64742-94-5	> 5000 mg/kg ( Rat )	> 2 mL/kg ( Rabbit )	> 590 mg/m <sup>3</sup> ( Rat ) 4 h
NAPHTHALENE 91-20-3	= 1110 mg/kg ( Rat ) = 490 mg/kg ( Rat )	(> 20 g/kg ( Rabbit ) = 1120 mg/kg ( Rabbit )	> 340 mg/m <sup>3</sup> ( Rat ) 1 h
CUMENE (SKIN) 98-82-8	= 1400 mg/kg ( Rat )	= 12300 µL/kg ( Rabbit )	= 39000 mg/m <sup>3</sup> ( Rat ) 4 h > 3577 ppm ( Rat ) 6 h
1,3,5-TRIMETHYLBENZENE 108-67-8	= 5000 mg/kg ( Rat )	-	= 24 g/m <sup>3</sup> ( Rat ) 4 h
1,2,4-TRIMETHYLBENZENE 95-63-6	= 3280 mg/kg ( Rat )	> 3160 mg/kg ( Rabbit )	= 18 g/m <sup>3</sup> ( Rat ) 4 h

### Information on toxicological effects

**Symptoms** Symptoms of overexposure are dizziness, headache, tiredness, nausea, unconsciousness, cessation of breathing.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Chronic Toxicity** NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid repeated exposure.

**Sensitization** No information available.

**Mutagenicity** No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
NAPHTHALENE 91-20-3	A3	Group 2A Group 2B	Reasonably Anticipated	X
CUMENE (SKIN) 98-82-8		Group 2B	Reasonably Anticipated	X

**Reproductive effects** No information available.

**STOT - single exposure** No information available

**STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure

**Target organ effects** blood, Central nervous system, Eyes, kidney, liver.

**Aspiration hazard** Risk of serious damage to the lungs (by aspiration).

**Acute Toxicity** 0 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Toxic to aquatic life with long lasting effects

0 % of the mixture consists of components(s) of unknown hazards to the aquatic environment



Chemical name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
SOLVENT NAPHTHA (PETROLEUM) HEAVY AROMATIC 64742-94-5	2.5: 72 h Skeletonema costatum mg/L EC50	19: 96 h Pimephales promelas mg/L LC50 static 2.34: 96 h Oncorhynchus mykiss mg/L LC50 1740: 96 h Lepomis macrochirus mg/L LC50 static 45: 96 h Pimephales promelas mg/L LC50 flow-through 41: 96 h Pimephales promelas mg/L LC50	0.95: 48 h Daphnia magna mg/L EC50
NAPHTHALENE 91-20-3	0.4: 72 h Skeletonema costatum mg/L EC50	0.91 - 2.82: 96 h Oncorhynchus mykiss mg/L LC50 static 5.74 - 6.44: 96 h Pimephales promelas mg/L LC50 flow-through 1.6: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 1.99: 96 h Pimephales promelas mg/L LC50 static 31.0265: 96 h Lepomis macrochirus mg/L LC50 static	1.09 - 3.4: 48 h Daphnia magna mg/L EC50 Static 1.96: 48 h Daphnia magna mg/L EC50 Flow through 2.16: 48 h Daphnia magna mg/L LC50
CUMENE (SKIN) 98-82-8	2.6: 72 h Pseudokirchneriella subcapitata mg/L EC50	6.04 - 6.61: 96 h Pimephales promelas mg/L LC50 flow-through 2.7: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 4.8: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 5.1: 96 h Poecilia reticulata mg/L LC50 semi-static	7.9 - 14.1: 48 h Daphnia magna mg/L EC50 Static 0.6: 48 h Daphnia magna mg/L EC50
1,3,5-TRIMETHYLBENZENE 108-67-8		3.48: 96 h Pimephales promelas mg/L LC50	50: 24 h Daphnia magna mg/L EC50
1,2,4-TRIMETHYLBENZENE 95-63-6		7.19 - 8.28: 96 h Pimephales promelas mg/L LC50 flow-through	6.14: 48 h Daphnia magna mg/L EC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

Chemical name	log Pow
SOLVENT NAPHTHA (PETROLEUM) HEAVY AROMATIC 64742-94-5	2.9 - 6.1
NAPHTHALENE 91-20-3	3.3
CUMENE (SKIN) 98-82-8	3.55
1,2,4-TRIMETHYLBENZENE 95-63-6	3.63

**Other Adverse Effects**

No information available

**13. DISPOSAL CONSIDERATIONS****Waste treatment methods****Disposal Methods**

It must undergo special treatment, e.g. at suitable disposal site, to comply with local regulations.

**Contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
NAPHTHALENE 91-20-3	U165	Included in waste streams: F024, F025, F034, F039, K001, K035, K060, K087, K145		U165
CUMENE (SKIN)				U055



NAPTHALENE  
CUMENE (SKIN)

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

Chemical name	SARA 313 - Threshold Values
NAPTHALENE - 91-20-3	0.1
CUMENE (SKIN) - 98-82-8	1.0
1,2,4-TRIMETHYLBENZENE - 95-63-6	1.0

**SARA 311/312 Hazardous**

**Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
NAPTHALENE 91-20-3	100 lb	X	X	X

Chemical name	Hazardous Substances RQs	CERCLA EHS RQs	RQ
NAPTHALENE 91-20-3	100 lb 1 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ
CUMENE (SKIN) 98-82-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

**California Prop. 65**

:This product can expose you to the following chemicals which are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Chemical name	California Prop. 65
NAPTHALENE - 91-20-3	Carcinogen
CUMENE (SKIN) - 98-82-8	Carcinogen

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Chemical name	New Jersey	Massachusetts	Pennsylvania
NAPTHALENE 91-20-3	X	X	X
CUMENE (SKIN) 98-82-8	X	X	X
1,3,5-TRIMETHYLBENZENE 108-67-8		X	
1,2,4-TRIMETHYLBENZENE 95-63-6	X	X	X

**16. OTHER INFORMATION**

<b>NFPA</b>	Health 2	Flammability 2	Instability 0	Physical hazard *
<b>HMIS (Hazardous Material Information System)</b>	Health 2*	Flammability 2	Reactivity 0	

Prepared By Tnemec Regulatory Dept: 816-474-3400  
Revision Date 02-Jun-2017

**Revision Summary**


1 9 4 5 6 7 8 11 14 15 13

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of SDS**



# Safety Data Sheet

Issue Date 02-Jun-2017

Revision Date 02-Jun-2017

Revision Number 3

## 1. IDENTIFICATION

### Product identifier

**Product Code** F041-0085  
**Product Name** THINNER CLEAR

### Other means of identification

**Common Name** NO. 85 THINNER  
**UN/ID no.** 1090  
**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO  
64120-1372 816-474-3400

#### **Distributor**

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203,  
Boisbriand, Quebec Canada J7G 2T3

#### **Emergency telephone number**

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Flammable Liquids	Category 2

### Label elements

#### EMERGENCY OVERVIEW

**Danger**

#### **Hazard statements**

Causes skin irritation  
Causes serious eye irritation  
Highly flammable liquid and vapor



**Appearance** clear**Physical state** liquid**Odor** Strong Solvent**Precautionary Statements****Prevention**

Wash face, hands and any exposed skin thoroughly after handling  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment

**Response**

Get medical advice/attention if you feel unwell  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 If skin irritation occurs: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store in a well-ventilated place. Keep cool  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

May be harmful if swallowed and enters airways  
 Harmful to aquatic life with long lasting effects  
 SEE SAFETY DATA SHEET  
 Acute Toxicity

0 % of the mixture consists of ingredient(s) of unknown toxicity.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical name	CAS No	Weight-%
ACETONE	67-64-1	60 - 100%
PCBFT	98-56-6	10 - <30%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

**4. FIRST AID MEASURES****Description of first aid measures****General advice**

If symptoms persist, call a physician.

**Eye contact**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.

**Skin contact**

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.

**Inhalation**

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

**Ingestion** If swallowed, do not induce vomiting. Get medical attention immediately. Never give anything by mouth to an unconscious person.

**Self-protection of the first aider** Use personal protective equipment. Avoid contact with eyes, skin and clothing.

**Most important symptoms and effects, both acute and delayed**

**Notes to physician** Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

**Suitable extinguishing media**

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

**Specific hazards arising from the chemical**

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Chlorine. Fluorine. Carbon oxides.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to cool unopened containers.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Use personal protective equipment. Avoid contact with eyes, skin and clothing. Ensure adequate ventilation. Remove all sources of ignition.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Handling** Wear personal protective equipment. Avoid contact with eyes, skin and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not breathe vapours or spray mist. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Wash

thoroughly after handling.

#### Conditions for safe storage, including any incompatibilities

**Storage** Keep containers tightly closed in a cool, well-ventilated place. Keep out of the reach of children.

**Incompatible products** Strong oxidizing agents.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

#### Exposure guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ACETONE 67-64-1	TWA: 250 ppm STEL: 500 ppm	TWA: 750 ppm TWA: 1800 mg/m <sup>3</sup> STEL: 2400 mg/m <sup>3</sup> STEL: 1000 ppm TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup>	2500 ppm
PCBFT 98-56-6	TWA: 2.5 mg/m <sup>3</sup>	-	

#### Appropriate engineering controls

**Engineering measures** Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

#### Individual protection measures, such as personal protective equipment

**Eye/face protection** Chemical goggles or safety glasses with side-shields.

**Skin and body protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection** Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

<b>Physical state</b>	liquid	<b>Odor</b>	Strong Solvent
<b>Appearance</b>	clear	<b>Odor threshold</b>	No information available
<b>Color</b>	clear		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
pH		No data available
Melting point / freezing point	No data available	No data available
Boiling point / boiling range		No information available
Flash point	< 3 °C / < 37.00 °F	Seta closed cup
Evaporation rate		No data available
Flammability (solid, gas)	No data available	
Flammability Limit in Air		No data available



Upper flammability limit	13%	
Lower flammability limit	1%	
Vapor pressure	368.8	mmHg @ 20°C
Vapor density	2.3	
Specific gravity	0.83094	g/cm3
Water solubility	Insoluble in cold water	
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition temperature	No data available	No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity		No data available

**Other Information**

Density	6.93001 lbs/gal
Volatile organic compounds (VOC) content	NaN lbs/gal
Total volatiles weight percent	100 %
Total volatiles volume percent	100 %
Bulk density	No information available

**10. STABILITY AND REACTIVITY****Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Strong oxidizing agents

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Chlorine. Fluorine. Carbon oxides.

**11. TOXICOLOGICAL INFORMATION****Information on Likely Routes of Exposure**

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. May be harmful if inhaled.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Skin contact</b>	May cause irritation.
<b>Ingestion</b>	Harmful if swallowed.

Chemical name	LD50 Oral	LD50 Dermal	LC50 Inhalation
ACETONE 67-64-1	= 5800 mg/kg ( Rat )	> 15700 mg/kg ( Rabbit )	= 50100 mg/m <sup>3</sup> ( Rat ) 8 h
PCBFT 98-56-6	= 13 g/kg ( Rat )	> 2 mL/kg ( Rabbit )	= 33 mg/L ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** Irritating to eyes and skin.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** No information available.  
**Mutagenicity** No information available.  
**Carcinogenicity** Not classifiable as a human carcinogen.  
**Reproductive effects** No information available.  
**STOT - single exposure** May cause damage to organs  
**STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure  
**Target organ effects** Central nervous system, Eyes, respiratory system, Skin, liver, kidney.  
**Aspiration hazard** No information available.

**Acute Toxicity** 0 % of the mixture consists of ingredient(s) of unknown toxicity.  
**The following values are calculated based on chapter 3.1 of the GHS document .**

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

Harmful to aquatic life with long lasting effects

0 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
ACETONE 67-64-1		4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L LC50 6210 - 8120: 96 h Pimephales promelas mg/L LC50 static 8300: 96 h Lepomis macrochirus mg/L LC50	10294 - 17704: 48 h Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h Daphnia magna mg/L EC50
PCBFT 98-56-6		11.5 - 15.8: 48 h Lepomis macrochirus mg/L LC50 static	3.68: 48 h Daphnia magna mg/L EC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

Chemical name	log Pow
ACETONE 67-64-1	-0.24
PCBFT 98-56-6	3.7

**Other Adverse Effects**

No information available

## 13. DISPOSAL CONSIDERATIONS

**Waste treatment methods**

**Disposal Methods** It must undergo special treatment, e.g. at suitable disposal site, to comply with local regulations.

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

**US EPA Waste Number**

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes

ACETONE 67-64-1		Included in waste stream: F039		U002
--------------------	--	-----------------------------------	--	------

**California Hazardous Waste Status**

Chemical name	CAWAST
ACETONE 67-64-1	Ignitable

**14. TRANSPORT INFORMATION****DOT**

**UN/ID no.** 1090  
**Proper Shipping Name** ACETONE SOLUTION  
**Hazard Class** 3  
**Packing Group** II  
**Emergency Response Guide Number** 127

**Additional information**

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

**15. REGULATORY INFORMATION****International Inventories**

**TSCA** Complies  
**DSL/NDSL** Complies  
**EINECS/ELINCS** Complies  
**ENCS** Complies  
**IECSC** Complies  
**KECL** Complies  
**PICCS** Complies  
**AICS** Complies

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**United States of America****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372.

**SARA 311/312 Hazardous Categorization**

**Acute Health Hazard** Yes  
**Chronic Health Hazard** Yes  
**Fire Hazard** Yes  
**Sudden Release of Pressure Hazard** No  
**Reactive Hazard** No

Chemical name	Hazardous Substances RQs	CERCLA EHS RQs	RQ
ACETONE 67-64-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

**California Prop. 65**

None of the ingredients are listed with California Proposition 65.

**California SCAQMD Rule 443**

Does Not Contain Photochemically Reactive Solvent

**State Right-to-Know**

Chemical name	New Jersey	Massachusetts	Pennsylvania
ACETONE 67-64-1	X	X	X
PCBFT 98-56-6	X		

**16. OTHER INFORMATION**

<b>NFPA</b>	Health 2	Flammability 3	Instability 1	Physical hazard -
<b>HMIS (Hazardous Material Information System)</b>	Health 2	Flammability 3	Reactivity 1	

Prepared By Tnemec Regulatory Dept: 816-474-3400  
 Revision Date 02-Jun-2017


Revision Summary  
 1 9 5 6 7 10 8 11 14 15 13 4

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of SDS



# Safety Data Sheet

Issue Date 02-Jun-2017

Revision Date 02-Jun-2017

Revision Number 3

## 1. IDENTIFICATION

### Product identifier

**Product Code** F041-0086  
**Product Name** THINNER CLEAR

### Other means of identification

**Common Name** NO. 86 THINNER  
**UN/ID no.** 1263  
**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

**Manufacturer Address** Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372 816-474-3400  
**Distributor** Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Aspiration toxicity	Category 1
Flammable Liquids	Category 2

### Label elements

## EMERGENCY OVERVIEW

### **Danger**

### **Hazard statements**

Causes skin irritation  
Causes serious eye irritation  
May be fatal if swallowed and enters airways  
Highly flammable liquid and vapor



**Appearance** clear

**Physical state** liquid

**Odor** Solvent

**Precautionary Statements**

**Prevention**

Wash face, hands and any exposed skin thoroughly after handling  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment

**Response**

Get medical advice/attention if you feel unwell  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 If skin irritation occurs: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do NOT induce vomiting  
 In case of fire: Use CO2, dry chemical, or foam for extinction

**Storage**

Store locked up  
 Store in a well-ventilated place. Keep cool  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

**Other information**

May be harmful in contact with skin  
 Toxic to aquatic life with long lasting effects  
 SEE SAFETY DATA SHEET

Acute Toxicity 3 % of the mixture consists of ingredient(s) of unknown toxicity.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical name	CAS No	Weight-%
ALIPHATIC PETROLEUM DISTILLATES	64742-89-8	30 - <60%
PETROLEUM SOLVENT (NAPHTHA)	64742-95-6	10 - <30%
TRIMETHYLBENZENES	25551-13-7	10 - <30%
1,2,4-TRIMETHYLBENZENE	95-63-6	10 - <30%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

**4. FIRST AID MEASURES**

**Description of first aid measures**

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	Aspiration hazard. If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

**Most important symptoms and effects, both acute and delayed**

**Notes to physician** Treat symptomatically.

**5. FIRE-FIGHTING MEASURES****Suitable extinguishing media**

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

**Specific hazards arising from the chemical**

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon dioxide.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Use personal protective equipment. Avoid contact with eyes, skin and clothing. Ensure adequate ventilation. Remove all sources of ignition.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal

regulations.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Wear personal protective equipment. Avoid contact with eyes, skin and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not breathe vapours or spray mist. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not ingest. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

### Conditions for safe storage, including any incompatibilities

**Storage** Keep containers tightly closed in a cool, well-ventilated place. Keep out of the reach of children.

**Incompatible products** Strong oxidizing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
TRIMETHYLBENZENES 25551-13-7	TWA: 25 ppm	TWA: 25 ppm TWA: 125 mg/m <sup>3</sup>	

#### Appropriate engineering controls

**Engineering measures** Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

#### Individual protection measures, such as personal protective equipment

**Eye/face protection** Chemical goggles or safety glasses with side-shields.

**Skin and body protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection** Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	liquid	<b>Odor</b>	Solvent
<b>Appearance</b>	clear	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		



<u>Property</u>	<u>Values</u>	<u>Remarks</u>
pH		No data available
Melting point / freezing point	No data available	No data available
Boiling point / boiling range		No information available
Flash point	2.77 °C / 37.00 °F	Pensky Martens - Closed Cup
Evaporation rate		No data available
Flammability (solid, gas)	No data available	
Flammability Limit in Air		No data available
Upper flammability limit	NA	
Lower flammability limit	NA	
Vapor pressure	341.7	mmHg @ 20°C
Vapor density	26	No data available
Specific gravity	0.86958	g/cm3
Water solubility	Insoluble in cold water	
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition temperature	No data available	No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity		No data available

**Other Information**

Density	7.24003 lbs/gal
Volatile organic compounds (VOC) content	7.240 lbs/gal
Total volatiles weight percent	100 %
Total volatiles volume percent	100 %
Bulk density	No information available

**10. STABILITY AND REACTIVITY****Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Strong oxidizing agents

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon dioxide.

**11. TOXICOLOGICAL INFORMATION****Information on Likely Routes of Exposure**

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. Aspiration into lungs can produce severe lung damage.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Skin contact</b>	Irritating to skin.

**Ingestion**

Harmful if swallowed. Potential for aspiration if swallowed.

Chemical name	LD50 Oral	LD50 Dermal	LC50 Inhalation
ALIPHATIC PETROLEUM DISTILLATES 64742-89-8	-	= 3000 mg/kg ( Rabbit )	-
PETROLEUM SOLVENT (NAPTHA) 64742-95-6	= 8400 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	= 3400 ppm ( Rat ) 4 h
TRIMETHYLBENZENES 25551-13-7	= 8970 mg/kg ( Rat )	-	-
1,2,4-TRIMETHYLBENZENE 95-63-6	= 3280 mg/kg ( Rat )	> 3160 mg/kg ( Rabbit )	= 18 g/m <sup>3</sup> ( Rat ) 4 h

**Information on toxicological effects****Symptoms**

Simple asphyxiant. May cause suffocation by displacing the oxygen in the air. Exposure to oxygen-deficient atmosphere (<19.5%) may cause dizziness, drowsiness, nausea, vomiting, excess salivation, diminished mental alertness, loss of consciousness and death. Exposure to atmospheres containing 8-10% or less oxygen will bring about unconsciousness without warning and so quickly that the individuals cannot help or protect themselves. Lack of sufficient oxygen may cause serious injury or death. Irritating to eyes and skin.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure****Skin corrosion/irritation**

Irritating to skin.

**Irritation**

Irritating to skin.

**Sensitization**

No information available.

**Mutagenicity**

No information available.

**Carcinogenicity**

Not classifiable as a human carcinogen.

**Reproductive effects**

No information available.

**STOT - single exposure**

No information available

**STOT - repeated exposure**

Causes damage to organs through prolonged or repeated exposure kidney, liver, Central nervous system, Skin, Lungs, respiratory system.

**Target organ effects****Aspiration hazard**

Risk of serious damage to the lungs (by aspiration).

**Acute Toxicity**

3 % of the mixture consists of ingredient(s) of unknown toxicity.

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

Toxic to aquatic life with long lasting effects

3 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
ALIPHATIC PETROLEUM DISTILLATES 64742-89-8	4700: 72 h Pseudokirchneriella subcapitata mg/L EC50		
PETROLEUM SOLVENT (NAPTHA) 64742-95-6		9.22: 96 h Oncorhynchus mykiss mg/L LC50	6.14: 48 h Daphnia magna mg/L EC50
TRIMETHYLBENZENES 25551-13-7		7.72: 96 h Pimephales promelas mg/L LC50 flow-through	
1,2,4-TRIMETHYLBENZENE 95-63-6		7.19 - 8.28: 96 h Pimephales promelas mg/L LC50 flow-through	6.14: 48 h Daphnia magna mg/L EC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

Chemical name	log Pow
1,2,4-TRIMETHYLBENZENE 95-63-6	3.63

**Other Adverse Effects** No information available

### 13. DISPOSAL CONSIDERATIONS

**Waste treatment methods**

**Disposal Methods** It must undergo special treatment, e.g. at suitable disposal site, to comply with local regulations.

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

### 14. TRANSPORT INFORMATION

**DOT**

<b>UN/ID no.</b>	1263
<b>Proper Shipping Name</b>	paint Paint related material
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>Emergency Response Guide Number</b>	128

**Additional information** Call TNEMEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

### 15. REGULATORY INFORMATION

**International Inventories**

<b>TSCA</b>	Complies
<b>DSL/NDSL</b>	Does not comply
<b>EINECS/ELINCS</b>	Does not comply
<b>ENCS</b>	Does not comply
<b>IECSC</b>	Does not comply
<b>KECL</b>	Does not comply
<b>PICCS</b>	Does not comply
<b>AICS</b>	Does not comply

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical

or chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372:

Chemical name	SARA 313 - Threshold Values
1,2,4-TRIMETHYLBENZENE - 95-63-6	1.0

**SARA 311/312 Hazardous****Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**California Prop. 65**

:This product can expose you to the following chemicals which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Chemical name	California Prop. 65
PETROLEUM SOLVENT (NAPHTHA) - 64742-95-6	.

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Chemical name	New Jersey	Massachusetts	Pennsylvania
TRIMETHYLBENZENES 25551-13-7	X	X	X
1,2,4-TRIMETHYLBENZENE 95-63-6	X	X	X

**16. OTHER INFORMATION**

<b>NFPA</b>	Health 1	Flammability 3	Instability 0	Physical hazard -
<b>HMIS (Hazardous Material Information System)</b>	Health 1	Flammability 3	Reactivity 0	

Prepared By Tnemec Regulatory Dept: 816-474-3400  
 Revision Date 02-Jun-2017  
 Revision Summary  
 1 9 4 5 6 7 10 8 11 14 15

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of SDS**